

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 7 R. W. W. M.

FOX-CHAPMAN CO., EUGENE, ORE. 97196

Willard W. Haines #239 &  
Leo J. Martin #363  
For Harold Woolley  
Dec. 18, 1957  
Map File M 8 - 7

1/4 Section Corner to Section 13, T21S, R7W, & Sec. 18, T21S R6W.  
Set Lot Marker 1"X 1"X 36" Iron 1 Rods with brass caps inscribed,  
Wilford N. Haines #239  
Survey Point, Drain, Ore.

Scribed: 28" Fir, S.50°E. 32.0 ft. 16" Fir S50°W 9.8 ft  
12" Hemlock South 17.0 ft. 20" Fir N39°W 7.5 ft

*This info for 18/17-6*

*9-29-97  
D.C.S.C.*

19

Section Corner to Secs. 12 & 13, T21S R7W, & Secs 7 & 18, T21S R6W.

Found: Fir BT. N.20°W. 42.24 ft.  
Set Lot Marker, in Creek, scribed as above.  
Scribed: 40" Fir S.45°W. 23.3 ft.  
30" Fir N.45°E. 57.5 ft.

20

North 1/4 Corner to Section 4.

Set Lot Marker from Original BTs. to S. W.  
Scribed: 30" Fir S.08°W., 35.4 ft.

21

Closing Corner Section 33/34 North Boundary Section 4.  
Set Lot Marker from Original BTs.

*101*

22

Northeast Corner Section 4.

Set Lot Marker from Original B. T. to N. W.  
Scribed: 9" Cedar S.55°W. 31.3 ft.  
12" Fir S.46°E. 22.8 ft.

23

East 1/4 Corner to Section 4.

Set Lot Marker in Pile of Rocks.  
Carved: X in 1' x 2' Rock, S. 66°W., 11.5 ft.  
X in 3' x 4' Rock, N. 21°E., 15.4 ft.

24

Southeast Corner to Section 4.

Set Lot Marker from Original B.T.'s.

25

Southwest Corner to Section 4.

Set Lot Marker from Original B.T.

26

West 1/4 Corner to Section 4.

Found both Original B.T.'s  
Carved 6" X on Face of Bed Rock S.11°W, 29.7 ft.

27

1/4 Section Corner to Sections 26 & 27.  
Found - Both Orig. BT's.

*FD. OK 9/92  
L. ROBERTS M115-63*

Orig. 24", now 48" Fir Stump N.71°E. 40.9 ft., shows good scar near base, I do not open.

Orig. 60", now 68" Cedar West 35.6 ft., I open & find good scribing " 4". BT's check for bearing & distance.

Set Brass Cap at Corner Mkd: 1/4 S27/S26 T21S R7W County Surveyor's Office, 1958

New BTs: 20" Cedar bears N.18°E. 97.5 ft. scribed 1/4 S26 CS BT.  
8" Hemlock " S.39°W. 5.9 ft. scribed 1/4 S27 CS BT.

28

1/4 Section Corner to Sections 13 & 24. - *SHOULD BE IN T20/R7*  
Found - Orig. W.C. chisled "+ W C" on standstone ledge.

Found Stone that checks size of Orig. Corner Stone out of ground.  
At Corner, I do not find any chisled marks on Corner Stone nor any trace of Original BT's.

Set Brass Cap at Corner Mkd: 1/4 S13/S24 T20S R7W County Surveyor's Office, 1958.

New BT's: 12" R. Fir bears N.43 1/2°E. 20.0 ft. scribed 1/4 S13 CS BT.  
7" R. Fir bears S.55°E. 26.4 ft. scribed 1/4 S24 CS BT.

Wilford N. Haines & Leo J. Martin  
For Harold Woolley  
Filed Jan. 21, 1958  
Map File M 8 - 31

James W. Byron, Deputy  
M. Godfrey  
S. Bilow  
May 23, 1958  
C. S. File No. 49/20

Section Corner to Sections 8, 9, 14, & 17.

Found - Orig. 40", now 50" Fir S.35°E. 5.3 ft., shows good bark scribing.

*See Corner #30*