

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 7 R. W. W. M.

NOKE-CHAPMAN CO. EUGENE, ORE. 21881

James W. Byron, Deputy  
Milo Godfrey  
C. Putnam  
July 9, 1959  
C.S. File No. 49/20

1/4 Section Corner to Sections 15 & 16. 34  
Found - Point of Rotted Oak Stake at Corner.  
40" Fir N.68°E. 12.5 ft., chopped open & found scribe "S".  
48" Fir S.72°W. 18.5 ft.  
At Corner Set Iron Pipe with Brass Cap Mkd. "County Surveyor's Office,  
1959 T21S R7W 1/4 S16/S15.  
Blaze & Scribe following Trees:  
11" Hemlock N. 8 1/2°W. 35.5 ft. Mkd. "1/4 S16 CS BT." 72  
18" Fir S.48 1/2°E. 12.8 ft. Mkd. "1/4 S15 CS BT."

1/4 Section Corner to Sections 16 & 21. 35  
Found - Fir tree, now 54", N.64°E. 8.6 ft., old bark scribing  
found "BT 1/4 S".  
No trace of other old B.T.  
At Corner Set Iron Pipe with Brass Cap Mkd., "County Surveyor's  
Office, 1959"  
1/4 S16  
S21

Blaze & Scribe following Trees:  
12" Hemlock N.78°W. 27.4 ft. Mkd. "1/4 S16 CS BT".  
14" Hemlock S. 3°E. 34.2 ft. Mkd. "1/4 S21 CS BT."

10/6/59  
C.S. File  
No.  
49/20

Same  
as  
Above.

1/4 Corner to Sections 15 and 22. 36  
Found - Hemlock Snag, now 36", N.63°E. 4.6 ft. This Snag had  
been chopped open to expose scribing "BT", plainly visible.  
Rotted Remains of Maple S.30°W. 33 ft., chopped open &  
found fragmentary but unmistakable scribe marks.  
At Corner Set Iron Pipe with Brass Cap Mkd: "County Surveyor's Office,  
1959  
T21S R7W 1/4 S15  
S22  
Blaze & Scribe New BT's: 10" Hemlock N.21°E. 37.4 ft. mkd. 1/4 S15 CS BT.  
15" R.Cedar S.81°W. 47.3 ft. mkd. 1/4 S22 CS BT.

1/4 Corner Sec. 1, T.21S. R.7W. & Sec. 6, T.21S. R.6W. 37  
Set 1" x 1" x 36" T. Iron from Orig. BT's.

Section Corner to Sec. 1 & 12, T21S R7W & Sec. 6 & 7, T21S R6W. 38  
Set 1" x 1" x 36" T. Iron from Orig. BT's.

1/4 Corner to Sec. 12, T21S R7W, & Sec. 7, T21S R6W. 39  
Set 1" x 1" x 36" T. Iron from Orig. BT's.

1/4 Corner to Sec. 24, T21S R7W, & Sec. 19, T21S R6W. 40  
Set 1" x 1" x 36" T. Iron.  
Scribed: 12" Fir N.50°E. 18.6 feet  
40" Fir N.17°E. 41.1 feet.

Section Corner to Secs. 24 & 25, T.21S. R.7W. & Secs. 19 & 30, T21S R6W. 41  
Set 1" x 1" x 36" T. Iron.  
Scribed: 8" Fir N.56°W. 11.7 feet.  
6" Fir N.29°E. 7.4 feet.  
8" Fir S.01°E. 1.7 feet.  
8" Fir S.78°W. 17.8 feet.

1/4 Corner Sec. 25, T21S R7W, & Sec. 30, T21S R6W. 42  
Set 1" x 1" x 36" T. Iron.  
Scribed: 10" Fir N.08°W. 2.7 feet.  
10" Fir S.46°E. 2.1 feet

Section Corner to Secs. 24 & 36, T21S R7W (continued over)  
Set 1" x 1" x 36" T. Iron.

Renewed Corners & retracement of Range Line.  
By Wilford N. Haines  
Filed Feb. 18, 1960  
C. S. File No. 51/67