

Douglas County Surveyor's Record of
Government Corners Renewed

21

T. S.

7

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Secs. 25 & 36, T21S R7W. & Secs. 30 & 31, T21S R6W. 43

Set 1" x 1" x 36" T. Iron.
Scribed: 36" Fir N.72°W. 53.3 feet.
30" Fir N.40°W. 60.6 feet.
6" Hem. N. ~~02°E~~ 41.7 feet.
582°E N.E.G.

1/4 Corner to Sec. 36, T21S R7W. & Sec. 31, T21S R6W. 44

Found old BT's., very rotten.
Scribed: 40" Fir N.53°W. 28.4 feet.
6" Hem. N.31°W. 16.8 feet.

Twp. Corner to Sec. 36, T21S R7W, Sec. 31, T21S R6W, Sec. 6, T22S R6W. 45
and Sec. 1, T22S R7W.

Set 1" x 1" x 36" T. Iron from old BT's. 86

Sec. Corner to Secs. 35 & 36, T21S R7W. & Sec. 1 & 2 T22S R7W. 46

Found Orig. BT's: Fir S.36°W. 32 lks.
Maple S.15°E. 20 lks.
Set 1" x 1" x 36" T. Iron. 62

See also #16

Section Corner to Sections 25, 26, 35, and 36. 47

Found - 40" Fir, now 52", N.50°W. 114 lks.
Set 1" x 1" x 36" T. Iron from which:
Scribed: 10" Fir S.15°W. 25.0 ft.
12" Fir S.69°E. 28.7 ft.
5" Fir N.42°E. 26.4 ft.
4" Fir N.12°W. 19.7 ft.

FD. B.L.M. CAP
12/91 BY BAKER
M 114-26

Section Corner to Sections 23 & 26. 48

Found both Original BT's.
Set 1" x 1" x 36" T. Iron. 51

Section Corner to Sections 13, 14, 23, and 24. 49
FD OK BYWARD 4/99 M131-54

Found - B.T. S.58°W. 34 lks.
Set - 1" x 1" x 36" T. Iron
Scribed - New B.T. N.14°E. 25.7 feet, (Fir?)

Section Corner to Sections 22 - 23 - 26 - 27. 50

Set 1" x 1" x 36" T. Iron from Orig. N.W. BT. (Now down)
Scribed New BT's: 10" Hemlock S.30°W. 63.7 ft.
16" Hemlock S.72°E. 60.9 ft.

1/4 Corner Section 23 & 26. 51

Found 1" x 1" T. Iron & 2 Orig. B.T.'s: - Ren. # 48
40" Fir Snag South 64 lks.
12" Maple N.45°E. 37 lks.
Scribed New BT's: 12" Fir S.37°W. 10.0 ft.
20" Fir N.11°W. 58.8 ft.

Section Corner to Sections 21 - 22 - 27 - 28. 52

Found - 3 Orig. Fir B.T.'s.
Set - 1" x 1" x 36" T. Iron for Corner.

Section Corner to Sections 1 - 2 - 11 - 12. 53

All the Orig. BT's. have been dead for many years. None had healed over.

Found - 10" Fir N.33°W. 28 lks. (now stub 1 ft. ht., no scribe)
16" Fir N.11°E. 19 lks. (now down & rotten)
16" Fir S.56°W. 47 lks. (now stub 1 ft. ht. fd. scribe "BT")
16" Fir S.52°E. 11 lks. (now down, fd. scribe T21S R7W)

Set 1" x 1" x 36" T. Iron - Mkd: X B.O. on Rock face 20 ft. wide x 8' ht. S.17 1/2°W. 25.4'
Scribed - 14" Hemlock N.43 1/2°E. 10.8 ft.

Renewed Corner & Retracement of Range Line between 7 & 6.
By Wilford N. Haines
Filed Feb. 17, 1960
C. S. File No. 51/67

F.B. H-7L

Wilford N. Haines
For E.G. Whipple & Woolley Logging
February 1961
Map File M 20 - 19

W. Haines
May 1961
C.S. File
51/67

Same as
COR #54

RE-RENEWED, SEE CORNER NO. 51

RE-RENEWED, SEE CORNER NO. #116

RE-RENEWED, SEE CORNER NO. 94