

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 7 W. R. W. W. M.

KOHLCHAPMAN CO., EUGENE, ORE. 21981

65

Section Corner to Secs. 32 & 33, T21-7W. & Secs. 4 & 5, T22-7W.  
Found - Fir, now 60", S.45°W. 28.4 ft., chopped open & found good  
scribing on old face.  
Badly burned Cedar Snag S.30°E. 14.0 ft. No scars or scribng found.  
Fir Snag, N.55°E. (instead of N.65°E) 4.0 ft. Shows very old  
axe marks on bark. No scribing found.  
No trace of Original Fir BT. to N.W. No trace of Nicklin's  
N.E. or N.W. BT's. No trace of Rock set by Nicklin.  
Set - Brass Cap at Corner Mkd: County Surveyor's S32 | S33 T21S R7W  
Office, 1962 S 5 | S 4 T22S  
New BT's: 10" Hemlock N.63°W. 11.1 ft. Mkd: T21S R7W S32 CS BT.  
6" W.Fir S.34°W. 14.3 ft. Mkd: T22S R7W S 5 CS BT.  
5" Hemlock S.23°E. 14.2 ft. Mkd: T22S R7W S 4 CS BT.  
32" D.Fir N.65°E. 57.2 ft. Mkd: T21S R7W S33 CS BT.

Milo E. Godfrey, Deputy  
Vernon Tracy & Mike Stone  
July 10, 1962  
C. S. File No. 52/14

E. S.  
File  
No. 52/14

1/4 Corner to Sec. 31, T21-7W. & Sec. 6, T22-7W.  
Found - Fir, now 40", N.49°W. 31.7 ft. very faint bark scribing  
visible "S" & part of "B".  
Fir Snag bears S.37°W. 42.2 ft., bark all gone & big hole  
burned in N.E. side. No marks found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R7W 1/4 S31  
Office, 1962 T22S S 6  
New BT's: 16" D.Fir N.75°E. 10.2 ft. Mkd: 1/4 S31 CS BT.  
10" D.Fir South 31.6 ft. mkd: 1/4 S6 CS BT.

66

Aug. 3, 1962

Wilford N.  
Haines.  
Renewal  
Oct. 1962  
C. S. File  
No. 51/222

Section Corner to Sections 27 - 28 - 33 - 34. *FD. OK BY L. ROBERTS  
5/99 M131-62*  
Found - 10" Fir Corner Tree & Orig. BT's:  
10" Fir, now 24", N.40°E. 33 lks. 21.78 ft. rescribed on N. side.  
20" Fir N.64°W. 6 lks. = 3.96 feet. (Gone)  
New Trees Scribed: 5" Fir S.19°W. 3.1 feet.  
4" Fir N.65°W. 5.6 feet.  
No suitable Tree in Section 34.  
Corner tree is now dead & almost all burned.  
Set - 1" x 1" x 36" T. Iron in Center of Shell.

67

Corner to Sections 5 and 4 only.  
Found - 70" Fir Snag S.37°W. 13.2 ft., faint bark scribing visible.  
36" Cedar (uprooted, down & dead) S.34°E. 32.3 ft. Cut open & fd. scribng.  
No trace of Maple to N.E. - 30" Hemlock N.24°W. 13.0 ft., old  
scribing visible in prev. opened scar, "BT S33T20", looks like  
original, but no record of this tree.  
24" Red Cedar N.84°W. 21.1 ft., recent scribing found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R7W S 5/S 4  
Office, 1962  
New BT's: 5" D.Fir S.79°E. 19.3 ft. Mkd: S4 CS BT.  
Rescribe 70" Fir Snag S.37°W. 13.2 ft. (in bark) T21SR7WS5 CS BT.  
Haines' "T" Iron bears N.17°W. 4.0 ft. Corner is on level ground  
approximately 75 ft. East of Smith River Road.

68

Corner to Sections 32 and 33 only, T20-7W.  
Found - Haines' "T" Iron & Cap, not recorded.  
15" Fir Snag S.27°W. 12.5 ft. scribing visible "T21S R7W S5 BT".  
No trace of N.E. or N.W. BT's.  
DID NOT SET BRASS CAP  
New BT's: 6" Hemlock N.57 1/2°E. 45.7 ft. Mkd: S33 CS BT.  
8" Hemlock N.58°W. 24.6 ft. Mkd: T20S R7W S32 CS BT.  
Corner lies on steep N.W. slope approx. 500 ft. south of road.

69

1/4 Corner to Sections 6 and 5.  
Found - 4" sq. wooden stake at corner. - The Fir S.80°E. 6.6' is down, dead  
& burned, also bulldozed out of position. Part of old face exposed  
& mks. burned off. Chop open & find good scribe on upper edge of  
old face. Tag on tree dated same date & name as on stake at cor.  
Portion of root in gr. that checks bear. & dist. from corner.  
No trace of N.W. BT. Entire area around corner logged off and  
burned, fire trail on both East & West of Corner.  
(continued over)

70

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy and Mike Stone  
Oct. 31 and November 8, 1962

49/89

C. S. File No.

C.S. File No. 49/20

RE-RECORDED # 110