

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 7 W. R. W. W. M.

(continued)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

T21S R7W 1/4 S6/S5

New BT's: 10" Hemlock S. 69 1/2° W. 53.7 ft. Mkd: 1/4 S6 CS BT.

11" Hemlock S. 30 1/2° W. 84.1 ft. Mkd: 1/4 S6 CS BT.

No trees available East of Corner.

Godfrey & Crew  
Oct. 31, 1962  
C.S. File  
No. 49/20

Section Corner to Sections 4 - 5 - 8 - 9. 71

Found - Cedar, 40" diam., S. 60° E. 26.4 ft., previously opened,  
scribing visible on old face, "BT S9 T21S R7W".

45" Cedar N. 50° W. 12.5 ft. (19 lks. not 29 lks.)  
shows scar. Did not open.

No trace of N.E. or S.W. BT's.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

T21S R7W 

S 5	S 4
S 8	S 9

Reblaze & scribe 2 Orig. BT's:

40" Cedar S. 60° E. 26.4 ft. Mkd: T21S R7W S9 CS BT.

45" Cedar N. 50° W. 12.5 ft. Mkd: T21S R7W S5 CS BT.

New BT's: 12" D. Fir N. 79° E. 79.1 ft. Mkd: T21S R7W S4 CS BT.

No suitable tree available S.W. of corner.

Godfrey &  
Crew  
Nov. 9, 1962  
C.S. File  
No. 49/20

1/4 Corner to Sections 16 and 15. 72

Found - 40" Fir N. 68° E. 12.5 ft. (Orig. BT. found in 1959)

Tree alive & in good condition.

18" Fir S. 48 1/2° E. 12.8 ft., mkd. in 1959, scar pitched  
over & nearly healed.

58" Fir to the S. W. (Orig. BT.) is uprooted & down.

Hemlock to the N.W. marked in 1959 is gone.

Did not find Brass Cap set in 1959 (See Ren. No. 34)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

T. 21S R7W 1/4 S16/S15

New BT: 13" Hemlock S. 30° W. 37.3 ft. Mkd: 1/4 S16 CS BT.

Note - Corner lies approx. 100 ft. north of ridge top.

Milo E.  
Godfrey  
& Crew  
Dec. 20, 1963  
C.S. File  
No. 49/20

1/4 Corner to Sections 27 and 34. 73

No trace of Original Corner.

Set - 1" x 1" x 36" T. Iron from which:

Scribed - 10" D. Fir N. 37° E. 5.0 feet.

7" D. Fir S. 67° E. 5.7 feet.

1/4 Corner to Sections 34 and 35. 74

Set - 1" x 1" x 36" T. Iron from

Original Fir Bearing Tree.

Center 1/4 of Section 34. 75

Set - 1" x 1" x 36" T. Iron from which -

Scribed - 40" D. Fir S. 80° W. 48.2 feet

20" D. Fir N. 04° W. 44.0 feet.

Sec. Cor. to Secs. 12 & 13, T21-7W. & Secs. 7 & 18, T21-6W. 76

Found - Haines' "T" Iron at Corner in Creek Bed. See Ren. No. 20.

30" Fir N. 45° E. 57.5 ft., Haines' bark scribing visible.

Tree standing & alive.

Orig. BT., 20" Fir N. 20° W. 42.2 ft., uprooted & down, old  
blaze prev. opnd., scrbing. vis. on old face, "BTS12T21R7W".

Haines' S.W. BT., 40" Fir S. 45° W. 23.2 ft. also uprooted & down.

Set - Wit. Cor. 23' E. of Cor. (Sec. Line runs right in creek bed).

Brass Cap at Cor. Mkd: County Surveyor's Office, 1964

23' W. to Corner. Office, 1964 

T21S W C S12	S 7
R7W S13	S18 R6W

Haines' N.E. BT. to Sec. Cor. - 30" Fir (bark scbd.) bears N. 20' E. 45.4'  
from Wit. Cor., not rescribed.

New BT's: 9" Hemlock N. 14° W. 75.0 ft. Mkd: T21S R7W S12 CS BT.

36" Red Cedar S. 22° W. 125.6 ft. Mkd: T21S R7W S13 CS BT.

Witness Corner is in West Edge of Logging Road.

Wilford N. Haines  
For Woolley Logging Co.  
1963  
Map File M 27 - 32

Milo E. Godfrey, Deputy  
Stoffel - Stone - Halterman  
March 3, 1964  
C.S. File No. 49/143