

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Sections 7, 8, 18, and 17 Ren. # 29 **105**  
Found: 10" now 11" dia. fir scribed "S 8 T21S R7W" partially healed over, tagged  
partially uprooted and leaning heavily,  
8" now 9" dia. Fir has good blaze-did not open, tagged.  
8" dia. chinquapin scribed "S 17 T21S R1W CS BT" Tagged  
33" now 33 1/2 inch dia. fir has good blaze- did not open- tagged  
18" now 18 1/2" dia. fir has good blaze did not open-tagged  
8" now 30" dia. fir is down, has been opened and is rotted. Tagged  
Renewal: Set Brass cap at section corner marked:

L.E. Monrean  
P.L. Earle  
J.H Cook  
10/28/75  
CS 57/36

County Surveyor's Office  
1975

T21S	R7W
S 7	S 8
S18	S17

Bearing Trees:

11" dia. Fir (see Found#1) Scribed "S 8 T21S R7W CSBT" bears N6°E., 17.0ft.  
( record N 7 1/2°E., 17.3 ft.)  
9" dia Fir (see Fd.#2) scribed "S7 CS BT" bears N 40°W., 34.9ft. (record  
N 40°W., 34.4 ft.)  
8" dia chinquapin (see Fd #3) scribed "S 17 T21S R7W CS BT" bears S 80°  
E., 23.0 ft. (record per renewal S 78°E., 23.0 ft; record per Gov't.  
survey N88°E., 27.1 ft.)  
33.5" dia. fir (see fd.#4) scribed "T 21 S, R7W, S 17 BT" bears S59 1/2°E.,  
80.8 ft. (Record per Gov't survey S64°E., 79.7 ft)  
18.5" dia. Fir (see fd.#5) scribed "T21S, R7W, S7 BT" bears N52°W., 42.6  
ft. (record per Gov't survey N 46°W., 42.9 ft.)  
30" dia. Fir (see fd #6) bears N23°W., 11.5 ft. (orig. N19°W., 16.5 ft.)  
No new bearing trees scribed as sec. 18 has no substantial trees in area of  
corner. Corner lies approx. 60' easterly of BLM Rd. #21-7-22: line crossing  
tag on westerly side of Road. Corner lies near the top of slide area. The  
corner and all accessories lie on a westerly slope with signs of severe  
shifting

**106**

1/4 corner section 15 and 22 REN#36  
Found-I Pipe with brass cap attached, firmly set and marked as described by  
the county surveyor in 1959.  
We find the original NE Bearing as described in Ren#36. It bears N63°E , 4.6ft.  
The orig. SW bearing tree has been destroyed.  
We find the CS BT's as follows:  
A 10" now 14" hemlock bears N21°E, 37.4 ft. alive and well healed.  
A 15" R.cedar, now a stump bears S81°W., 47.3 ft. partially buried in logging  
debris. We mark a new Bt  
New BT- A 12" maple stump with numerous sprouts growing from its top, bears  
S22°W., 17.3 ft. scribed "1/4 S22 CS BT" on a double blaze.  
Note: this corner lies along an E-W cutting line at the north edge of an  
existing clearcut. approx. 250 ft north and 75 ft. lower than a paved BLM  
access road. Compass declination setting 20°E. 12/3/75

Gary L Langlitz  
Clell E Goodwin  
A Vic Cangie  
M Lenora Ladig  
12/3/75  
C.S. 57/39

**107**

Sec. Cor. for Secs. 18, 17, 19 and 20.  
Found - 1967 BLM brass cap 6 ins. above ground and properly marked.  
A 13" Hemlock now 15" bears N.33°E., 24.8 ft. (Rec. N.26°E., 25.7 ft.)  
with single partially healed blaze marked "T21S R7W S17 BT".  
A 38" Fir, now 40" bears S.73°E., 74.6 ft. with single well healed  
blaze.  
A 12" Hemlock now 14" bears S.36 1/2°W., 13.2 ft. (Rec. S.34°W.,  
13.9 ft.) with single partially healed blaze marked "T21S R7W  
S19 BT".  
A Hemlock stump, 15" now 18" bears N.26°W., 38.3 ft. (Rec. N.29°W.)  
with bottom of single partially healed blaze "W S18 BT".  
New BT - A 8" Hemlock bears N.87°W., 5.4 ft. single blazed and marked  
"T21S R7W S18 CS BT".  
Note: Corner is in SE corner of clearcut unit.

R. B. Kimberl  
P. L. Earle  
Doug. Co. Surveyors  
Office  
July 27, 1977  
C.S. 59/38

**108**

Section corner for Secs. 17, 18, 19, and 20.  
REFERENCED CORNER  
Found - 1967 BLM brass cap as per ren. #107.  
All BT's are stumps now due to logging in progress.  
Did find a 12" Hemlock, now 13", (Rec. 14") bears S.34°W., 13.7 ft.  
Rec. S.34°W., 13.9 ft.) (Ren. #107, S.36 1/2°W., 13.2 ft.)  
Set - A 5/8" I.R. under BLM brass cap 1.5 ft. under ground.  
A 48" Fir stump bears N.69°W., 26.4 ft. to a PK nail set in notch in Easterly face of  
stump. A 26" Cedar stump N.56°E., 26.5 ft. to PK nail set in top.

L. E. Monrean, Deputy  
Doug. Co. Surveyors  
Karen Reed - Karen  
Mosely  
April 22, 1980  
C.S. 61/6

Cor. Fd. at 12/1/81  
G. Quisenberry - Doug. Co.  
C.S. 61/29

SEE CORNER NO. #108