

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 21 S. T.S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

**109**

Les Roberts  
For: Int. P. Co.  
M 90 - 21  
May 30, 1982

Center 1/4 Corner for Sec. 30.  
Set - 2-1/2" B.C. in sandstone face.  
New BTs- 18" fir bears N.38°W., 40.4-ft. (scribed)  
27" fir bears S.67°W., 21.6-ft. (scribed)

5/30/82

**110**

Les Roberts  
L.S. #1039  
For: Int. Paper Co.  
M 92 - 37  
June 15, 1982

1/4 Corner common to Secs. 6 & 5.  
Fd. - 1962 Doug. Co. B.C. Ren. # 70  
BTs - 17" hemlock bears S.30°W., 83.7-ft. (Scar visible). (both 1962BTs).  
18" hemlock bears S.69°W., 53.7-ft. (Scar visible).  
New BTs- 12" fir bears S.73°E., 21.3-ft. (scribed). 6/15/82

**111**

1/4 Corner common to Secs. 6 & 7.  
No evidence found of orig. corner.  
Set - 1-1/2" x 36" I.P. with B.C.mkd.w/S-T-R, Date & PLS No.1039.  
New BTs- 18" hemlock bears S.86°E., 22.0-ft. (scribed).  
21" hemlock bears N.7°W., 24.4-ft. (scribed).

6/15/82

**112**

Section corner for Sec. 6; and Sec. 31 only. (NW cor. Sec. 6)  
Found - Std. GLO 2 1/2" I.D. iron pipe projecting 8" above ground with  
a 3 1/4" brass cap properly marked.  
12" fir, down with blaze bears East 60 lks.  
27" fir, down with blaze burnt out, N.38°E., 55 lks.  
31" rotten fir stump bears N.55°E., 28.45 ft. burnt bad with  
tree alongside.  
New BTs - 8" D. fir bears N.43°W., 5.5 ft. scribed T20S R8W S BT.  
6" D. fir bears N.39°E., 27.5 ft. scribed T20S R7W S31 BT.  
Set - 5/8" x 30" rebar with yellow plastic 1 1/4" dia. cap marked  
"Branch Eng. L.S. 1137" flush with the ground.

**113**

1/4 Corner for Section 31 only of T.20-7.  
Found - 70" fir laying 30 ft. down hill from root hole. Tree has burnt  
blaze with no visible scribing.  
Set - At record S.30°W., 23.1 ft. from root hole, I set a 2 1/2" I.D.  
alum. pipe protruding 6" above the ground with 3 1/4" alum.  
cap marked "T20S R7W 1/4 S31 1983 PLS 1137".  
New BTs - 7" alder bears N.27°E., 11.1 ft. bark scribed 1/4 S 31 BT.  
8" alder bears S.26°W., 34.3 ft. scribed 1/4 S6 BT.

**114** (In T.20-7)

Section corner for Secs. 31 and 32 only of T.20-7.  
Found - T-iron with cap marked "Survey marker Haines Drain, OR. (Ren. #21)  
36" fir stump bears N.35°E., 9.0 ft. with no scribing  
Burnt out stump with no visible markings bears S.81°W., 27.7 ft.  
Set - Std. I.P. Co. 2 1/2" I.D. alum. pipe protruding 6" above ground  
with 3 1/4" alum. pipe marked "T20S R7W S31 S32 T21S R7W S6  
1983 PLS 1137.  
New BTs - 36" D. fir bears S.16°W., 54.7 ft. scribed T21S R7W S6 BT.  
Set 1/2" x 6 ft. rebar 30" in ground with BT sign attached bears  
N.63°W., 10.8 ft.  
5/8" x 30" rebar with 1 1/4" yellow plastic cap marked "Branch  
Eng. LS 1137" in top of BT stump bears N.35°E., 9.0 ft.

**115**

Section corner for Secs. 5 and 6 only. (NE of Sec. 6)  
Found - "T"-iron, no record, with cap marked "Survey Marker W. Haines  
Drain, OR".  
Set - At the same point and with the "T" iron inside, Set 2 1/2" alum.  
pipe protruding 6" above ground with std. I.P. Co. 3 1/4"  
alum. cap marked T20S R7W S32 S6 S5 T21S R7W 1983 PLS 1137.  
New BTs - 16" D. fir bears N.3°E., 33.7 ft. scribed T20S R7W S32 BT.  
17" chinquapin bears S.32°W., 5.8 ft. scribed T21S R7W S6 BT.  
18" D. fir bears S.25°E., 43.6 ft. scribed T21S R7W S5 BT.

(SEE AFFIDAVIT STATEMENT FILED 2/10/84 FROM WILFORD HAINES REGARDING  
ABOVE CORNER.) (C.S. 58/290)

Donald L. Branch, L.S. 1137  
Branch Engineering, Springfield, OR  
For: International Paper Co.  
November 1983  
M 95 - 66