

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

- CONTINUED FROM PREVIOUS PAGE -

1/4 corner for Sec's. 12, & 13. 28
Found - Brass Cap (GLO) 1954 - 1960 RESURVEY.
BT's - 13" Cedar bears S.40°W., 28.6-ft. (scar visible) 1954 BT
27" Hemlock bears N.38 1/2 °E., 32.0-ft. (scribe vis.) 1954 BT
6/26/81

1/4 corner for Sec's. 1, & 12. 29
Found - Brass Cap (GLO) 1954 - 1960 RESURVEY.
BT's - 36" Cedar stump bears N.49 1/2 °W., 16.3-ft. (burned face) 1954 BT
60" Fir stump bears S.17 1/2 °E., 18.4-ft. (scribe vis.) 1954 BT
6/26/81

1/4 corner for Sec's. 12, & 7. 30
Found - Brass Cap (GLO) 1954 - 1960 RESURVEY.
BT's - 14" Hemlock stump bears S.76 1/2 °W., 14.7-ft. (scribe vis.) 1954 BT
6/26/81

1/4 corner for Sec's. 12, & 11. 31
Set - 1 1/2 " x 36" Iron Pipe & Brass Cap.
New BT's- 18" Fir stump bears S.55°W., 103.1-ft. (scribed)
24" Fir stump bears N.85°E., 57.0-ft. (scribed)
34" Fir stump bears S.46°E., 98.6-ft. (scribed) 6/26/81

1/4 Corner for Secs. 10 and 15 32
Found - 1" iron pipe with GLO brass cap "1954".
21" Cedar stump, N.5°W., 71.5 ft. (scribe visible-1954 BT)
New BT - 8" fir, N.4°W., 45. 2 ft. (scribed 1/4 S10 BT)

Center 1/4 Corner for Section 10 33
Set - 2 1/2" x 31" alum. monument marked "T21S R8W C1/4 S10 PLS 1978
1984". Magnet in base.
BTs - 23" fir, S.78°E., 51.6 ft. scribed C 1/4 S10 BT.
27" fir, S.20 1/2°W., 9.5 ft. scribed C 1/4 S10 BT.

1/4 Corner for Sections 3; and Sec. 34 of T.20-8 34
Found - 24" fir stump, N.17°E., 10.5 ft. (scribe visible-1950 BT)
28" fir stump, S.6 1/2°W., 12.5 ft. (cut below scribe-orig. BT.)
Reset - 1" iron pipe with GLO brass cap, "1950" at slope distance from
existing BTs.)
1/2" rebar driven in center of BT stumps and 4" x 4" post found
east, 0.5 ft. from corner point.)

1/4 Corner for Secs. 3 and 4. 35
Found - 1" iron pipe with GLO brass cap "1945".
42" fir stump, S.63 1/2°E., 31.6 ft., closed face, 1945 BT.
21" fir stump, N.45 1/2°W., 23.7 ft., closed face, 1945 BT.
New BTs - 7" fir, N.70°E., 18.2 ft. scribed 1/4 S3 BT.
7" fir, N.60 1/2°W., 14.5 ft. scribed 1/4 S4 BT.

South 1/4 corner for Section 34 only. Ren. #9 36
Found - A 1952 G.L.O. brass cap set firmly in the ground, marked W.C.
30" corner tree bears West 1.98'.

24" Fir stump bears N54°E, 25.2' (Scribe Vis.) 1952 BT
Record N54 1/2°E, 25.7'.
New BT - 8" Fir bears N17°W, 12.6' (scribed/painted red)
Note - Set metal fence post, with survey attention sign wired to
beside brass cap. Corner lies on South slope about 50' South
of old dirt logging road. All Distances and bearings are
From brass cap.

Les Roberts
For: International Paper Co.
June 26, 1981
M 88 - 22

Daniel W. Baker L.S.# 1978
For: International Paper Company
October 25, 1984
M 97 - 51 C.S. 58/289

Les Roberts
International Paper
June, 1986
M 102 - 18