

Douglas County Surveyor's Record of
Government Corners Renewed

21 T. S. 9 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Closing Corner to Sec 4 & 5 T 22 R 9 only:

28

Found - 14 12 X 6 " sand stone, CC marked on one side, s grooves on one side, stone badly weathered and laying on surface.

Old BT's-A Fir, 26 (now 39) " dia. bears N 20 1/2°E., 27.7 ft. Scribed "CC T22S R9W S" Blaze partially opened and burned.

A fir stump, 28 (now 39) " dia. bears S 71 1/2°E., 69.7 ft. (rec. 68.0 ft) partial blaze below cutting linescribed "BT" (blaze not orig. as face of blaze falls well outside of record dia.)

A fir 8 (now 35) " dia. bears S 53 1/2°W., 115.5 ft. (rec. S 52°W). Tree has good blaze.

Set - Brass cap at Closing corner stamped "COUNTY SURVEYORS OFFICE" 1975

T 21 S R 9W
S 32

S 5 | S 4

CC

T 22 S R 9W

Orig. corner stone on north side of cap with CC on south face.

Note: Corner lies on top of ridge running west. 11/20/75

L.E Monrean
P.L.E.
11/20.75
CS 57/39

JAN 76
1-79
Center 1/4 Corner Sec. 20

Set - 1 1/2" Iron Pipe and Brass Cap
BT's - 10" Hemlock bears N.47°W., 15.8 feet.
8" Hemlock bears S.80°W., 17.5 feet.

Note - Corner was set at the intersection of the N - S and E - W center lines.

1/4 Corner Secs. 17 and 20

Set - 1 1/2" Iron Pipe and Brass Cap
BT's - 22" Fir bears S.86°E., 5.3 feet.
16" Fir bears N.13°W., 19.9 feet.
Note - Corner was set by single proportionate measure.

Sec. Corner Secs. 17, 18, 19 and 20

Found - 20" x 14" x 8" notched stone (original)
20" Fir stub bears N.34°W., 17.2 feet (1894 BT)
18" Maple bears S.9°E., 17.2 feet (1894 BT)

Set - 1 1/2" Iron Pipe and Brass Cap, buried stone beside pipe.
New BT's - 38" Fir bears N.34°W., 36.7 feet.
34" Fir bears S.35°W., 28.6 feet.
32" Fir bears N.34°E., 8.3 feet.

1/4 Corner for Section 1 only of T.21-10

Found - 3/4" inside diam. concrete filled iron pipe badly rusted with brass cap stamped "1/4 S1 1919. Monument is broken into 3 pieces with lower portion remaining firmly set, protruding 3" above ground.

1919 BT, a 14" D. Fir now a 30" stump 36" high bears S.67°W., 22.1 ft. (rec. 23.1 ft. checks on slope measurement). We open portion of blaze and find scribing "1/4".

1919 BT, an 11" D. Fir now a 14" stump 14" high bears N.78°W., 13.8 ft. (rec. N.10°W., 14.5 ft.) We open blaze and find scribing "BT".

The only logical determination we can make at this time is that the compass bearing of N.80°W., (being 10° off of cardinal west) was possibly misread. As the stump is leaning, a bearing of N.80°W., a distance of 14.5 ft. would be reasonable course to center of tree at blaze height. The blaze and scribing faces monument position. No evidence of tree was found at record bearing and distance.

Set - A 1" x 30" iron pipe with attached brass cap stamped "Douglas County Surveyor" T21S R10W S1 1/4 1981, is set at corner position. Monument is set with cap 4" above ground. Placed pieces of old monument along north and south side underground.

L.E. Monrean
Deputy, Doug. Co. and Surveyors Office
Witnesses: S.J. Flause; K.S. Mosely.
April 2, 1981
C.S. 61/19