

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 9 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21891

38

Larry Monrean, Deputy
Doug. Co. Surveyors
Office.
J.M. Powell
R.L. Smith
Jan. 25, 1982
C.S. 61/30

Closing corner for Secs. 6 and 7 only.
Found - A 1 3/4" I. Pipe, firmly set, filled with concrete and rusted off 4 inches above ground. Upper portion of pipe with a GLO 1918 properly marked brass cap has been placed alongside lower portion.
Orig. fir, 65" now a 69" dia. stump with well healed blaze bears N.35 1/2°E., 69.4 ft. (Rec. N.37°E., 71.3 ft.)
Orig. fir, 67 in. dia- now a stump with visible burl bears S.52°E., 118.7 ft. (Rec. 101.0 ft.)
1966 resurvey, a fir, 20 ins. now a 24 in. dai. stump with well healed blaze bears N.85°E., 27.8 ft.
1966 resurvey, a cedar, 6 in. now a 10 in. diam. stump with unhealed blaze scribed "T21S R9W S7 CC BT" bears S.86°E., 48.1 ft. (Rec. 51.5 ft.).
Set - A 1" x 30" galv. I.P. with brass cap attached is set at position of found monument along northerly side. Cap stamped: "Douglas County Surveyor T21S R10W CC S6 S7 R9W 1982".
New BO - As there are no trees available to scribe, WE SET a railroad spike in the pitch ring of a 24" diam. fir stump. Spike is stamped "BO" and bears S.55 1/2°E., 53.6 ft.
This corner lies on south side of a spur ridge sloping westerly.
Sketch in CS file.

1/25/82

Richard J. Hintz
PLS #497
For: International
Paper Co.
August, 1982
M 92 - 74

East 1/4 Corner to Sec. 6.
Set - 1-1/4" x 36" I.P. w/ Brass Cap stamped P.L.S. 497.
New BTs- 92" maple bears N.53°E., 36.0-ft. (scribed).
24" maple bears N.56°W., 59.9-ft. (scribed).
note - distances to a 50d nail in the face of each B.T. 8/82

39

Center 1/4 Corner of Sec. 6.
Set - 1-1/4" x 36" I.P. w/Brass Cap stamped PLS 497.
New BTs- 14" fir bears N.45°45'E., 15.5-ft. (scribed).
12" cedar bears S.8°00'W., 18.2-ft. (scribed). 8/82

40

Les Roberts
PLS # 1039
For: International Paper
Dec. 21, 1982
M 90 - 30

South 1/4 corner of Sec. 5 only.
Set - 1-1/2" x 36" I.P. w/B.C. at proportionate distance.
New BTs - 23" cedar bears N.3°W., 47.8-ft. (scribed).
58" fir bears N.72°W., 50.1-ft. (scribed). 12/82

41

Center 1/4 corner for Sec. 5. FOR WITNESS CORNERS, SEE: M 96-30 (Mar. 27, 1984)
Set - 1-1/2" x 36" I.P. w/B.C.
New BTs - 14" hemlock bears S.85°E., 30.3-ft. (scribed).
29" alder bears N.13°E., 10.2-ft. (scribed). 12/82

42

Closing Corner for Secs. 7, and 8.
Set - 1-1/2" x 36" I.P. w/B.C. by broken boundaries method.
New BTs - 34" fir bears S.32°W., 99.0-ft. (scribed).
64" fir bears S.66°E., 44.5-ft. (scribed).
67" fir bears West, 41.9-ft. (scribed). 12/82

43

Les Roberts
PLS #1039
For: International
Paper Company
December 30, 1982
M 90 - 36

Center 1/4 Corner of Sec. 4.
Set - A 1-1/2" x 36" I.P. w/B.C.
Incorrect corner (fnd.) bears N.30°20'19"E, 90.81-ft. I replaced the incorrectly set pipe with a 1/2" x 30" I.R. (buried 1.0-ft.).
New BTs- 32" fir bears S.47°W., 36.3-ft. (scribed both BTs).
56" fir bears N.30°E., 21.2-ft.

44

Les Roberts LS 1039
For: International
Paper Co.
March 10, 1983
M 94 - 4

1/4 Corner for Sections 21 and 22
Found - 24" Cedar stub, N.79°E., 17.2 ft. (no marks) 1894 BT.
42" Cedar line tree, North, 31.7 ft. (no marks)
16" downed fir, N.10°W., 26.4 ft. (cut open and found scribing "1/4 S", 1894 BT.)
Set - 1 1/2" x 36" iron pipe & brass cap stamped with S-T-R, date & PLS No. 1039.
New BTs - 29" hemlock, N.70°E., 47.6 ft. scribed/set washer.
56" cedar, S.6°W., 12.2 ft. (scribed/set washer).

45

RE-RENEWED, SEE CORNER NO. # 59

3/10/83