

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 9 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97301

C O N T - - - -

54

13" Alder with bark scribe W 1/4 S31 BT and tag bears S.62°E.,
24.8 ft. to a spke in side center.
9" hemlock with face scribed BT X at BH and tag bears S.58°E.,
32.23 ft. to a spke in side center.
About 2 miles up Wells Creek take spur to the West about 1 mile to point
where road crosses line between secs. 31 and 36.

55

Harvey Wilcox
L.S. #2244
For: Stuntzner
Eng.
Sept. 5, 1990
C.S. 63/104

East 1/4 Corner for Section 36 only of T.21-10
Found - 1" iron pipe with 2 1/2" brass cap. I.P. had rusted in two at
ground level. (1919 GLO brass cap)
48" Fir stump with old face and visible scribe bears N.79°W.,
50.02 ft. to center of stump.
Set - A 2" alum. cap on a 3/4" x 30" iron rod along side old monument.
Cap mkd. "Stuntzner Eng. T21S R10W E 1/4 | 1990 LS 2244"
36
New BTs- A 24" hemlock with face scribed E 1/4 S36 BT and tag bears
N.68°E., 38.5 ft. to spke in side center.
A 14" Fir with face scribed E 1/4 S36 BT and tag bears S.41°E.,
11.7 ft. to a spke in side center.
A 10 1/2" Fir with face scribed E 1/4 S36 BT and tag bears S.40°W.,
23.5 ft. to a spike in side center.
About 2 miles up Wells Creek take spur to the West about 1 mile to point
where road crosses line between Secs. 31 and 36.

Daniel Baker
L.S. # 1978
For: Intntl. Paper
Co.
Dec. 13, 1990
M 111 - 29

1/4 Corner between Sec's 1 & 2.
Found - U.S. B.L.M. brass cap - "1967"
BT's (found)
- 12" fir snag S.78°E., 5.9 ft. original
15" fir snag S.65°W., 7.0 ft. original
BT's new-37" fir S.13°E., 30.4 ft. scribed 1/4 S1BT
14" fir S.89 1/2°W., 17.5 ft. scribed 1/4 S2BT

56

12/90

Daniel Baker
L.S. # 1978
For: Intntl. Paper
Co.
Dec. 12, 1990
M 111 - 27
FILED 1991

Center 1/4 corner for Section 10
Found - 20" Hemlock stump rotten N.22°W., 7.6 ft. (M 46 - 58)
Set - 3/4" X 30" aluminum rod and I.P. Co. aluminum cap
New BTs- 36" Fir stump, N.46 1/2°E., 65.0 ft. Ren. # 18
7" Hemlock, S.16°E., 92.8 ft. scribed C 1/4 S10BT
41" Fir stump, S.17 1/2°W., 40.6 ft.
28" Fir stump, N.35 1/4°W., 32.8 ft.

57

12/90

Douglas County
Surveyors Office
Randall Smith
John Pike
May 20, 1992
C.S. 64/26

Witness Corner for Sections 28, 29, 32 & 33.
Found - 2 1/2" dia. DCSO brass cap marked 'T.21S. R.9W. Wit. Cor. S.28,
S.29, S32, S.33 55 ft. east to corner 1974' cap sits on 1 1/2" O.D.
I.P. and protrudes 5" above ground. See renewal # 25.
Accessories Found -
18" now 24" dia. hemlock with a partially healed double blaze
illegible scribing visible, bears N.10°W., 21.0 ft. (ren.25)
24" now 23" dia. maple with a partially healed single blaze,
scribing visible "WC T21S R9WS32" bears S.31°W., 52.2 ft.
(Rec. S.32 1/2°W., 52.2 ft.) (ren. 25)
New Accessories -
60" now 95" dia. D. fir with a previously opened healed blaze,
blaze faces southeast, bears n.42 1/2°E., 49.0 ft. (orig. BT)
35" now 33" dia. maple with a fully healed double blaze, blaze
faces northeast, bears S.45°E., 44.1 ft. (1966 resurvey)
18" dia maple double blazed and scribed "WC T21S R9WS33 CS BT"
bears S.17°E., 16.5 ft.

58

6/3/92

- SEE NEXT PAGE -