

Douglas County Surveyor's Record of
Government Corners Renewed

T 21

T. S.

R 10

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Harvey Wilcox
L.S. 2244
For: Stuntzner
Engineering
Sept. 5, 1990
C.S. 63/104

West 1/4 Corner for Section 31 only of T.21-9

130

Found - 1" iron pipe with 2½" brass cap. I.P. had rusted in two at ground level. (1919 GLO Brass cap)

A 58" cedar with axe marks bears N.107°E., 47.94 ft. to side center.

A stump hole where Fir BT was blown out of and slid down hill bears S.76°E., 19.14 ft. to center of hole.

Set - 2" alum. cap on a 3/4" x 30" iron rod along side old monument.

New BTs - 56" cedar with face scribed W 1/4 S31 BT and tag bears S.25°E., 52.93 ft. to a spike in side center.

58" cedar with face scribed W 1/4 S31 BT and tag bears N.07°E., 47.94 ft. to a spike in side center.

13" alder with bark scribe W 1/4 S31 BT and tag bears S.62°E. 24.8 ft. to a spike in side center.

9" hemlock with face scribed BT X at BH and tag bears S.58°E., 32.23 ft. to a spike in side center.

About 2 miles up Wells Creek take spur to the West about 1 mile to point where road crosses line between sections 36 and 31.

9/5/90

FD. OK. 2/92 STUNTZNER
M114-80

Harvey Wilcox
RLS 2244
For: U.S.F.S.
December 1990
M 111-47 A-F

Northwest Corner for Section 6.

131

Found - 2½" brass cap on 1¼" IP 12" above ground, with 1" IP along side.

BTs Fnd - 30" maple S.E. trunk of tree with healed face. tags, bears N.14°W., 15.2 ft. to side center. Ren. # 7

21" douglas fir, healed face, tags, bears N.80°E., 83.6 ft.

37" douglas fir, healed face, tags, bears S.77°15'E., 42.9 ft.

39" maple, healed face, tags, bears S.27°W., 11.2 ft.

Note - 39" maple has blown down, retagged another trunk of the same tree it bears S.25°30'W., 14.20 ft.

Set R.M.- Std. U.S.F.S. disk "RMT20S R10W S31 S88°09'W 52.91' 1990 RLS 2244" bears N.89°09'E., 52.91 ft.

12/90

1/4 Corner for Sections 22 and 27.

132

Found - Iron pipe & brass cap, top broken off. (From 1918 G.L.O. survey) 25" Fir "shell" bears S.82°W., 17.5 ft. (scar visible) 1918 B.T. Record N.74°W., 17.8 ft. No evidence of 10" alder.

Set - 5/8" X 36" aluminum rod with aluminum cap beside G.L.O. iron pipe. Buried purple magnetic marker under 36" aluminum rod.

New BTs - 10" fir bears N.7°E., 77.4 ft. Scribed/painted red.

16" alder bears N.56°E., 23.4 ft. Bark scribed/painted red.

18" alder bears S.13°E., 16.3 ft. Bark scribed/painted red.

42" fir bears S.73°W., 31.7 ft. Scribed/ painted red.

Note - Corner lies on West slope about 150 ft. west of ridge. Ridge bears North South.

1/17/92

Les Roberts
L.S. 1039
For: Int. Paper Co.
Dec. 1991
M 114 - 28
C.S. 63/138

Corner Secs. 3 & 4; 33 & 34 T20-10

133

Found - 1951 GLO brass cap

30" Hemlock, N.85°W., 64.3' (scribe vis.), 1951 BT

33" Fir, N.70°E., 148.5' (scar vis.), 1951 BT (rec. 87.1)

38" Fir, S.59°W., 64.5' (scar vis.), 1951 BT

36" Maple, S.20°E., 26.5' (scribe vis.) 1983 BT

Les Roberts
L.S.1039
For: INT. Paper
Dec. 1992
M118-47

1/4 Corner for Sections 5 and 8.

134

Found - 3" alum. cap on 2" alum. pipe. See renewal # 79.

Found BT's -

40" D.Fir, bears N.19°E., 33.7 ft.

30" Cedar, bears N.2°W., 21.8 ft.

10" Maple, bears S.69°W., 37.7 ft.

New BT's -

10" Maple, bears S.33°W., 13.1 ft.

14" Maple, bears S.25°E., 11.3 ft.

Ronald Stuntzner
For: I.P. Timberlands
Operating Co. Ltd.
L.S. 1342
Jan. 1994
M 118 - 73