

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 10 W. R.W.W.M.

KORZ-CHAPMAN CO. EUGENE, ORE. 97401

C. S.
File
No.
53/66

John M. Powell
Frank Jones & W. Penley
C. S. File No. 54/1

Vernon "Ray" Tracy
Jack Heritage & V. Perron
Feb. 1970 C.S. File No. 54/1

Section Corner to Sections 1 and 12 only, T21-10W. 32
Found - GLO Brass Cap properly marked in 1919. NO. 50
22" D.Fir, now snag, S.33°W. 42.9 ft., shows scar.
36", now 36" D.Fir, N.10°W. 28.4 ft., shows good scar.
20" D.Fir S.20°W. 67.3 ft., pitched over scribing visible. (Ren. Tree)
New BT: 17" D.Fir N.59½°E. 40.2 ft., scribed "T21S R9W S 6 CS BT."
Note - I renew this corner because of new road to be built. The S.W. BT.
is on top of ridge & will probably be taken out. P.Line 72+30.
9/10/69

¼ Corner West Side of Section 21. 33
Found - Remains of I. Rod for Brass Cap at Corner, 1919 Brass Cap gone.
12", now 13" Hemlock, N.35°E. 7.9 ft., shows good scar.
32", now 32" D.Fir, S.14°E. 7.3 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 21 S R 10 W
Office, 1969 S 21 ¼
Bearing Trees O. K. and Tagged. 10/1/69

Section Corner to Sections 2 and 11 only. 34
Found - GLO Brass Cap set in 1919, Cap is rusted away.
24", now 38" D.Fir, N.33°E. 16.5 ft., shows good scar.
12" Alder, now dead, S.71°E. 28.4 ft.
Set - New Brass Cap at Cor. Mkd: County Surveyor's T 21 S R 10 W
Office S 3 S 2
1969 S 11
New BT: 16" Cedar S.29°E. 29.7 ft. Mkd: "T21S R10W S11 CS BT." 10/2/69

Section Corner to Sections 3 and 10 only. 35
Found - GLO Brass Cap set in 1919, Cap rusted away.
10", now 28" Alder, N.66°W. 27.1 ft., shows old face.
No trace of S. W. Bearing Tree.
Set - New Brass Cap at Cor. Mkd: County Surveyor's T 21 S R 10 W
Office S 3 S 11
1969 S 10
New BT's: 48" Cedar S.73°W. 27.7 ft. mkd: T21S R10W S10 CS BT.
58" Cedar East 8.5 ft. mkd: T21S R10W S11 CS BT.
No trace available in N. W. Quadrant. 10/2/69

¼ Corner to Sections 33 and 34. 36
Found - Remains of old concrete-filled Iron Pipe with 1919 GLO
Brass Cap laying alongside.
Orig. 14", now 16" Fir Snag, East 1.3 ft., open & find "¼ S34 BT"
scribe and reverse.
Orig. 14", now 22" Fir, Alive, S.53°W. 13.9 ft., shows good scar.
Rescribe above old scar: "¼ S33 CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 21 S R 10 W
(Dep. Old Cor. Mat. Alongside) Office, 1970 ¼ S 33 S 34
New BT: 24" D.Fir N.65°E. 8.8 ft. mkd: "¼ S34 CS BT".
This corner lies on very steep, N.E. slope in very dense rhododendron brush.
Feb. 1970

¼ Corner to Sections 11 and 12. 37
Found - No trace of 1919 I.P. & Brass Cap.
Orig. 18", now 24" D.Fir, alive, N.42°W. 11.2 ft., prev. opened
& scribe visible. We rescribe "¼ S11 CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 21 S R 10 W
Office, 1970 ¼ S 11 S 12
New BT's: 16" D.Fir N.25°E. 35.8 ft. mkd: "¼ S12 CS BT"
14" D.Fir S.33°W. 14.1 ft. mkd: "¼ S11 CS BT".
This corner lies on very steep, easterly slope about 60 ft. east of
top of spur, ridge sloping south. Feb. 1970

MARCH 71