

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 10 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21981

(Continued)

53

Ernesto R. Alvarado,
U.S.F.S...Deputy,
Douglas County Surveyor
Colin Long, witness
August 21, 1981
C.S. 61 / 27

New BT's - 4" D. Fir bears N.9°E., 15.6-ft. with blazed X at breast height & on lower blaze scribed CS BT. No other trees large enough to mark.

Note - Attention & property boundary signs placed on 6-ft. steel fence post North of corner. Attention sign on fence post placed South of corner. Painted 6" red bands & blazes on all BT's. Area flagged with pink "Land Line" ribbon. Distances are to side and center of trees at root crown.

Location - From Smith River Road, take F.S. Rd.#110 approx. 2.2 miles to location poster on Section line post on East side of road. From post, go S.0°17'41"E., 324.6-ft. Corner lies on SW slope. 8/21/81

54

1/4 corner for Sec's. 1 & 2.

Found - Doug. Cou. Surveyors Cap 6" above ground, solid, Ren.#42. leans slightly to West.

1" concrete-filled iron pipe, badly rusted, in ground, 0.3-ft South of Cap (pipe was for 1919 B.C.). Cap is marked:

T21S R10W

BT's - 27" Alder bears N.24°W., 23.7-ft., 1/4 S2|S1
open blaze, face rotted w/faint 1975
scribing visible (1919 BT).

Broken remains of low cut Hemlock stump, bears N.49°E., 50.3-ft., scribing visible on broken piece of wood (still attached) (1975 - Doug. Co.)

23" Hemlock bears S.76°W., 47.2-ft., open face, scribing visible: 1/4 S2 CSBT .

New - Re-scribed 27" Alder (bark scribed): 1/4 S2 CSBT alongside old face (1919 NW BT).

Note - Distances are to side and center of trees at root crown.

Location - From Sec. line poster on East side of road (see ren.#53), go N.0°17'41"W., 2312.5-ft. Follow old fire trail. 1/4 cor. is on tree line on small bench West of N landing in unit. 8/13/81

55

Section corner for 1 and 12 only. (on range line)

Found - No monument found. Construction of a log landing directly above corner has destroyed evidence at corner position. Orig. 36" D. fir now a charred stump bears N.10°W., 28.4 ft. (We do not open blaze for scribing.)

A bridge spike set in rock stamped "BO 2" bears S.57 1/2°W., 172.08 ft. (Rec. 172.10 ft.) Ren. #50

A 5/8" dia. I.R. with alum. cap stamped "BO 1" bears S.60°E., 102.42 ft. (level chained 93.52 ft. + slope chained 11.97 ft. @ 42° slope) Rec. information indicates a distance of 102.08 ft. for this line. A review of the field notes for Ren. #50 indicates measurements on steep slopes, I assume this the most probable line for error.

A PK nail set in 30" dia. stump bearing S.60°E., 538.87 ft. not used as fog has visibility blocked.

Set - At corner position as determined by noted courses, SET a 1" x 30" I.P. with brass cap attached marked "Douglas County Surveyor T21S R10W S1 S12 R9W 1982". Monument is buried 28" deep.

New BO - Set a railroad spike stamped BO 3 in a charred 40" stump bears N.3°E., 56.9 ft.

Sketch on field notes in C.S. file.

1/13/82

56

Closing corner for Secs. 6 and 7 only of T.21-9

Found - A 1 3/4" I. Pipe, firmly set, filled with concrete and rusted off 4" above ground. Upper portion of pipe with a GLO 1918 properly marked brass cap has been placed alongside lower portion.

Orig. fir, 65" now a 69" dia. stump with well healed blaze bears N.35 1/2°E., 69.4 ft. (Rec. N.37°E., 71.3 ft.)

Orig. fir, 67" dia. now a stump with visible burl bears S.52°E., 118.7 ft. (Rec. 101.0 ft.)

Ernest R. Alvarado,
U.S.F.S... Deputy,
Douglas County Surveyor
Carol Dickison, witness
August 13, 1981
C.S. 61 / 27

Larry E. Monrean,
Deputy, Doug. Co.
Surveyors Office
John M. Powell
Jan. 13, 1982
C.S. 61/30

Larry Monrean, Deputy
Doug. Co. Surveyors
Office
J.M. Powell
R.L. Smith
Jan. 25, 1982
C.S. 61/30