

Douglas County Surveyor's Record of
Government Corners Renewed

T 21

T. S.

R 10

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91001

56

C O N T - - -

Larry Monrean
Deputy, Doug.
Co. Surveyors
Office.
J.M. Powell
R.L. Smith
Jan. 25, 1982
C.S. 61/30

(closing corner for Secs. 6 and 7 only, T.21-9)
1966 resurvey, a fir, 20" now a 24" dia. stump with well
healed blaze bears N.85°E., 27.8 ft.
1966 resurvey, a cedar, 6" now a 10" dia. stump with
unhealed blaze scribed "T21S R9W S7 CC BT" bears S.86°E.,
48.1 ft. (Rec. 51.5 ft.)
Set - A 1" x 30" galv. I.P. with brass cap attached is set at position
of found monument along northerly side. Cap stamped: "Douglas
County Surveyor T21S R10W CC S6 S7 R9W 1982".
New BO - As there are no trees available to scribe, WE SET a railroad spike
in the pitch ring of a 24" dia. fir stump. Spike is stamped
"BO" and bears S.55 1/2°E., 53.6 ft.
This corner lies on south side of a spur ridge sloping westerly.
Sketch in C.S. file.

1/25/82

57

Witness Corner to 1/4 corner common to Sec. 4, & Sec. 33, of T.20-10.
Set - 1-1/4" x 36" I.P. with B.C. stamped "P.L.S. 497", 2.0-ft.
south of corner position, which is in a field ditch.
New BTs- 32" fir bears N.65°45'E., 265.5-ft. (scribed).
68" maple bears S.57°30'W., 320.5-ft. (to face). 2/82

Sec. cor. common to Secs. 4, 5, and Secs. 32, & 33 of T.20-10. #60 58
Found - F.P. with U.S.G.L.O. B.C. dated 1918, and a plow share.
New BTs- 14" alder bears S.70°W., 4.7-ft. (scribed). 2/82
SEE REN. #1 T.20-10

Sec. corner common to Secs. 4, 5, 8, & 9. #67 59
Set - 1-1/4" I.P. with B.C. stamped "P.L.S. 497", from which:
BT - (1919) 24" cedar (now 48" stump) bears N32°W., 25.9-ft. to
a 50d nail in face.
New BTs- 30" alder bears S.69°45'E., 34.1-ft.
12" maple bears N.59°30'W., 7.0-ft. 2/82

Section corner common to Secs. 32 and 33; and Secs. 4 & 5 of T.20-10. #60 60
Found - 2" I.P. filled with concrete firmly set protruding 6" out o
ground. The top 10" of said I.P. has brass cap attached and
is broken off and lying on ground. Cap is an unrecorded GLO
cap stamped "General Land Office Survey" T20S R10W S E2 S33
S 5 S 4 T21S 1918. See Ren. #1, T20-10 and Ren. #58
Also found unrecorded 20" x 5" plow shear along side iron pipe.
14" alder with possible well healed blaze and newly bark scribed
"S 5 BT" bears S.63°W., 4.7 ft. (rec. 5.7 ft.) bark scribing
per Ren. #58.
15" now 20" fir stump with scribed "BT" visible bears N.32°E.,
28.2 ft. (rec. N.45°30'E., 29.0 ft.)
12" now 15" fir snag approx. 40 ft. tall with well healed blaze
bears N.30°E., 23.8 ft.
12" alder is gone as is any orig. evidence. (Ren. #1 of T.20-10)
Set - At the location of the 2" I.P. filled with conc. I set a 1" x 30"
I.P. with brass cap attached marked "Douglas Co. Surveyor"
T20S S32 S33 S5 S4 R10W T21S 1982.
I buried both parts of found GLO I.P. and brass cap along
with plow shear alongside new brass cap.
New BT's- 16" fir scribed "T20S R10W S33 CS BT" in double blaze bears
N.2°E., 83.8 ft.
7" fir scribed "T21S R10W S4 CS BT" in double blaze bears S.1°E.,
16.2 ft.
24" cedar scribed "T21S R10W S5 CS BT" in double blaze bears
S71°W., 32.9 ft.

3/22/82

61

Richard J. Hintz
For: International
Paper Co.
March 28, 1982
M 91 - 24

Center 1/4 Corner of Sec. 4.
Set - 1-1/4" x 36" I.P. with Brass Cap marked PLS 497 from which:
New BTs- 14" fir bears S.56°15'E., 22.5-ft.
38" fir bears S.29°00'W., 38.1-ft.
note - Both trees scribed, and distances taken to a 50d nail in center.

3/28/82

Richard J. Hintz
For: International Paper
February, 1982
M 91 - 24

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
Randy Smith,
Witness
March 22, 1982
C.S. 61/30