

Douglas County Surveyor's Record of  
Government Corners Renewed

T 21 T. S. R 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Richard Hintz  
For: International  
Paper  
November 1983  
M 95 - 40

Section corner for Sections 7 and 18; and Secs. 12 & 13, T.21-11<sup>72</sup>  
Found - Original 60" cedar corner tree which is now an uproot.  
Set - A 50 d nail in the upturned roots from which:  
Orig. 24" cedar BT now 50" bears S.35°W., 34.3 ft.  
I measured to a point 12" from the center of the tree, assuming the  
record distance of 34.3 ft. was taken from the face, i.e. 1/2 of the  
original diam. cedar bearing tree.

Section corner for Secs. 5 and 6; and Secs. 31 & 32 of T.20-10  
Found - 1 1/2" I.P. with 1979 2 1/2" brass cap set in conc., properly  
marked. Ren. #49  
21" red cedar bears N.6°W., 28.8 ft. with scribe marks "BT  
S31" visible on partially healed face.  
27" fir bears S.43°E., 85.0 ft. with healed face.  
New BTs - 13" D. fir bears N.55°E., 80.7 ft. blazed and scribed "T20S  
R10W S32 BT".  
19" big leaf maple bears S.81°W., 73.3 ft. bark scribed "T21S  
R10W S6 BT".

1/4 Corner for Section 5; and Sec. 32 of T.20-10  
Set - 2 1/2" x 30" alum. pipe, 24" in the ground with 3 1/4" cap mkd.  
"US Dept of Agri-Forest Service T20S 1/4 S32 S 5 T21S  
RLS 1651 1983 Unlawful to Disturb".  
New BTS - 20" hemlock bears N.31°E., 57.2 ft. scribed "1/4 S32 BT".  
24" hemlock bears S.8°W., 59.4 ft. scribed "1/4 S5 BT".

Section corner for Secs. 3 and 4; and Secs. 33 & 34 of T.20-10  
Found - 2" iron pipe loosely set 18" above ground with 1951 3" brass  
cap, properly marked. (GLO brass cap) Firmed up.  
36" D. fir bears N.67°E., (75° record) 148.49 ft. healed.  
35" hemlock bears N.84°W., 64.3 ft. scribes visible "R10W  
S33 BT US".  
36" D. fir bears S.59°W., 62.7 ft. healed blaze.  
New BTs- 36" big leaf maple bears S.19°E., 27.8 ft. blazed and scribed  
"T21S R10W S3 BT".

1/4 Corner for Sections 5 and 6.  
Set - 2 1/2" x 30" alum. pipe, 26" in the ground with 3 1/4" alum.  
cap mkd. "US Dep of Agri-Forest Service T21S R10W 1/4 S6 S5  
RLS 1651 1983 Unlawful to disturb".  
BTs - 15" D. fir bears S.25°W., 19.9 ft. blazed and scribed "1/4 S6 BT".  
9" D. fir bears S.48°E., 14.0 ft. blazed & scribed "1/4 S5 BT".

1/4 Corner for Secs. 4 and 5.  
Set - 2 1/2" x 30" alum. pipe, 26" in the ground, with 3 1/4" alum  
cap mkd. "US Dep of Agri-Forest Service 1/4 T21S R10W  
S5 S4 RLS 1651 1983 Unlawful to Disturb".  
BTs - 6" D. fir bears N.72°E., 76.6 ft. blazed & scribed "1/4 S4 BT".  
8" D. fir bears S.83°W., 30.0 ft. blazed & scribed "1/4 S5 BT".

Section corner for Secs. 5, 6, 7 and 8.  
Found - 1" I.P. filled with concrete & rusted & broken off, with 2 1/2"  
brass cap. (1919 GLO cap, properly mkd.)  
36" fir stump bears S.78°E., 27.0 ft. (Rec. 44.2 ft.) shows  
fragmentary marks  
16" cedar snag bears S.20°W., 46.4 ft. (Rec. S.30°W., 48.8 ft.)  
Shows open face, no marks but "H" carved in bark above face,  
40" fir stump bears N.32°W., 47.6 ft. (Rec. 52.8 ft.) Shows no  
marks.  
40" cedar snag bears N.34°E., 55.2 ft. (Rec. 59.2 ft.) No visible  
marks.  
Set - 2 1/2" x30" alum. pipe at position of found pipe, 24" in the  
ground, with mound of stone, with 3 1/4" alum. cap mkd. "US  
Dep of Agri-Forest Service T21S R10W S6 S5 S7 S8 RLS 1651 1983  
Unlawful to Disturb".  
New BTs continued next page - - - -

Herman Pieske, LS 1651  
AA Surveying Services, Inc.  
For: US Dept. of Agriculture, Forest Service,  
Siuslaw National Forest  
November, 1983  
M 95 - 59 A & B

Services Above Page,  
Applicant filed 1/16/84  
On county Records Book 879  
Page 176 (Case No. 5502/17)

RENEWED, SEE CORNER NO. #113

11/83  
73

74

75

76

77

78