Douglas County Surveyor's Record of Government Corners Renewed

21 T. S. 11 R. W. W. M.

1 ¼ CORNER BET. SECS. 27 & 28 — RE-RENEWED, SEE CORNER NO. #183
I found the witness corner to the ¼ corner between 27 & 28. I could not find the stone as described in the government field notes, but found two dead witness trees in place, I therefore set cedar post 4' long, 4" diam., 18" in ground marked ¼ S. W. C. from which:
A Fir, 16" diam., bears S. 79°E. 23 ft. marked ¼ S. W. C. R.T. 722
A Fir 12" diam., bears S. 9°W. 5 ft. marked ¼ S.W.C. R.T. 722

2 ¼ CORNER BET. SECS. 34 & 35 — RE-RENEWED, SEE CORNER NO. #193
At the ¼ corner between sections 34 & 35, I found the scribe on on the original alder bearing tree had been rotted out, but in the soft muck where the post was supposed to set I found the well preserved point of an old wooden stake, also, running N. from this point is a well blazed line, whose topography checks for a considerable distance with the government field notes. I therefore set an old wooden stake marked ¼ S.W.C. from which:
A White Spruce, 24" diam., bears S.10°E 5 ft. marked ¼ T.21S. R.11W. S35 R. T. 722
A spruce, 36" diam., bears S. 75° W. 24 ft. marked ¼ T.21S. R.11W. S. 34 R. T. 722

3 SEC. COR. OF SECS. 18-19 — RE-RENEWED, SEE CORNER NO. 32
T.21S. R.11W. & Sec. 13-24 T.21S. R.12W. on Range line.
Drove 2" x 5' pipe for corner from which
7" Fir bears S. 70°E. 7.7 ft.
12" Fir bears S. 10° W. 8.2 ft.
8" Fir bears N. 49½° W. 18.2 ft.
10" Fir bears N. 44° E. 21.8 ft.

4 COR. SEC'S. 16, 17, 20 & 21 — RE-RENEWED, SEE CORNER NO. 58
Renew cor. from old hem ock and cedar trees. in 5 in. Cedar stake. from which:
A 7 in. Fir bears S. 26½° E. 9½ lks. dist.
A Hemlock bears N. 75° W. 30 lks. dist. old tree
A Cedar bears N. 65° E. 100 lks. dist. old tree

5 COR. SEC'S. 8, 9, 16, 17 — RE-RENEWED, SEE CORNER NO. #23
Renew cor. from four Fir stumps of old R.T.S. Set in 3" x 48" Chittem stake, from which
A 10 in. Chittem bears S. 18° E. 0.48 chs.
A 10 in. Fir bears S. 41° W. 0.25 chs.

6 ¼ COR. BETWEEN SEC'S. 16 & 17 — RE-RENEWED, SEE CORNER NO. 57
A reestablishment, no old trees or cor. found. Set in 5" x 48" Cedar stake, from which
A 16 in. Fir bears N 48½° W. 7.6 ft.
A 12 in. Fir bears S. 31½° E. 4.9 ft.

7 COR. SEC'S. 4,5,32,33 — N. BORY T20-10 WEING TWP. & RANGE — SEE GOV'T. 1952 BRASS CAP VOL. 27 Pg. 11682
Renew Cor. from old Maple tree and two Fir trees set
A 11 in. Fir bears S. 46½° E. [illegible] lks.
A 18 in. Fir bears N. 54½° E. 32 lks.
A 18 in. Fir bears S. 85° W. 15 lks.
A 12 in. Fir bears N. 78° W. 47 lks.
F.B. 45 Pg. 10 C.S. 1/36

8 CORNER 9,10,15,16 — RE-RENEWED, SEE CORNER NO. #106
Renew corner from old Cedar R. R. stake set 4" x 4" x 26" Cedar stake and marked net R. R. 48" Fir 7" Dia. 75 lks. 15" Cherry S. 71°E. 46 lks; 60" Cedar N. 67° W. 197 lks. No other tree available in 9, 10, or Sec. 16.

8A ¼ Cor. between sec. 9 - 16 set on true line between section cor. RE-RENEWED, SEE CORNER NO. 72 set a 1" x 5' galv. iron pipe. Witness a 24" Fir N. 20° E. 5.4 lks.

By F. C. Freer, R. L. S. — Witness H. A. Hohnbison, Exer. 722 — April 18, 1939 — C S 16/55 — Ren Cor Vol 1 Pg 15
A. C. Freer, Dep. Co. S. — Witness W. J. Peck, James W. Tolford — May 9, 1939 — Ren Cor Vol 18 Pg 15
F. C. Frehr, Dep. Co. Sur. — Witness R. D. Minter, L. D. Pierson — May 17, 1918 — Ren Cor Vol 18 Pg 16 — C.S. 1/36
June 27, 1926 — H. L. Engelsin, G. S. Bert Lane, Grover Lachors, Harry Barnhardt — C.S. 1/66