

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 11 R. W. W. M.

KORE-CHAPMAN CO., SUGARS, ORE., 1981

Frank Cain  
9/27/1912  
F. E. 6-61, page 41.

Meander corner between sections 35 and 36.  
Set a Cedar post, 4"x 4"x 4' long, marked M. C. C. S. on S. face,  
T 21 S on N. face, R 11 W, S 36 on E. face and S 35 on W. face,  
from which:  
A Spruce, 28 inches in diameter bears N. 42° 20' W., 108 1/2 lks.,  
marked M. C. S. 35 C.S. B.T. ~~210~~  
An Alder, 12 inches in diameter bears N. 73° 19' E., 24 lks.,  
marked M. C. S. 36 CS B.T.

17

1/2 Section Corner common to Section 34, & Sec. 3, T22S., R.11W.  
Marked by a 1/2" Pipe & witnessed by a 57" Spruce Tree. This  
is the original BT. for Sec. 3, the face has grown closed,  
so I rescribed this tree in a different place. It is now a  
Spruce 57" DBH, bearing S. 31° 30' E., 47.3 ft.  
I also mark a forked Spruce, 40" DBH, which bears N. 70° 00' W.,  
14.5 ft.  
This corner lays in a swamp 131.8 ft. South of the shoulder of  
the Dean Creek Road.

18

South Section Corner common to Sections 33 & 34.  
Said point being witnessed by a 36" R. Fir, which is the Orig. BT.  
No trace of the Willow found in 1893.  
Set a Sandstone Rock, 20" x 21" x 9", and mark it with an "X" for  
the corner point & scribe new BT's. as follows:  
A. Fir 33" DBH, bears N. 42° 15' E., 15.0 ft.  
Cherry 7" DBH, bears S. 36° 30' E., 10.5 ft.  
D. Fir 35" DBH, bears S. 82° 00' W., 58.5 ft.  
This corner lays on a N. slope facing the Umpqua River.

19

C. C. common to Sections 32 & 33.  
Which is an angle Iron set by Haines, from the Orig. BT's.  
Mark additional trees for this corner as follows:  
Spruce, 25" DBH, bears N. 11° 00' W., 34.2 ft.  
Alder 35" DBH, bears S. 24° 30' W., 47.1 ft.

20

Closing Corner for Sections 33 & 34.  
I set this corner 2,676.3 ft. South of the C. C. for Secs. 27 & 28  
and 4,026.0 ft. East of South Corner of Secs. 28 & 29, T21S, R11W.  
Drove a 1" Iron Rod & Marked BT's. as follows:  
D. Fir 32" DBH, bears S. 39° 30' E., 58 ft.  
D. Fir 23" DBH, bears S. 65° 30' W., 25.7 ft.  
D. Fir 12" DBH, bears N. 19° 30' E., 40.7 ft.

21

Closing Corner common to Sections 27 and 28.  
Drove a Pipe and marked the following Bearing Trees:  
Cedar 14" DBH, bears S. 6° 00' E., 16.1 ft.  
D. Fir 19" DBH, bears N. 86° 00' W., 15.0 ft.  
D. Fir 24" DBH, bears N. 50° 30' E., 7.2 ft.

22

Section Corner to Sections 8, 9, 16, and 17.  
Found - 1 1/2" Iron Pipe with Plug Mkd: S8 189 - Ren # 5  
S17 186  
Found Stump of 3 Original BT's. & 1 near S. W. BT.  
New BT's: 36" R. Fir S. 11° 30' W. 79.6 ft. scribed S17 T21S R11W CS BT.  
R. Fir bears S. 26° E. 107.4 ft. scribed S16 T21S R11W CS BT.

23

South 1/2 corner to Section 12.  
At a point midway on the S. line of Sec. 12, the bearing & distance of  
which is 2643.8 ft. S. 85° 57' E. of the Sec. Cor. for Secs. 11, 12, 13, & 14,  
I set the S. 1/2 corner. This corner is mkd. with a 1" x 45" galv. iron pipe  
25" in the gr. & surrounded by a mound of native stone. 2 BT's. as follows:  
22" crooked gr. D. Fir bears N. 43° 15' E. 44.6 ft. scribed S12BT  
42" gr. D. Fir bears S. 70° 30' W. 74.4 ft. to center of tree &  
scribed: S-13 BT- on face looking at the corner.

24

Warren D. Hootman #399  
Done for Western Lane Logging Company  
Reedsport, Oregon  
July 1, 1959  
C. S. File No. 51/30  
Map File M 15 - 23

James W.  
Byron, Dep.  
For Ore. St.  
Game Dept.  
Sept. 1959  
C.S. File 49/186  
M 15 - 63

Robert G.  
Kintigh  
For Tree Farm  
Management  
July 1960  
C.S. 51/106

RE-RENEWED, SEE CORNER NO. #210

RE-RENEWED, SEE CORNER NO. #28

RE-RENEWED, SEE CORNER NO. #147

RE-RENEWED, SEE CORNER NO. #191

RE-RENEWED, SEE CORNER NO. #185

RE-RENEWED, SEE CORNER NO. #184

RE-RENEWED, SEE CORNER NO. #34

RE-RENEWED, SEE CORNER NO. #164

FD. OK 12/78  
J. PROCHNAU  
C. S. 50/186  
& STATE HWY  
C. S. 82-11  
5/23/77