

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 11 R. W. W. M.

1/4 CORNER BETWEEN 13-18 (T 21 S, R 12 W) West side of this Tp.  
Set 1 1/2 in. iron pipe (Computed by proportional measurement)  
12" Alder bears N 21° W 6.2 ft.  
14" Alder bears S 89° E 14.0 ft. See 40/169 **9**

SEC. COR. 19-20-29-30  
Set from old B. T.  
Set 1 1/2 in. iron pipe  
5" Fir bears N 21° E 5 lks. dist., marked T 21 S R 11 W  
S 20 B T. (Now 7 in. in diameter) See 40/169 **10**

SEC. COR. 17-18-19-20  
Set 1 1/2 in. iron pipe from proportional measurements, from which  
42" spruce on S side of fence bears N 27 1/2° W 72.3 ft.  
West corner gate post on E-W fence bears N 52 1/2° W 139.7 ft.  
South edge of 2 story white house bears S 65° E.  
See 40/169 **11**

1/4 COR. BETWEEN 18-19  
Set a 1 1/2 in. iron pipe from proportional measurement.  
in open pasture, no reference points available. See 40/169 **12**

1/4 COR. BETWEEN 17-18  
Set 1 1/2 in. iron pipe by proportional measurements.  
Point on W side of canyon, above bare rock outcrop and 75.0 ft.  
West of creek.  
8 in. Alder bears S 18° W 11.5 ft.  
6 in. Alder bears N 20° E 10.0 ft. See 40/169 **13**

1/4 corner Sec. 1&2  
Found old stakes N'K'D.  
1/4 C. S.  
Set steering gear of an auto  
Old stump decayed to badly to identify checks for dist. & bearing.  
Orig. 10" cedar (burned badly) no scribe. Marks visible. Checks b & d.  
30" cedar S 43° E 26 ft. 8" Alder S 28° W 17 1/2"  
See 40/169 **14**

Section corner to secs. 11, 12, 13 and 14.  
I found an old fir stump with cruiser marks S. 55° E., 29.7 feet, a 92  
inch fir snag N. 75 1/2° E., 31.9 feet, an 80 inch fir stump NE 4 1/2° W.,  
43.4 feet, and the remains of an alder tree S 9° W., 25 feet. No  
scribe marks were found but trees check well for bearing and dist.  
recorded in notes of original survey, although two did not check for  
size. The topography on the lines from the corner checked well with  
the notes.

I set a 1 inch x 78 inch Aluminum pipe 36 inches in the ground located  
by intersection of arcs from above described fir bearing trees;  
From which:  
80 inch DF stump bark scribed Sec. 11, T 21 S, R 11 W., BT bears  
N. 87° 31' W., 43.4 feet.  
92 inch DF snag scribed Sec. 12, T 21 S, R 11 W BT bears N. 74° 32' E.,  
31.9 feet.  
32 inch DF tree bark scribed Sec. 13, T 21 S, R 11 W BT bears **15**  
S. 85° 38' E., 90.2 feet.  
94 inch DF tree scribed Sec. 14, T 21 S, R 11 W BT bears S. 79° 36' W.,  
104.3 feet.

1/4 corner to secs. 1 and 12.  
This corner was located midway between the sec. corners common to these  
two sections.  
I set a 1 inch x 60 inch Aluminum pipe 33 inches in the ground, **16**  
from which:  
24 inch cedar with forked top scribed "BT 1/2 S 1" bears N 64° E 11.6  
feet.  
24 inch cedar scribed "BT 1/2 S 12" bears S 77° W., 52.0 feet.

Survey made for Walter A. Pyrits by  
Harry S. Ingall - Reg. Surveyor  
January 15, 1949  
C. S. 19/169

B. A. Jans  
April 14, 1938  
C. S. 19/184

Robert G. Kintigh  
July, August, 1956  
C. S. File No. 42/170.