

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 21 T. S. R 11 R.W.W.M.

KOBE-CHAPMAN CO., EUREKA, ORE. 91001

101

C O N T -----

(Center South 1/16 Sec. 4)

4" below stump top stamped: "Douglas County Surveyor"

T 21 S
C
CS 1/16 | S 4
C
R 11 W
1977

BT's - A 12" Hemlock bears S.24°E., 88.7 ft. Double blazed and scribed "CS 1/16 S4 CS BT".
A 34" Hemlock stump with boat spike stamped "80" bears N.67 1/2°E., 69.6 ft.

9/20/77

102

Center 1/4 Corner for Sec. 4

No monuments or accessories found.

Set - a 1" Iron pipe with brass cap 4" above ground stamped: "Douglas County Surveyor"

T 21 S R 11 W
C 1/4 S4
1977

BT's - A 12" Cedar bears S.70°E., 23.4 ft. double blazed and scribed "C 1/4 S4 CS BT".
A 8" Cedar bears N.46°E., 21.0 ft. double blazed and scribed "C 1/4 S4 CS BT".

Note: Corner lies on North line of clearcut unit.

9/20/77

103

North E 1/16 Corner for Sec. 4

No monuments or accessories found.

Set - Brass cap on 1" Iron pipe, 2" above ground and stamped: "Douglas County Surveyor"

T 21 S
N E 1/16
S 4
R 11 W
1977

BT's - A 30" Alder bears N.35°E., 19.4 ft. bark scribed "NE 1/16 S4 CS BT".
An 18" Maple bears S.41°W., 81.2 ft. double blazed and scribed "NE 1/16 S4 CS BT"

9/20/77

104

Center North 1/16 Corner for Sec. 4

No monuments or accessories found.

Set - 1" x 30" Iron pipe with brass cap attached at corner point as determined by single proportion. Cap is 3" above ground marked "Douglas County Surveyor"

T 21 S R 11 W
C
N 1/16 | S 4
C
1977

BT's - A 20" D. Fir bears N.58 1/2°W., 4.1 ft. Tree double blazed and knife scribed "CN 1/16 S4 CS BT".
A 9" Cedar bears S.9 1/2°W., 10.4 ft. Tree double blazed and knife scribed "CN 1/16 S4 CS BT"

9/20/77

105

1/4 Corner for Sec. 6 and Sec. 31 of T20-11

No monuments or accessories found.

Position determined by single proportionate measurement.

Set - At the corner point we set a 1" x 30" I.P. 26" in the ground # 240 on a steep SE slope, with brass cap attached marked

County Surveyors Office
T 20 S
R 11 W - 8 31
S 6
T 21 S

29.8 ft.

BT's - A 18" D. Fir double blazed & scribed "1/4 S6 CS TT" bears S.18°W
A 14" D. Fir double blazed & scribed "1/4 S31 CS BT" bears N.31°W., 18.3 ft.

Corner is located approx. 100 ft. east of top of spur ridge running NE.

Douglas County Surveyors Office

Gary L. Langlitz

R. B. Kimberling - P. L. Earle - S. J. Flaue

September, 1977 For Doug. Co. Land Dept. (See CS File 59/32)

C. S. 59/40

RM 3-13

RE-RECORDED CORNER NO. 240