

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 21                      T. S.                      R 11                      R. W. W. M.

EDGE-CHAPMAN CO., EUGENE, ORE. 21881

Douglas Co. Surveyors Office

Gary L. Langlitz  
R. B. Kimberling  
P. L. Earle  
S. J. Flause  
April, 1978  
C.S. 59/46

Richard J. Hintz  
PLS #497  
For: Champion Inter-  
national Corp.  
March 1978  
M 70 - 10

**109**

1/4 Corner for Sec. 5 and Sec. 32 of T20-11.  
Set - A 1" x 36" I.P. with brass cap set 6" above ground in a 30" mound of stone and marked: "Douglas County Surveyor" 1978  
T 20 S R 11 W  
1/4 S 32  
S 5  
T 21 S R 11 W

BT's - A 9" Spruce bears S.14°E., (55°@+25°) 49.8 ft. I double blaze and scribe "1/4 S5 CS BT".  
A 7" D. Fir bears N.20°E., (69.0@+35°) 56.8 ft. I double blaze and scribe "1/4 S32 CS BT".  
Corner is 5 ft. North of a westerly stream.

4/19/78

**110**

NE 1/16 Sec. 5.  
Set - A 1" x 36" I.P. with brass cap set 6" above ground and marked "Douglas County Surveyor" 1978  
T 21 S R 11 W  
NE 1/16  
S 5

BT's - A 18" D. Fir bears S.74°W., 18.9 ft. I double blaze and scribe "NE 1/16 S5 CS BT".  
A 19" D. Fir bears N.24°W., 4.7 ft. I double blaze and scribe "NE 1/16 S5 CS BT".  
Corner is approx 65 ft. West of ridge top.

4/25/78

**111**

C-E 1/16 Section 5  
Set - A 1" x 36" I.P. with brass cap set 3" above ground and marked: "Douglas County Surveyor" 1978  
T 21 S R 11 W  
E 1/16  
C S C

BT's - A 4" D. Fir bears N.77 1/2°E., 69.6 ft. I double blaze and scribe "CE 1/16 S5 CS BT"  
A 16" Spruce bears N.79°W., 45.9 ft. I double blaze and scribe "CE 1/16 S5 CS BT".  
Corner is 45 ft. East of a north-south ridge.

4/25/78

**112**

C-N 1/16 Section 5.  
Set - Corner location determined by survey. At the corner point, we set a 1" x 30" I.P. 28" in the ground with brass cap attached marked: "Douglas County Surveyor" 1978  
T 21 S  
C  
N 1/16 S 5  
C  
R 11 W

BT's - A 21" D. Fir scribed "CN 1/16 S5 CS BT" on a double blaze bears N.77°W., 66.6 ft.  
A 24" D. Fir scribed "CN 1/16 S5 CS BT" on a double blaze bears N.54°E., 91.7 ft.  
Corner located approx. 30 ft. West of small creek, course S.50°W.

4/25/78

**113**

1/4 Corner for Secs. 30 and 29.  
Set - Iron pipe with brass cap from which:  
36" White Fir bears S.69°W., 40.4 ft. scribed.  
60" Cedar, bears S.31°30'E., 80.8 ft. scribed.

3/78

**114**

Section corner for 30 and 29 only.  
Set - Iron pipe with brass cap from which:  
20" Cedar bears S.87°E., 106.8 ft. scribed.  
28" Spruce bears S.52°E., 48.4 ft. scribed.  
18" Maple bears N.66°30'W., 29.4 ft. scribed.

3/78

**RE-RENEWED, SEE CORNER NO. #155**

**RE-RENEWED, SEE CORNER NO. #151**