

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 11 R.W.W.M.

FORE-CHAPMAN CO. EUGENE, ORN. 97401

Ronald Stuntzner
For: Moore Mill
and Lumber
June 20, 1979
M 78 - 79

M 78-79 8/15/83

Meander Corner between Secs. 32 and 33 123
Set - Chipped "X" in rock face
From which:
8" D. Fir bears N.44°E., 10.8 ft.
34" D. Fir bears East 49.3 ft.
Witness corner is a 5/8" Iron rod 11.05 ft. North of true corner.

RE-RENEWED, SEE CORNER NO. #192

South 1/4 Corner for Sec. 30 only. 124
Set - 5/8" Iron rod approx 20 ft North of Butler Creek Road
From which:

RE-RENEWED, SEE CORNER NO. #154

1" Pipe bears N.72°56'W., 83.35 ft.
20" Spruce bears S.59°10'W., 68.3 ft.
10" Alder bears S.62°40' E., 40.5 ft.

Robert Ward Jr.
For: Champion Inter-
national Corp.
August, 1979
M 78 - 76

1/4 Corner for Sec. 6 and 7 125
Set - 2 1/2" Brass cap attached to a 2 1/2" x 30" Galv. iron pipe
with flared bottom.
BT 's- 13" Alder bears S.30°59'E., 19.6 ft. Bark scribed; N 1/4, S7, BT.
15" Fir, bears N.62°55'W., 25.0 ft. scribed; S 1/4, S6 BT.

Center 1/4 Corner for Sec. 6 126
Set - 2 1/2" Brass cap attached to a 2 1/2" x 30" Galv. iron pipe with
flared bottom
BT's - 16" Fir bears N.31°00'W., 24.3 ft. scribed C 1/4 S6 BT.
13" Fir bears N.38°00'E, 20.4 ft. scribed C 1/4 S6 BT.

Richard Hintz.
October 1979
C.S. 58/176

Survey in progress in
sections 1, 11, 12 and
13.

Will be filed later.

Section corner for Secs. 6 & 7; and Secs. 1 & 12 of T.21-12 127
Set - 2" I.P. with brass cap
from which:
12" Fir bears N.54°E., 15.8 ft.
12" Fir bears S.31°E., 9.7 ft.
10" Hemlock bears S.39°W., 38.8 ft.
12" Fir bears N.43°30'W. 9.8 ft.
All trees scribed. Corner falls in 'cat' road.

1/4 Corner for Sec. 7; and sec. 12 of T.21-12. 128
Set - 2" I.P. with brass cap
from which:
14" Hemlock bears N.46°E., 17.9 ft.
18" Spruce bears S.48°30'W., 11.0 ft.
Both trees scribed.

Filed as M 79-30
3/1984

10/13/79

FD. 11/90 M 111-10

Ronald Stuntzner
For: Internation-
al Paper Co.
Dec. 1979
M 81 - 43

1/4 Corner for Sec. 11 and Sec. 14 129
Set - 2" x 36" brass cap with iron pipe stamped " PLS 1342 1/4 S11/14
1979".
BT's - 8" Chittum bears N.65°W., 14.7 feet.
10" Douglas Fir bears S.76°E., 12.4 feet.
Note - No evidence of original corner found, set by proportionate
distance.

NO. #233

1/4 Corner for Sec. 6; and Sec. 1 of T.21-12. 130
Set - Stamped 2" I.P. with brass cap from Which:
12" Fir bears S.31°30'E., 45.2 ft. scribed.
10" Fir bears N.25°00'W., 11.0 ft. scribed.

RE-RENEWED, SEE CORNER NO. 243

Center 1/4 Cor. for Sec. 23 131
Set - 2 1/2" x 26" Alum. capped alum. pipe mkd: "T21S R11W C1/4 S23 1980
PLS 1342".
BT's - 14" D. Fir bears N.43°W., 59.2 ft.
11" Maple bears S.70°E., 29.5 ft.

See M 84 - 51 Filed Jul. 1980 by Ronald E. Stuntzner

7/80

Richard J. Hintz
For: Champion International
and International Paper
March 1980
M 79-30 & C.S. 58/140