

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 S T. S. R 11 W R.W.W.M.

KOVE-CHAPMAN CO., EUGENE, ORE. 97401

132

1/4 Cor. to Secs. 23 and 24
Fd. - 2 1/2" Brass Cap set in 1957 by B.L.M.
30" D. Fir brs. N.27°E., 26.5 ft.
Other BT's of record not verified.
New BT's - 28" D. Fir bears N.14°W., 31.9 ft.

7/80

133

Sec. cor. to Secs. 22,23,26 and 27.
Fd. - 2 1/2" Brass Cap set in 1960 by B.L.M. properly mkd. #171
10" D. Fir bears N.13°W., 17.2 ft.
Blown down D. Fir BT's in NW, SW, and SE quadrants.
New BT's - 10" D. Fir bears N.22°E., 21.7 ft.
26" Maple bears S.48°E., 110.0 ft. with scribed bark.
No acceptable witness monuments in S.W. quadrant.

7/80

134

1/4 Cor. to Secs. 23 and 26
Fd. - 5/8" I.R. bears S.42 1/2°W., 215.0 ft. set in survey for
Cone Lumber Co. dated Aug. 19, 1974. See Ren. #74.
Thoroughly searched for original corner stone and was not
found, therefore set this corner at proportional distance.
Set - 2 1/2" x 36" Alum. capped alum. pipe mkd: "T21S R11W 1/4
S23 S26 1980 PLS 1342"
BT's - 20" D. Fir bears N.45°W., 18.0 ft.
24" D. Fir bears S.12°E., 73.6 ft.

7/80

135

Sec. Cor. to Secs. 23,24,25, and 26.
Fd. - Original sandstone corner monument. One scribe groove mark
visible.
1968 20" D. Fir stump with alum. poster nails as per U.S.F.S.
corner perpetuation notes. Scribes now burned with chop
marks visible.
Set - 2 1/2" x 36" alum. capped alum. pipe mkd. "T21S R11W S23,S24,
S25 and S26 1980 PLS 1342".
New Assessories - 24" D. Fir stump bears N.50°E., 2.5 ft. Section
24 BT.
30" D. Fir stump bears S.44°E., 12.3 ft. Section
25 BT.
Mkd. "X" in rock face bears N.72°W., 36.3 ft.
Mkd. "X" in rock bluff bears S.6°W., 14.0 ft.

7/80

136

Section corner for Secs. 1 and 2 ; and Secs. 35 & 36 of T.20-11.
Set - Scribed "X" on rock 4" underground for corner. Unable to set BC I.P.
which I deposit alongside corner; built sandstone mound on top of
corner stone.
BT's 12" D. Fir N.44°W., 12.9 ft. "S35 BT" FO OK 12/90
10" D. Fir S.24°W., 3.4 ft. "S2 BT" M111-47 A-F
14" D. Fir S.49°E., 7.5 ft. "S1 BT"
10" D. Fir N.89°E., 12.9 ft. "S36 BT"
Chopped "X" on 10" D. Fir, West 12.2 ft.
Set - On July 29, 1980 the corner was revisited. A stardrill was driven
into the bedrock at the corner point on left extending 8" above
the surface. A 2" x 12" B.C. I.P. filled with concrete was
placed over the stardrill and stamped: T20S R11W S35 S36 S2 S1
T21S R11W PLS 1342 1980.

137

1/4 Corner for Section 1; and Sec. 36 of T.20-11.
Set - 2" B.C. I.P. at proportionate distance for 1/4 corner marked: 1/4
S36 T20S R11W S1 T21S R11W 1980.
BT's - 22" D. Fir, S.52°E., 18.3 ft. "1/4 BT"
40" Maple N.65°W., 14.7 ft. "1/4 BT".

7/24/80

Ronald E. Stutzner LS#1342
For: International Paper Co. and Siuslaw National Forest
May 1980
M 84 - 51

Ronald Stutzner
For: Coos Head
Timber Company
July 24-29, 1980
M 84 - 62

FO OK 12/90
M111-47 A-F