

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 11 W. R.W.W.M.

4046-CHAPMAN CO., EUGENE, ORE., 97301

157

1/4 Corner common to Secs. 5 and 8.  
Found - 1967 Doug. Co. B.C. Ren. #47.  
BT's - 21" double cedar stump (most westerly) bears N.23°E., 46.7-ft. (1967)  
no scribing visible. Set 8" nail in top, center of wstly. stump.  
27" maple bears S.21°E., 57.3-ft. (1967) No scribing visible.  
11/82

158

Section corner for Secs. 7, 8, 17 and 18  
Set - Replaced a leaning 1 1/2" x 54" I. P., plugged at top, with  
Brass cap and iron pipe. Placed the Iron pipe upside down  
and 0.3 ft. north of the Cap. Date set unknown. (See Ren. #33)  
Found - 46" fir bears N.25°W., 29.8 ft. (Rec. 27.1 ft.) Chopped face  
with marks visible. (1891)  
48" fir bears N.42°E., 25.8 ft. (Rec. N.45°E, 29.7 ft.) Scar  
visible. (1891)  
19" rotten fir stump bears S.72°W., (Rec. S.66°W.) 18.4 ft. (1891)  
New BTs 16" fir bears S.41°E., 49.1 ft. scribed T21S R11W S17 BT.  
24" fir bears S.82°W., 40.8 ft. scribed T21S R11W S18 BT.

159

Section corner for Secs. 8, 9, 16 and 17  
Found - 1978 Douglas Co. brass cap and a plugged 1 1/2" I.P. extending  
2.8 ft. above ground, on the west edge of the brass cap. Ren. #107  
28" rotten fir stump bears N.74°W., 19.3 ft. (orig. Rec. N.75°W.,  
23.1 ft.) Scribed: BT  
24" rotten fir stump bears N.23°E., 10.1 ft. (orig.) (rec. N.30°E.,  
9.2 ft.) No scribing visible.  
36" fir stump bears S.58°W., 16.3 ft. (orig.) (rec. S.55°W., 15.8 f  
Scribed: S17 BT  
14" rotten fir stump bears S.69°E., 23.6 ft. (orig.) (Rec. S.65°E.,  
24.4 ft.) No scribing visible.  
17" fir snag, 15 ft. tall, bears S.41°W., 16.5 ft. (1918) Chopped  
open, rotted blaze.  
48" fir bears S.15°W., 81.7 ft. (Rec. S.11 1/2°W., 79.6 ft.)  
X bark scribed alongside healed blaze. (1959)  
24" fir snag, 18 ft. tall, bears S.22°E., 107.4 ft. (1959)  
(Rec. S.26°E.) Scribe marks visible.  
18" maple bears S.68 1/2°E., 32.7 ft. (Rec. 30.3 ft.) Scribed:  
T21S R11W S16 CS BT. (1978)  
21" alder bears N.13°W., 52.0 ft. (Rec. 52.7 ft.) Bark scribed:  
T21S R11W S8 CS BT (1978)  
New BT - 12" forked alder bears N.54°E., 50.6 ft. Bark scribed: T21S R11W  
S9 BT (1982)

160

1/4 Corner for Secs. 16 and 17  
Found - 1959 Douglas Co. brass cap with iron pipe. Ren. #75  
22" fir stump bears N.44°W., (Rec. N.48 1/2°W.) 7.7 ft. No  
scribing visible.  
16" fir stump bears S.31°E., 5.7 ft. No scribing visible.  
27" fir bears N.77°E., 15.3 ft. Healed blaze. No scribing  
visible.  
New BT - 24" spruce bears S.18°E., 34.3 ft. Scribed W 1/4 S16 BT (1982)

161

1/4 Corner for Secs 17 and 20  
Set - A 2 1/2" brass cap on a 1" x 48" I.P. driven flush with the ground,  
in an open pasture. Cap is stamped with PLS 1988.  
BTs - 16" alder bears S.34°43'E., 222.3 ft. Scribed: N 1/4 S20 BT.  
16" fir bears S.88°58'E., 287.6 ft. Scribed: N 1/4 S20 BT.  
16" alder bears N.46°45'W., 437.8 ft. scribed: S 1/4 S17 BT.  
Power pole 10-67 bears N.6°28'E., 268.4 ft.  
11/82

162

W.C. to 1/4 Cor. common to Secs. 28, & 29. Ren. # 148.  
Found - Orig. fir cor. tree, now a badly rotted 48" stub. #189  
Set - 1 1/4" x 36" I.P. w/B.C. stamped P.L.S. 497 bears East 4.3-ft.  
New BTs - 12" fir bears N.52°E., 12.6-ft. to 50d nail in center.  
18" fir bears S.9°W., 16.6-ft. to 50d nail in center. (scribed)  
14" fir bears S.25°E., 9.7-ft. (overgrown blaze). 12/82  
This map amends M 70 - 74

Ronald G. Geisler L.S. #1988  
For: Champion International Corporation  
November 1982  
M 93 -34 C.S. 58/278

Richard J. Hintz  
PLS #497  
For: International  
Paper Co.  
Dec., 1982  
M 93 - 47

RE-EXAMINED  
SEE CORNER #189