

**Douglas County Surveyor's Record of
Government Corners Renewed**

T.21 S. T.S. R. 11 W. R.W.W.M.

Richard J. Hintz
PLS #497
For: International
Paper Co.
Dec., 1982
M 93 - 47

Center 1/4 Corner of Sec. 29, Ren. # 118. 163
Set - 1 1/4" x 36" I.P. w/B.C. mkd: PLS #497.
New BOs - 42" fir stump bears N.80°E., 128.6-ft. to RR spike in face (scribed)
RR spike w/4" washer set in bedrock bears S.16°E., 5.6-ft.
This map amends M 70-74. 12/82

Richard Hintz
For: International
Paper Co.
Nov. 1983
M 95 - 40

1/4 Corner for Sections 12 and 13. (SEE ALSO Ren. #24) 164
Set - 1 1/4" x 36" I.P. with stamped brass cap, PLS 497 1983.
BTs - 14" alder bears S.24° 30'W., 10.5 ft.
8" hemlock bears N.83°30'W., 20.9 ft.
Both trees scribed.

Section corner for Secs. 12 and 13; and 7 and 18 of T.21-10 165
Found - Original 60" cedar corner tree which is now an uproot.
Set - a 50-d nail in the upturned roots from which:
Orig. 24" cedar BT, now 40" bears S.12°W., 30 ft. #202
I measured to a point 12" from the center of the tree, assuming the record
distance of 24.9 ft. was taken from the face, i.e. 1/2 of the original
24" diam. cedar bearing tree.

Richard J. Hintz
For: International
Paper Co.
February, 1984
M 96 - 5

1/4 Corner for Sections 1, & 2. Ren. #14. 166
Fnd - 1/2" I.P. w/aluminum alloy fixture (origin unknown) from which:
BT - 50" cedar bears S.44°30'E., 19.9-ft. (1891 BT, Rec. S.43°E.,
22.4-ft.)
New BT - 28" cedar S.81°30'W., 44.7-ft. scribed. 2/84

North 1/4 Sec. Corner of Sec. 12. 167
Fnd - 1" aluminum pipe (out of position) set by Kintigh, Ren. #16.
bears N.85°03'W., 118.47-ft. No original BTs fnd.
Set - 3/4" x 30" Iron Rod w/2" aluminum cap stamped PLS 1342 and as
prescribed, half way between the NW & NE Corners of Sec. 12.
New BTs- 24" cedar bears S.7°W., 18.0-ft. (I scribed).
12" alder bears N.52°E., 24.4-ft. (I scribed).
Note - Corner is on the south slope of hill. 2/84

Section Corner for Secs. 1, & 12, and Secs. 6, & 7 of T.21-10. 168
Set - 3/4" x 30" I.R. w/2" aluminum cap stamped PLS 1342 and as
prescribed, from bearing tree and ridge calls:
Fd. - Dist. to creek to the north was 14.92ch. 1866 survey dist. was
15.0 ch. & 1891 survey 15.2 ch.
Dist. to ridge to the east was 3.06 ch. 1919 survey dist. was
3.00 ch.
Dist. to ridge to the south was 1.50 ch. 1891 survey dist. was
1.50 ch. & 1919 survey was 3.32 ch.
The two 28" cedars recorded in 1891 survey as bearing S.1/2°E.,
& S.1/2°W., 66-lks., have grown together forming a 48" cedar,
bearing S.1°E., 43.6-ft. (66lks.). The face is closed.
36" cedar snag w/face 44.2-ft. (67lks.) S.81°E. The 1891 call
was a 10" cedar N.81°E., 67lks.
Note - Corner is on the north face of a hill at the top of a slide area. 2/84

1/4 Sec. Corner for Secs. 11 & 12. 169
Fnd - No orig. BTs found. *FD 11/90 M 11-10*
Set - 3/4" x 30" I.R. w/2" aluminum cap stamped with PLS 1342 and as
prescribed, half way & on line between the SW & NW Sec. corners
of Section 12.
New BTs- 30" cedar bears S.69°W., 19.5-ft. (I scribed) # 230
10" cedar bears S.61°E., 16.9-ft. (I scribed)
Note - Corner is on the SE slope of a hill, 150-ft. above a creek. 2/84

Center 1/4 Sec. Corner of Sec. 12. 170
Set - 3/4" x 30" I.R. w/2" aluminum cap stamped with PLS 1342 and as
prescribed, at the intersection of the E-W and N-S center-
lines of the section.
New BTs- 14" alder bears S.58°W., 13.9-ft. (I scribed).
12" alder bears N.46°E., 27.8-ft. (I scribed).
50" cedar bears S.10°E., 59-ft. (NOT scribed). 2/84

Addendum: Sec. corner for Secs. 1 and 12; and 6 & 7 of T.21-10 # 168
I scribe:

- 10" D. fir, N.40°E., 40.9 ft.
- 9" cedar, S.89°E., 47.9 ft.
- 12" alder S.45°E., 10.5 ft.
- Double 28" cedar, S.1°E., 43.6 ft.

THIS INFO ADDED 12/19/84 J.R.

Ronald E. Stuntzner, PLS #1342
For: International Paper Co.
February 3, 1984
M 96 - 23

*See Exhibit
for Additional
Info.*

RE-RENEWED, SEE CORNER NO. # 230