

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 11 R.W.W.M.

808-CHAPMAN CO., EUREKA, CALIF. 91001

171

Section corner for Secs. 22, 23, 26 and 27

Found - 1960 BLM brass cap.

BLM BT a 14" D. fir bears N.13°W., 17.2 ft. healed face.

Stuntzner BT a 10" D. fir bears N.22°E., 21.7 ft. healed face

Stuntzner BT a 26" maple bears S.48°E., 110.0 ft. Ren. #133

Set - 3" alum. cap on 2 1/2" x 30" alum pipe reference monument, bears
N.55°56'51"E., 48.55 ft. mkd. RM S22 S23 S27 S26 1984 PLS
1305 48.55

172

1/4 Corner for Sections 23 and 26

Found - 3" alum. cap on 2 1/2" alum. pipe set by Stuntzner. Ren. #134

21" D. fir stump bears N.45°W., 18.0 ft. visible scribe.

24" D. fir bears S.12°E., 73.6 ft. vis. scribe.

Set - Ref. Mon. a 2 1/2" brass cap on a 1" iron pipe bears
S.35°48'45"E., 47.25 ft. mkd. R.M. 47.25 1/4 S26 1984
PLS 1305.

173

1/4 Corner for Sections 25 and 26

Set - 2" alum. cap on 1/2" x 30" alum. pipe stamped per BLM manual and
with PLS 1305.

New BT - 6" D. fir bears N.6°W., 32.9 ft. scribed 1/4 S26 BT.

Set - Reference Monument, a 2" alum. cap on 1/2" x 18" I.R. bears
N.56°E., 21.2 ft. mkd. "RM 1/4 S26 S25 1984 PLS 1305 21.2

174

Section corner for Secs. 26 and 25 only

Set - 3" alum. cap on 2 1/2" x 30" alum. pipe stamped per BLM manual and
with PLS 1305. Rock mound.

New BTs - 16" D. fir bears N.52°W., 89.8 ft. scribed T21S R11W S26 BT.

36" D. fir bears N.59°E., 27.5 ft. scribed T21S R11W S25 BT.

175

Closing Corner, Sections 35 and 36

Set - 2" alum. cap on 24" x 1/2" iron rod in sandstone. Cap stamped per
BLM manual and with PLS 1305. Rock mound.

New BTs - 16" D. fir bears S.3°E., 25.1 ft. scribed T21S R11W S36 CC BT.

12" D. fir bears S.59°W., 23.5 ft. scribed T21 R11W S35 CC BT.

176

South 1/4 Corner for Sec. 26 only.

Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM
manual and with PLS 1305.

New BTs - 26" D. fir bears N.9°W., 55.8 ft. scribed 1/4 S26 BT.

26" D. fir bears N.60°W., 76.8 ft. scribed 1/4 S26 BT.

177

1/4 Corner for Section 35 only. North boundary.

Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM
manual and with PLS 1305. Rock mound

New BTs - 20" D. fir bears S.16°W., 25.7 ft. scribed 1/4 S35 BT.

24" D. fir bears S.51°E., 33.3 ft. scribed 1/4 S35 BT.

178

1/4 Corner for Sections 26 and 27

Set - 3" alum. cap on 2 1/2" x 30" alum. pipe with cap stamped per BLM
manual and with PLS 1305. Rock mound.

New BTs - 23" D. fir bears N.31°W., 18.2 ft. scribed 1/4 S27 BT.

26" D. fir bears N.47°E., 16.2 ft. scribed 1/4 S26 BT.

179

Section corner for Secs. 27 and 26 only.

Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM
manual plus PLS 1305.

New BTs - 40" D. fir bears N.78°W., 44.9 ft. scribed T21S R11W S27 BT.

20" D. fir bears N.5°E., 83.5 ft. scribed T21S R11W S26 BT.

James W. Prochnau L.S. #1305
For: U.S. Forest Service
Feb. 24, 1984
M 96 - 62 C.S. 58/294 and
M 96 - 61 A & B