

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 11 R. W. W. M.

FORE-CHAPMAN CO., EUREKA, ORE. 97111

James W. Prochnau PLS #1305
For: U.S. Forest Service
February, 1984
M 96 - 63 A & B - C.S. 58/294

Section corner for Secs. 28 and 29 only. South boundary 188
Found - 5/8" iron rod set by Stuntzner LS 1342. Ren. #119
Stuntzner BT, a 42" hemlock bears N.14°W., 55.2 ft. (Rec. N.16°W.) Visible scribing.
Orig. BT, a 36" cedar bears N.10°E., 23.1 ft.
Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM manual and with LS #1305. Rock mound buried iron rod.
New BT - 15" hemlock bears N.70°W., 63.5 ft. scribed T21S R11W S29 BT.
Set - Reference monument - 2" alum. cap on 1/2" x 24" iron rod bears N.17°12'51"E., 50.17 ft. marked RM SW S28 1984 PLS 1305 50.17

Witness corner for 1/4 corner Sections 28 and 29 189
Found - Remains of orig. corner tree, a 44" rotten Fir snag.
2 1/2" brass cap on 1 1/4" I.P. for W.C. set by Hintz 4.3 ft. east of corner. Ren. #162
3/4" G.I.P. 0.3 ft. west of cap set by Haines LS #239. M34-30
Hintz BT, 13" D. fir bears N.48°E., 13.0 ft. (Rec. N.52°E., 12.6 ft.) Vis. scribe.
Hintz BT, 24" D. fir bears S.9°W., 16.5 ft. (Rec. 16.6 ft.) vis. scribe.
Orig. BT, 50" D. fir stump bears S.3°E., 324.0 ft. (Rec. 510 lks.)
Set - Reference monument - 3" alum. cap on 2 1/2" x 30" alum. pipe bears N.2°16'35"E., 58.72 ft. mkd. RM W C 1/4 S28 1984 PLS 1305 58.72

Center 1/4 Corner for Section 28 190
Set - 2" alum. cap on 1/2" x 18" I.R. in rock mound. Cap mkd T21S R11W C 1/4 S28 1984 PLS 1305.
Set - W.C. - 3" alum. cap in 2 1/2" x 30" alum. pipe bears S.87°13'30"W. 42.26 ft. on line from true corner mkd. T21S R11W WC 42.26 C 1/4 S28 1984 PLS 1305.
Set - Ref. monument to true corner - 2" alum. cap on 1/2" x 18" I.R. bears N.78°29'07"E., 54.3 ft. mkd. RM C 1/4 S28 1984 PLS 1305 54.3
Set - Ref. monument to W.C. - 3" alum. cap on 2 1/2" x 30" alum. pipe bears N.75°29'43"E., 168.27 ft. mkd. RM 168.27 WC C 1/4 S28 1984 PLS 1305
New BT - Scribed BT to true corner: 10" D. fir bears S.47°E., 20.0 ft. scribed C 1/4 S28 BT.
New BTs to witness corner:
13" D. fir bears N.58°W., 14.2 ft. scribed X BT.
10" D. fir bears S.45°W., 4.8 ft. scribed X BT.

Closing Corner for Secs. 32 and 33. 191
Found - 1" brass disk on T-iron. Ren. #20
Orig. BT, 55" rotten spruce snag bears N.26°W., 17.8 ft.
Hootman BT - 31" spruce bears N.9°W., 34.5 ft. (rec. N.11°W., 34.2 ft.) healed face.
Hootman BT - 38" alder bears S.41°W., 47.6 ft. (Rec. S.24°30'W., 47.1 ft.) visible scribe.
Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM manual and with PLS 1305. Rock mound.
Note: Haines monument for orig. CC bears S.2°40'43"E., 39.89 ft.
New BT - 32" spruce bears S.33°W., 7.5 ft. scribed T21S R11W CC S32 BT.
Set - Reference monument, 3" alum. cap on 2 1/2" x 30" alum. pipe bears S.57°41'14"E., 24.87 ft. mkd. RM CC S33 1984 PLS 1305 24.87

James W. Prochnau PLS #1305
For U.S. Forest Service
February, 1984
M 96 - 64 A&B C.S. 58/294