

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 11 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

James W. Prochnau
L.S. #1305
For: U.S. Forest
Service
Feb. 1984
M 96 - 64 A&B
C.S. 58/294

192

Witness corner for Meander corner, Sections 32 and 33
Found - "X" chopped in rock face by Stuntzner, LS 1342 bears S.54°38'E.,
0.38 ft. from true position. See Ren. #123
Stuntzner BTs: 9" fir bears N.44°E., 10.8 ft. healed face.
34" fir bears East, 49.3 ft. healed face
Stuntzner W.C.: 5/8" iron rod 11.05 ft. North from "X". Iron rod
is 0.80 ft. east of true line.
Set - Wit. Cor. 3" alum. cap on 2 1/2" x 30" alum. pipe 11.27 ft. North
on line from true position. Cap stamped per BLM manual and
with PLS 1305.
New BTs - 10" madrone bears N.73°W., 7.0 ft. scribed X BT. (scribed to W.C.)
8" D. fir bears S.38°E., 11.1 ft. scribed X BT. (scribed to W.C.)

193

Witness Corner for 1/4 Cor. for Secs. 34 and 35.
Set - W.C.- 3" alum. cap on 2 1/2" x 30" alum. pipe bears N.4°03'44"W.,
30.00 ft. from true corner. Cap stamped per BLM manual and with
PLS 1305.
Found - 47" forked spruce bears S.10°E., 5.0 ft. healed face. Ren. #2
43" spruce bears S.75°W., 24.0 ft. healed face. Ren. #2
New BT - 6" alder bears S.56°E., 10.6 ft. bark scribed X BT.
Set - Ref. monument - 3" alum. cap on 2 1/2" x 30" alum. pipe bears
N.71°30'24"W., 50.82 ft. from W.C. marked RM W.C. S34/S35 1984
PLS 50.82

194

Witness Corner for Meander Corner for Secs. 34 and 35
Set - 3" alum. cap on 2 1/2" x 30" alum. pipe North 63.37 ft. from
true position.
New BTs - 16" alder bears S.81°W., 15.9 ft. bark scribed X BT.
16" alder bears N.52°E., 29.2 ft. bark scribed X BT.

195

1/4 Corner fro Section 34; and Sec. 3 of T22-11
Found - 1 1/2" I.P. (no record)
Orig. BT a 62" spruce bears S.30°E., 50.1 ft. (S.31 1/2°E., 47.5 f
rec) healed face.
Hootman BT, a 26" forked spruce bears N.70°E., 16.3 ft. (rec.
N.70°W., 14.5 ft.)healed face. Ren. #28
Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM
manual and with PLS 1305. Rock mound.

196

CC for Sections 31 and 32 only.
Set - Set proportioned closing corner at point of true intersection
with south bdy. of Sec. 30. No substantial evidence found of
original C.C. See Ren. #120
Set 5/8" x 30" Iron rod with plastic I.D. cap mkd. "Stuntzner
Engineering".
1979 BT - 20" W. Fir bears N.15°W., 203.0 ft. (healed face).
New BT - 16" Alder bears S.49°E., 79.2 ft. (bark scribed T21S R11W
R11W S32 BT)

197

1/4 Corner for Sections 31 and 32.
Set - Set proportioned quarter corner, no evidence of original corner
found and called gulch, course south did not fit field.
Set - Set 5/8" x 30" Iron rod with plastic I.D. cap mkd. "Stuntzner
Engineering". See Ren. #121
New BTs-40" D. fir bears S.61°E., 59.3 ft. (1979 BT)
50" D. fir bears S.38°E., 8.4 ft. (scribed 1/4 S32 BT).

April 1984

198

Center 1/4 Corner for Section 17.
Set - 2 1/2" x 30" alum. pipe with 3" alum. cap mkd. PLS 497 C 1/4 S17
1984 T21S R11W.
BTs - 28" fir bears N.65°00'E., 22.4 ft. scribed C 1/4 S17 BT.
Reference monument, a 3" alum. cap on a 2 1/2" x 30" alum. pipe bears
N.86°10'W., 51.6 ft. stamped"RM C 1/4 S17 PLS 497, 1984 S.86°10'E,
51.6 ft."

Richard Hintz LS 497
For: International
Paper Co. & U.S.
Forest Service
Oct. 1984
M 97 - 56

10/84