

Douglas County Surveyor's Record of
Government Corners Renewed

T 21

T. S.

R 11

R. W. W. M.

ROSS-CHAPMAN CO., EUGENE, ORE. 97401

Herman Pieske
AA Surveying Service
For: U. S. Forest
Service
Nov. 1984
M 97 - 77 A & B

Section corner for Sections 13 and 24 only. #217 206
Found - 50" D. fir corner tree found. Healed faces on north and south sides. Bark scribes "R11W S24" visible on south side; "S 1" visible on NW side.
46" Obl D. fir bears S.64°E., 41.0 ft. Axe work on bark (tag reads obliterated N55°W 63.41 ft.) (Rec. S.55°E., 63.4 ft.)
54" D. fir bears S.22°W., 25.2 ft. with healed face.
30" D. fir bears N.89°W., 17.9 ft. healed burly face.
50" Obl. D. fir bears N.73°E., 18.5 ft. small healed face.
Reference monument, a 2 1/2" x 30" alum. pipe 25" in the ground, with 3 1/4" alum. cap mkd "USDA Forest Service T21S R11W S19 RM N89°44'W 6.0 ft. RLS 1651 1984 Unlawful to Disturb", bears S.89°44'E., 6.0 ft.

Robert B. Ward Jr.
RLS #1091
For: Champion Inter-
national Corp.
Oct.-Nov. 1984
M 97 - 79
C.S. 58/146

1/4 Corner for Sections 7 and 18 207
Found no trace of 1867 GLO corner or its accessories.
Set - At point of proportionate measure, set a 2 1/2" brass cap on a 2 1/2" x 30" I.P. with the following accessories:
12" alder bears S.8°16'E., 38.1 ft. (1984 BT) bark scribed 1/4 S18 BT.
13" alder bears N.57°19'W., 12.2 ft. (1984 BT) bark scribed 1/4 S7 BT.

Center 1/4 Corner for Section 35 208
Found - Unrecorded 1 1/2" iron pipe, bears N.87°20'19"E., 113.45 ft. from true corner.
BT. to unrecorded 1 1/2" pipe: 21" D. fir snag, bears S.30°E., 10.5 ft., with healed face.
Set - 3" alum. cap mkd. T21S R11W C 1/4 S35 1985 PLS 1305 on 2 1/2" alum. pipe. Rock mound.
New BT - 9" D. fir, bears N.43°E., 28.3 ft., scribed C 1/4 S35 BT.
New BO - Reference monument, a 3" alum. cap on 2 1/2" alum. pipe, bears N.31°42'23"E., 40.92 ft., Mkd. RM C 1/4 1985 PLS 1305 40.92

James W. Prochnau
PLS #1305
For: U. S. Forest
Service
June 1985
M 98 - 79 A&B

1/4 Corner for Sections 35 and 36 209
Found - 2" iron pipe, 3 ft. out of ground, set by Lewis (PE 722 1939). Lewis BTs: 15" (4' high) snag stump, bears S.30°W., 1.5 ft., visible scribe.
32" D. fir bears N.40°E., 10.5 ft., with healed face.
Set - 3" alum. cap mkd. T21S R11W 1/4 S35 S36 1985 PLS 1305, on 2 1/2" alum. pipe. Rock mound.
New BO - Reference monument, a 3" alum. cap on 2 1/2" alum. pipe, bears S.24°13'47"W., 53.88 ft., mkd. RM 1/4 S35 S36 1985 PLS 1305 53.88

M.C. for Sections 35 and 36 only (see Rev. #17) 210
Found - 2 1/2" I.P. with screw cap for Byars original M.C. as found by Lecklider in 1958.
Set - 3" alum. cap mkd. T21S R11W S35 S36 MC 1985 PLS 1305, on 2 1/2" alum. pipe filled with concrete.
New BTs - 16" alder, bears N.16°W., 53.5 ft., scribed T21S R11W S35 MC BT
11" alder, bears N.10°E., 63.6 ft., scribed T21S R11W S36 MC BT

James W. Prochnau
PLS #1305
For: U.S. Forest
Service
August, 1985
M 99 - 21 A&B

Witness Corner to M.C. in Sec. 36 211
Set W.C. - U.S. Forest Service 3 1/4" aluminum cap with magnet on a 2 1/2" by 30" aluminum, flared pipe, mkd. PLS 1305. USFS cap and pipe bears N.89°34'32"E., 74.38 ft. on line from true position.
New BT's - 13" Alder, bears N.46°W., 13.8 ft., bark scribed "X" BT.
8" Alder, bears N.19°E., 15.6 ft., bark scribed "X" BT.