

Douglas County Surveyor's Record of
Government Corners Renewed

21 T.S. 11 R.W.W.M.

ROSE CHAPMAN CO., EUGENE, ORE. 97401

212

James W. Prochnau
PLS #1305
For: U.S. Forest
Service
August, 1985
M 99 - 21 A&B

Section Corner for secs. 1 (T22-11) and 6 (T22-10) ONLY.
Found - Original stone, 6" x 12" x 22" in upright position. Buried stone.
BT's - Possible remains of original cedar BT, now a windfall out of position.
Set - A U.S. Forest Service 3 1/4" aluminum cap with magnet on a 2 1/2" by 30" aluminum flared pipe. Mkd. PLS #1305. Also set rockmound.
New BT's- 7" R. Cedar, bears S.14°W., 24.8 ft., scribed T22S R11W S1 BT.
11" R. Alder, bears S.22°E., 41.2 ft., scribed T22S R10W S6 BT.

213

West 1/4 Corner for Section 31 Only (T21-10)
Found - A 1" x 30" iron post set by GLO in 1919 at corner position, cap has been broken off. Buried pipe.
BT's - 38" Maple, bears N.80°E., 33 ft., no marks.
Set - A U.S. Forest Service 3 1/4" aluminum cap with magnet, on a 2 1/2" x 30" aluminum flared pipe. Mkd. T21S R11W R10W 1/4 S31 1985 PLS 1305. Rockmound.
New BT's- 12" Maple, bears N.67°E., 88.5 ft., scribed 1/4 S31 BT.
18" Maple, bears S.19°E., 49.1 ft., scribed 1/4 S31 BT.

214

1/4 Corner for sections 13 & 14.
Found - A 2 1/2" Iron Pipe with brass cap (B.L.M. 1957).
B.O.'s - A 2 1/2"x30" Al. Pipe with a 3 1/4" USDA - F.S. Aluminum cap stamped " R.M. N84°59'W, 1/4*S13 48.8', 1986 P.L.S. 497."
BT's
Found - 60" D. Fir bears S28°E, 35.6', closed face.
66" D. Fir bears S19°W, 30.0'(record S19 1/2°W, 31.0). with closed face.

215

Section Corner for 13,14,23&24
Set - 5/8" x 20" Iron Rod with 3 1/2" USDA FS Aluminum cap driven 10" into bedrock marked "T21S R11W 14,13,23,24, 1986 P.L.S. 497".
Found - 12" Maple bears S40°E, 27.8' (record 27.1') with closed face.
40" sawed D. Fir stump bears S56°W, 30.5', (record S58 1/2°W, 31.7') with closed face.
20" sawed D. Fir stump bears N 75°W, 65.3'(record N74°W, 66.0') with closed face.
B.O.'s
Set - N.E. Bearing tree is missing. (No new tree accessible).
5/8" x 16" Iron Rod with 3 1/4" USDA-F.S. Aluminum cap drilled 6" into a rock outcrop and marked "T21S R.M., R11W,N73°44'E 40.8', S23, 1986 PLS 497".

216

East 1/4 corner S13 only. Ren #204
Found - 3 1/4" USDA-FS Aluminum cap.
BT's
Found - 12" Hemlock bears S70°W, 7.8'(7.9'rec), partially closed face vis.
18" D. fir snag bears N65°W, 4.0'.
14" Hemlock bears N 2 1/2°W, 31.7', opened face, visible BT
B.O.'s
Set - 2 1/2" x 30" Aluminum pipe with 3 1/4" USDA FS Aluminum cap marked "R M , T21S R10W S1°26'W, 40.7' ↓ S18, 1986, P.L.S. 497".

217

Section Corner for sections 13 & 24. Ren #206
Found - 36" D. Fir Corner tree. Healed faces on North and South sides
Bark scribed "R11W S24" visible on the South "S 1" visible on the N.W. side
B.O.'s
Set - 2-1/2"x 30" Alminum pipe with a 3-1/4" USDA-FS Aluminum cap marked "T21S R11W S19 RM N89°44'W, ←6.0', R.L.S. 1651, 1984."

Richard J. Hintz LS 497
For: Sitka National Forest
July 1986
M 102 - 19