

Douglas County Surveyor's Record of
Government Corners Renewed

21 T. S. 11 R.W.W.M.

Richard Hintz LS# 497
For: Siuslaw National Forest
July, 1986
M 102 - 19

Continued...
Found - 46" Obliterated D. Fir bears S64°E, 41.0", (rec. S55°E, 63.4').
Axe work on bark.
54" D. Fir bears S22°W, 25.2' (rec. S21°W, 29.7'). **217**
Well healed face.
30" D. fir bears N89°W, 17.9' (rec. N89-1/2°W, 9.9').
Well healed face.
50" Obliterated D. fir bears N73°E, 18.5', with well healed face.

----- **218**
1/4 Corner Sections 13 & 24.
Found - 2-1/2" Iron pipe/brass cap in mound of stone (B.L.M. 1957).
50" Cedar bears S40-1/2°E, 11.7' (rec. S42°E, 12.5').
With closed face.
24" D. fir bears N15-3/4°W, 52.5' (rec. 50.8). With closed face.
Set - 2-1/2" x 30" Aluminum pipe with 3-1/4" USDA-FS Aluminum cap
marked "RM 1/4 S13, S1°18'E, ↓42.0', 1986 PLS 497".

FD. 22. 11/10 M 11/10

1/4 Corner Sections 10 and 11. **219**
Found - Brass cap and accessories of record.
BT's - 32" Cedar bears N 3 1/2° W, 24.4 ft. See Ren#144
38" Cedar Stump bears S63°E, 54.0 ft. (Record S71°E, 55.4 ft.)
16" Fir bears West, 93.1 ft.
10" Cedar bears N 12°E, 84.0 ft.

Meander Corner - Section 9 and 10. **220**
Set - 3/4"x5' Aluminum rod with 3" aluminum cap marked
"PLS 1093, 1987". and IP Timberlands Operating Co."
BT's - A 6" Alder bears N 72 1/2°W, 15.9 ft.
Scribed - 12" Alder bears N 59°E, 53.3 ft.

1/4 Corner Section 10 & 15. **221**
Found - A 2" Iron Pipe (No previous record).
BT's - A 46" fir stump bears N 24°E, 7.3 ft. to face letters
"BT" visible on face (No previous record).
Set - A 3/4" x 2' Aluminum rod with 3" aluminum cap in found
iron pipe marked "PLS 1093, 1987, IP Timberlands Oper-
ating Co."
BT's - A 10" Alder bears N52 3/4°W, 49.2 ft.
Scribed - 12" Alder bears S 57°W, 5.0 ft.

Center 1/4 Corner Section 15. **222**
Set - A 3/4" x 3' Aluminum rod with 3" aluminum cap
marked " PLS 1093, 1987, IP timberlands Operating Co."
BT's - A 6" Fir bears S 58 1/2°E, 20.5 ft. See BLM Resurvey
Scribed- 10" Cedar bears N 55 1/4°E, 22.5 ft.

1/4 Corner Sections 14 and 15. **223**
Found - A Brass Cap and accessories of record
BT's - A Maple bears S29 1/2°W, 59 links. See BLM Resurvey
Scribed- A 10" Cherry bears S 53°E, 5.7 ft.

Section Corner for Secs. 18, 19 and Secs. 13 & 24 of T. 21-12 **224**
Found - 2" iron pipe extending 16" out of ground. Ken. #116
16" hemlock bears N. 68°W. 27.0 ft. with healed face.
24" fir bears S. 6 1/2°W. 8.4 ft. with healed face.
20" fir stump bears S. 62 3/4°E. 24.6 ft. with healed face.
20" fir stump bears N. 72 1/4°E. 26.8 ft. with healed face.
Set - Replaced 2" I. P. with 3 1/4" alum. cap mkd. per 1973 Manual of
Instructions and with LS 1091.

Center 1/4 Corner for Section 18. **225**
Set - 3 1/4" Alum. cap mkd. LS 1091.
New BTS - 14" fir bears S. 2 3/4°W. 8.2 ft. scribed "C 1/4 S18 BT".
14" fir bears S. 74 3/4°E. 11.7 ft. scribed "C 1/4 S18 BT".
1/6/88

Eugene Wobbe
For: International Paper Co.
May, 1987
M 104 - 43 A & B

Robert B. Ward, Jr.
For: International
Paper Co.
Jan. 6, 1988
M 105 - 64