

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 21 T. S. R 11 R.W.W.M.

FOUR CHAPMAN CO. EUGENE, ORE. 91881

Les Roberts  
L.S. 1039  
For: International  
Paper Co.  
Nov. 27, 1990  
M 111 - 9  
C.S. 63/126

North 1/4 Corner for Section 30 232  
Set - 3/4" X 36" alum. rod with 3 1/4" alum cap by single proportionate  
measure. Buried purple magnetic marker under alum. rod. Set  
60" alum post with land monument sign beside alum. rod.  
New BTs - 27" fir stump S.31°E., 32.4 ft. R.R. spike/painted red.  
35" hemlock stump, N.85°W., 5.3 ft. R.R. spike/painted red.  
Corner lies on steep north slope about 25 ft. north of ridge. Ridge  
bears NW. and SE.  
Renewal # 83 11/90

Les Roberts  
L.S. 1039  
For: Internatl.  
Paper Co.  
Nov. 20, 1990  
M 111 - 10  
C.S. 63/126

CORNER REPORT ONLY 233  
South 1/4 Corner Section 11.  
Found - 2" X 36" iron pipe w/brass cap as set in survey M 81 - 43.  
BTs. - 9" Cascara, N.53°W., 14.1 ft. (bark scribed) 1979 BT.  
Record- N.65°W., 14.7 ft. Renewal No. 129  
15" Fir, S.82°E., 12.3 ft. (bark scribed) 1979 BT.  
Record S 76°E., 12.4 ft.  
11/90

Harvey Wilcox  
R.L.S. # 2244  
For: U.S.F.S.  
December 1990  
M 111 - 47 A-F

North East Corner Section 1. 234  
Found - 2 1/2" brass cap on 1 1/4" IP. 12" above ground with 1" IP along side.  
BTs Fnd. 30" maple S.E. trunk of tree with healed face, tags  
bears N.14°W., 15.2 ft. to side center. Ren. # 51  
21" douglas fir, healed face, tags, bears N.80°E., 83.6 ft.  
37" douglas fir, healed face, tags, bears S.77°15'E., 42.9 ft.  
39" maple, healed face, tags, bears S.27°W., 11.2 ft.  
Note - This tree trunk has blown down (39" maple) retagged another  
trunk of the same tree, it bears S.25°30'W., 14.20 ft.  
Set RM - Std. U.S.F.S. disk "RMT20S R10WS31 S88°09'W 52.91' 1990 RLS 2244"  
bears N.88°09'E., 52.91 ft.  
12/90

FO. OK 2/92 BY STUNTZNER  
M114-50

Richard J. Hintz  
for Robert Cowan  
April 1975  
C.S. 58/47-2

1/4 corner for sec. <sup>19</sup>24 & <sup>24</sup>19 235  
Fd. - Original BT, 30" Spruce, bears S.46°W., 26.4'  
1" I.P., bears S.67°55'W., 12.07'  
Set - 1" I.P./B.C.?

Clyde F. Mulkins  
for I.P. Timberlands  
Jan 18 1994  
M118-62

1/4 corner for sec. <sup>19</sup>24 & <sup>24</sup>19 236  
Fd. - 1" I.P. at 1/4 corner  
BTs Fd.- 40", GLO Spruce stump, bears S.46°W, 26.4'(slope dist)  
36", 1891 Glo Hemlock uproot remains, (1857 GLO 36" spruce),  
bears S.9°E., 13.2' (slope dist)  
38", Spruce stump, bears S.5°E, appox 15', Do. Co. Tag  
Unrecorded Stuntzner BTs:  
16", Alder, bears N.14°W., 35.8', bankscribed "1/4 S24 BT"  
38", Cedar, bears S.17°W., 26.0', "X" chopped into it (tag  
reads 34' at 64%)  
35", Spruce, bears S.49°E., 10.9', "X" chopped into it (tag  
reads N.57 1/2°W., 11')  
19", Alder, bears N.28°E., 31.7', scribed "1/4 S19 BT".

Sec. corner to 18,19,13 & 24 237  
Fd. - 3 1/4" Alum cap with 3/4" x 30" Alum rod  
BTs Fd.- 19", Hemlock with a healed face, bears N.68°W., 27'  
20", DF stump with a healed face, bears N.72 1/2°E., 26.8'  
27", DF with a healed face, bears S.6 1/2°W., 8.4'  
New BTs- 07", WF I scribe "S13 T21S R12W BT", bears N.1°W., 35'

1/4 corner for sec. 18 & 13 238  
Fd. - 2 1/4" County Brass cap  
BTs Fd.- 39", DF Stump with healed face, bears N.80 1/2°W., 61.7'  
22", Spruce with healed face, bears S.82°E., 29.3' (record S.83  
3/4°E., 29.5')  
New BTs- 21", Alder I scribe "1/4 S18 BT", bears N.41°E., 8.4'  
18", Spruce I scribe "1/4 S18 BT", bears S.47°E., 35.8'

CLYDE MULKINS  
FOR I.P. Timberlands  
Jan 18 1994  
M118-62