

Douglas County Surveyor's Record of
Government Corners Renewed

21

T. S.

11

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

L.E. Monrean
P.L. Earle
J.H. Cook
C.S. 59/2
2/12/76

E. 1/16 Corner to Section 5 and 8 Ren #46 81
Found -1967 County Surveyors Brass cap properly marked at 1/16 corner.
BT's- 6" Dia. D. Fir bears S 8°E., 6.8 ft, tree blazed and scribed "E 1/16 S8
CS BT" Tree is dead.
14" now 15" diameter D. Fir bears N 50°E., 14,1 ft. Tree has good blaze, do not
open for scribe.
New BT's- 11" D. fir bears S 31 1/2°E., 25.0 ft. Tree double blazed and
scribed. Mag. Dec. 20°East 2/12/76

M. Lenora Ladig
Jim Cook
Karen Cheney
D.C. Surveyor's
Office
C.S. 59/15
May 24, 1976

Witness corner for 1/4 corner for Sec. 36 only, T.21-12. 82
Found - 1971 DCSO brass cap properly marked. Ren. #65
From which:
A 17" Maple bears N.82°E., 67.0 ft. Tree is alive with visible
scribing "WC CS BT" in double blaze.
Found no trace of bearing objects. (S.W. one in swamp area.
N.W. one has tree uprooted over area.
New BT - 12" Fir bears N.5°W., 49.0 ft. scribed "WC 1/4 C.S. BT" in
double blaze.
Note - True corner lies in marsh. See M 42 - 27.

5/24/76

~~1/4 Corner for Secs. 19 and 30.~~ *NOT PROPER 1/4 CORNER - SEE* 83
REVISED SURVEY M 70-77
Set - 5/8" Iron Rod *(CORNER LEFT IN FIELD.) # 8/81 CORNER REMOVED.*
From Which: *SEE M 88-52*
A 28" W. Fir bears West, 32.7 ft. scribed
A 16" Hemlock bears S.50°E., 22.3 ft. scribed.
RE-RENEWED, SEE CORNER NO. # 232

Richard J. Hintz
For: International Paper Co.
Sept. 1976
M 62 - 1

Section Corner For Secs. 19 and 30; and Secs. 24 & 25 of T21-12, 84
Set - 5/8" Iron Rod FD OK 11/90
M III - 9
From Which:
A 34" Cedar, bears N.71°E., 36.7 ft. scribed.
A 26" Hemlock, bears S.82°E., 23.6 ft. scribed.
An 18" Hemlock, bears S.5°E., 22.7 ft. scribed.
A 16" Cedar, bears N.58°W., 58.1 ft. scribed.
Corner is on top of ridge which bears NW & SE.

Larry E. Monrean, Douglas Co. Surveyors Off.
Pete Earle
Mike Tompkins
Dec. 15, 1976
C.S. 59/26

1/4 Corner for Sec. 30; and Sec. 25 of T.21-12. 85
Set - 5/8" Iron Rod FD OK 11/90
M III - 9
From Which:
A 60" Fir, bears N.45°W., 1.8 ft. to an aluminum nail in face, bark
scribed.
18" Spruce, bears S.9°E., 31.5 ft. scribed corner is approx.
120 ft. north of USFS road.
Sept. 1976

*FD OK 5/19/80
S. ALVARADO
C.S. 61/4*

Sec. Corner for 5 and 4; and Secs. 32 & 33 of T20-11. 86
Found - 1964 DCSO brass cap. Cap is firmly in place, 4 inches above
ground. On south edge of a 5" Hemlock stump. Ren. #30
Orig. 33" now 58" Fir stump bears N.75°E., 28.4 ft. (to face)
Tree has opened blaze, scribing no longer legible, fragmentary
reverse scribing found.
7" Hemlock bears S.79 1/2°E., (Rec. S.83°E.) 12.7 ft. Tree double
blazed partially healed, scribing visible "R11W S4 CS". This
tree is now a dead snag.
16" now 21" Hemlock, bears S.87°W., (Rec. S.85°W.) 30.8 ft. Tree
double blazed, partially healed, scribing visible "25R8"
18" now 22" D. Fir. bears N.57°W., (Rec. N.58°W.) 30.3 ft. Tree
has a well healed double blaze.
11" Hemlock bears N.65 1/2°E., (Rec. N.62°E.,) 20.3 ft. Tree has open
double blaze, visible scribing "20S R11 S33 CS BT" This tree is
dying.
New BT's - A 11" Hemlock, bears S.76 1/2°E., 23.0 ft. Tree double blazed and
scribed "T21S R11W S4 CS BT".
A 10" Hemlock bears N.72°E., 42.5 ft. Tree double blazed and
scribed "T20S R11W S33 CS BT".

12/15/76