

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 11 R. W. W. M.

XXXX CHAPMAN CO., SUGAR, ORE. FIRE!

95

1/4 Corner for Secs. 20 and 21.
Found - Orig. 60" Fir bears N.85°W., 4.0 ft. (now rotted snag, 25 ft. high).
Set - 5/8" Iron rod from which:
36" Fir bears S.61°W., 36.2 ft. scribed.
12" Hemlock bears S.7°30'W., 51.0 ft. scribed.

8/77

Richard Hintz
For: International
Paper Co.
Aug. 1977
M 66 - 48

1/4 Corner for Secs. 16 and 21.
Set - 5/8" Iron rod
From which:
28" Cedar stump bears N.72°19'E., 57.87 ft. scribed. (Dist. and bearing to 60 penny nail in face.)
6" Alder bears S.2°E., 7.9 ft. scribed.
Corner is 3 ft. east of a creek, course N.20°E.

96

RE-RENEWED, SEE CORNER NO. #153

8/77

97

Center 1/4 Corner for Sec. 21.
Set - 5/8" Iron rod
From which:
72" Cedar stump bears S.82°42'W., 95.48 ft. scribed (Dist. and bearing to R.R. spike in face).
10" Maple bears N.26°30'W., 10.4 ft. scribed.

8/77

98

1/4 Corner for Secs. 4 and 3
No monuments or accessories found.
Set - A 1" x 30" Iron pipe at 1/4 corner position determined by single proportion. Monument set 27" deep, cap is marked:
"County Surveyors Office"

T 21 S
1/4 S 4 | S 3
R 11 W
1977

New BT's- A Maple, multi-trunk, 48" bears S.11°E., 55.6 ft. Double blaze and scribe "1/4 S3 CS BT" on a 10" trunk.
A 10" Alder bears N.73°W., 33.6 ft. to base. Tree bark scribed "1/4 S4 CS BT".

Note: Corner lies on a southerly slope approx. 80 ft. west of N-S cutting line in an old clear cut.

9/19/77

99

Center East 1/16 Sec. 4.
No monuments or accessories found.
Set - 5/8" x 30" Iron Rod in road way 6" below surface. Place alum. cap on Iron rod marked "Douglas Co. Surveyor
C E 1/16 S 4 C 1977"

New BT's- An 18" Cedar bears N.74 1/2°E., 44.8 ft. Tree double blazed and scribed "CE 1/16 S4 CS BT"
An 8" Hemlock bears N.44 1/2°W., 46.5 ft. Tree is double blazed and scribed "CE 1/16 S4 CS BT"

9/19/77

100

South E 1/16 Corner for Sec. 4
No monuments or accessories found.
Set - 1" x 30" Iron pipe 26" deep with brass cap attached at corner
Cap marked: "Douglas County Surveyor"

T 21 S R 11 W
S E 1/16 S 4
1977

New BT's- A 8" D. Fir bears N.47 1/2°W., 16.6 ft. Tree double blazed and scribed "SE 1/16 S4 CS BT".
A 9" W. Fir bears S.67°W., 16.8 ft. Tree double blazed and scribed "SE 1/16 S4 CS BT".

9/20/77

101

Center South 1/16 S 4.
No monuments or accessories found.
Set - A 5/8" x 30" Rebar one foot below top of remains of a 42" Fir stump. The rotted center of which we dug out and filled with rocks and dirt. Set a 1"x36" I.P. over 5/8" rebar with brass cap

CONT. NEXT PAGE

Douglas County Surveyors Office
Gary L. Langlitz
R. B. Kimberling - P. L. Earle - S. J. Flause
September, 1977 For Doug. Co. Land Dept. (See C.S. File 59/32)
C.S. 59/40

RM 3-13