

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 12 R. W. W. M.

CORNER TO SECS. 22, 23, 25 & 27, Twp. 21 S. R. 12 W. #78 1  
Set a hemlock post 4" square firmly in the ground and properly marked, from which  
An Alder 20" diam. bears N. 19° E. .50 lks. dist.  
An Alder 20" in diam. bears S. 28° E. .46 lks. dist.  
A Spruce 12" in diam. bears S. 32° W. .57 lks. dist.  
An Alder 15" in diam. bears N. 69° W. 47 lks. dist.

REESTABLISHMENT OF THE A. C. GIBBS DONATION LAND CLAIM, #87 2  
Twp. 21 S. R. 12 W. The South West Corner of Silver Bank.  
Set a fir post 4" square firmly in the ground and properly marked, from which *See also old #36*  
An Alder 6 (12)" diam. bears S. 59° E. 32 lks. dist.  
An Alder 12" diam. bears N. 58° E. 44 lks. dist.

The South East Corner.  
Set a spruce post 4" square firmly in the ground, properly marked, from which 2A  
An Alder 20" diam. bears S. 58° E. 25 lks. dist.  
An Alder 20" diam. bears N. 75° W. 12 lks. dist.

The North East Corner.  
Set a spruce post firmly in the ground and properly marked, from which #86 2B  
An Alder 12" diam. bears S. 48° W. --lks. dist.  
A Spruce 20" diam. bears N. 33° W. 10 lks. dist.  
A Spruce 20" diam. bears S. 15° E. 36 lks. dist.  
A Spruce 8" diam. bears S. 35° W. 48 lks. dist.

COR. BET. SECS. 32 & 5 ON S. RDY OF 21-12 3  
Set in a 6" x 48" Sp. stake, from which  
A Spruce 20" diam. bears N. 36° W. 22 lks. dist.  
Both stakes found

N. E. COR. OF D.L.C. 37 Ext. "L" 4  
Set 4" x 4" x 4" post from old P.T. standing, which was a  
12" Alder S. 58° E. 25 lks. (See info. in Rev. #55) 1/16

COR. 13, 18, 19, 24, T. 21 S. R. 11 & 12 W. 5  
There was an Iron pipe 2" x 6" driven in ground for this corner by previous surveyor, the old bearing trees gone but remains of stump check with field notes, but buried so had no scribe marks visible, did not mark new tree on account of being too far off. (See Rev. #3 - T21-11) 16

SEC. COR. 14, 15, 22, 23 6  
Location identified from old stake and a P.T. Fir 24" dia. S. 42° W. scribed T. 21 S. R. 12 W. S. 22. The stake & tree are not original but were set approximately 35-40 years ago. Set a 2 1/2" x 2 1/2" x 48" post for corner, from which  
A Fir 50" diam. bears S. 82° W. 50ft. T. 21 S. R. 12 W. S. 22 S. S. P.T.  
Alder 15" diam. bears N. 70° E. 23.4 ft. T. 21 S. R. 12 W. S. 14. S. S. P.T.  
Alder 15" diam. bears S. 33° E. 47.0 ft. T. 21 S. R. 12 W. S. 22. S. S. P.T. 25  
Fir 50" diam. bears N. 38° W. 32.3 ft. T. 21 S. R. 12 W. S. 15. S. S. P.T.  
This location fits topography as records original field notes.

MEANDER COR. BET. SEC. 15-22 on Rt. Bank of Umpqua River. 7  
Location determined from line West from Sec. Cor. 14, 15, 22, 23, and falls in a drainage ditch. Set a 6" x 6" x 15" block of concrete in top of dike, 33 ft. west of corner for a witness corner and set 2" x 6" x 48" post along side.

COR. BET. SECS. 15 & 16 8  
Set by proportional measurement between sec. cor. 10, 15, 16 and meander cor. 15-16. Drove an iron pipe 1" x 48" flush with the ground & set a 4" x 36" post alongside from which

(over)

Found 5/24/26  
Among P. Cairns notes  
W. C. Bowker  
old Vol. 1 Renewed Corners Pg. 16

(Pg. 16 Old Rev. Vol. 1)  
Jan. 25, 1925 J. Ford  
Treas. Coin M. C. Bowker  
Harry Henderson H. L. Epstein  
Witness  
H. L. Epstein 3/17/1925  
C. S. 5.5.16/25

Ben P. Irvin  
Witness  
H. E. Richardson  
Loren Geber  
6.5.16/25  
7/15/1940

(Old Rev. Vol. 1, Pg. 16)  
Secs. 14, 15, 22, 23  
Pg. 16  
25

Secs. 14, 15, 22, 23  
Pg. 16  
25

RE-RENEWED CORNER NO. #78

RE-RENEWED CORNER NO. #86

RE-RENEWED CORNER NO. #86

RE-RENEWED CORNER NO. #38