

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 12 W. R. W. W. M.

KORR-CHAPMAN CO., EUBANK, DRE. 51881

22

Sec. Cor. to Secs. 7 & 18, T21-11W. & Secs. 12 & 13, T21-12W.
Found - 1 1/2" Iron Pipe in poor condition & remains of Orig. BT's.
Orig. 24", now 36" Hemlock, badly decayed remains of stump, N. 23° E.
10.6 ft., no scribe found.
Orig. 48", now 50" Spruce, badly decayed stump, N. 19° W. 5.9 ft.,
scribe visible on old blaze.
Other Orig. BT's. would have been destroyed by very old logging
road, no unusable.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 21 S R
(Reset old Pipe & old Office 12 S 12 S 7 11
5/8" I. Rod fd. while digging) W S 13 S 18 W
1970

New BT's: 10" Cedar N. 31° E. 26.0 ft. mkd: T21S R11W S7 CS BT.
12" D. Fir S. 53° E. 16.6 ft. mkd: T21S R11W S18 CS BT.
12" Cedar S. 15° W. 5.2 ft. mkd: T21S R12W S13 CS BT.
12" Cedar N. 61° W. 14.3 ft. mkd: T21S R12W S12 CS BT.

This corner lies about 100 ft. N. of slough, course N.W. and
20 ft. N. of old logging road, course N.W.

FD OK 1/28
R. WARD
C.S. 63/70

4/3/70
23

Sec. Cor. to Secs. 18 & 19, T21-11W. & Secs. 13 & 24, T21-12W.
Found - 2" Iron Pipe at corner, 12" above ground, See Ren. #16.
16", now 16" D. Fir, S. 8° W. 8.4 ft., shows pitched over scribing.
14", now 14" D. Fir S. 60° E. 24.7 ft., shows pitched over scribing.
13", now 13" D. Fir, N. 77° E. 27.2 ft., shows pitched over scribing.

New BT: 12" Hemlock N. 67° W. 26.4 ft. scribed T21S R12W S13 CS BT.

3/27/70
24

1/4 Corner to Sec. 18, T21-11W and Sec. 13, T21-12W.

This corner set from survey as shown, 1/4 corner prorated. # 103

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's R T 21 S R
11W S13 S18 11W
1970

New BT's: 38" D. Fir N. 80° W. 62.20 ft. scribed "1/4 S13 CS BT".
12" Spruce S. 82° E. 29.3 ft. scribed "1/4 S18 CS BT".

Also Found - 2" I. Pipe, S. 3° W. 48.22 ft. from 1/4 Corner, See C.S. 40/169
and Ren. #12. Creek bears West 25.0 ft.

FD OK 1/28
R. WARD
M 105-44

25

Section Corner to Sections 14 - 15 - 22 - 23.

Corner re-established in 1929 by Eppstein, See Ren. #6.

Found - 2 1/2" x 2 1/2" Post set by C.S. Eppstein, scribing visible, from which:

26" Fir bears S. 46° W. 40.0 ft., face pitched over. This BT.

is not an Orig. according to Eppstein, it was scribed
btwn. 1890 & 1895, 4 notched & x scribed, with tags.

42" Fir Snag bears N. 28° W. 32.3 ft., face visible, axe marks,

has 4 notched & x scribed in tree. Eppstein does not
make reference to, but believe same as above.

62" Fir Stump bears N. 38° W. 32.3 ft. (cut low to ground) No

evidence of face set by Eppstein in 1929.

Set - 2" x 30" I.P. with brass cap mkd: T21S R12W 15 14
22 23
1970
650

FD OK 12/92 34 BAKER
M 116-46

from which:

6" alder bears S. 44° E. 9.6 ft., scribed S23 BT, with tag.

32" spruce bears N. 23° E. 45.6 ft., scribed S14 BT, with tag.

Set 2 fence posts with signs + 5 ft. N. facing W. & 5 ft. E. facing S.

FD OK
7/85
O.G. Hutcherson
M 99-13
M 101-32

U. S. Forest Service
Tom O. McCullough
April, 1970
C. S. File No. 55/148

26

Sec. Corner to Secs. 30 & 31, T21-11W. & Secs. 25 & 36, T21-12W.

Found - Orig. 30" D. Fir, now down, N. 36° E. 59.4 ft., found bark
scribe "2" and other marks.

Cedar, down in draw, possible BT. No trace of other BT's.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 21 S R
Office 12 S 25 S 30 11
1971 W S 36 S 31 W

New BT's: 6" Spruce N. 55° W. 36.8 ft., scribed "S25 CS BT".

22" D. Fir North 32.3 ft. scribed "T21S R12W S25 CS BT".

38" Spruce N. 48° E. 45.5 ft. scribed "T21S R11W S30 CS BT".

No trees to the south

This corner lies about 12 ft. north of ravine, running E - W.

N. PIPE
POK: HUNT
10/21/76

John K. Powell
W. Penly & J. Heritage
C.S. File No. 56/1

2/9/71

MARCH 1971