

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 12 R. W. W. M.

NOBLE CHAPMAN CO., EUGENE, ORE. 31887

45

Sec. Corner for Secs. 5 and 4; and 32 and 33 of T20-12.
Found - Orig. 8" Hemlock, really only 5" when scribed, now 12" scribed
T12W (?) R20S S33. From it relocated cor. S.63°W., 49.5 ft.
Creek West 75.5 ft.
Crayon mkd: 5' Spruce stump, S.28°E., 27.1 ft. RP BT S4, out 27.1 ft. ✓
6' Spruce stump, RP BT S5 out 106.7 ft. S.83°W., 106.5 ft.
6' Spruce stump, RP BT S32, out 98.1 ft. N.70°15'W., 98.2 ft.
3' Hemlock stump RP BT S33, out 41.4 ft. N.83°E., 41.4 ft.
to spike in top of stump.
N.86°30'E., 72.2 ft. to face of old blaze 86 yrs. old on
3' Spruce stump. W side of truck road.
Set - 1 1/2" I.P. 2x2x5 Fir post Crayon mkd. S32 S33 T20S R12W
S 5 S 4 T21S R12W
July/Aug. 1943

46

1/4 Corner for Secs. 5 and 4.
Found - Both bearing trees to 1/4 corner and relocated corner with 1 1/2"
I.P. and 2x2x5 Fir Post crayon mkd. 1/4S S5 S4 July 24, 1943
From which bears:
Orig. 36" Douglas Fir, now 4.0ft. S.83°E., 13.2 ft. to nail
scribed 1/4S (BT covered)
Orig. 16" D. Fir, now broken off snag, 8 ft. tall, N.73°W.,
5.94 ft. to nail scribed 1/4S BT.
I crayon mkd. 3' D. Fir, N.73°W., 10.5 ft. RP BT 1/4 S 5.
Corner stands on south slope of small ridge course E & W.
7/24/43

FD. 0540
1941-43
1942-43

W. G. Corbitt
H. Hendrickson
for Crown Zellerbach
1941-43
C.S. 52/91

47

Section Corner for Secs. 5,4,8 and 9.
Found - Orig. 24" Spruce BT and from it relocated the corner as all alders
were missing. FD. 0540/1942-03
Set - 1 1/2" I.P. and 2x2x4 ft. Cascara post crayon mkd. S5 S4 July 27, 1943.
From which Bears: S8 S9
Orig. 24" Spruce Now 5 ft. S.81°E., 14.52 ft. scribed
BT. rest covered with 30' overgrowth.
I crayon mkd. 7 ft. Spruce S.15°W., 40.75 ft. RP BT S8
6 ft. Spruce N.82°W., 63.5 ft. RP BT S5
7/27/43

48

1/4 Corner for Secs. 4 and 9.
Found - Orig. BT bearing SW which is dead Spruce snag from it reset cor:
Set - 1 1/2" I.P. and 2x2x5 ft. Spruce post crayon mkd. 1/4S S4 S9
Aug. 19, 1943 W.G. Corbitt, form which bears:
Orig. 12" Fir, now 25" Spruce snag 30 ft. high S.27°W., 17.84 ft.
to scribed face 1/4 S or 17.6 ft. to nail.
BT's - 4 ft. Spruce S.38°15'E., 45.8 ft. crayon mark RP BT S9.
5 ft. Fir, N.89°30'W., 24.7 ft. crayon marked RP BR S4.
Corner stands 17 ft. east of creek course S by E.
8/5/43

FD. 0540-CA
1942-43

49

1/4 Corner for SEC. 5 and Sec. 32 of T20-12.
At 2+97 west of W.C. set:
1 1/2" I.P. and 2x2x4 Fir post crayon mkd. 2+97 W of W.C.S32, S5
Aug. 4,1943 W.G. Corbitt
From which bears:
8' Fir, N.65°W., 11.5 ft. crayon mkd. RP 35 ft. W of Creek course 5 W.
Field notes call for ridge SW at 23+10.
8/4/43

50

W.C. for 1/4 Cor. Sec. 5; and Sec. 32 of T20.12.
Field notes call for W.C. at 23.43
Found - Fir BT's at W.C. and from them relocated W. Corner as best I
could considering distances did not check exactly.
Set - 1 1/2" I.P. and 2x2x4 Fir post crayon mkd. WC S32 Aug.4,1943.
From which bears: S 5
Orig. 36" Fir, now 5', N.54°W. (Rec. S.65°W.), 25.08 ft. Slope
-39% =23.38 to base of nail crayon mkd. RP BR W.C. S5. Evidently
the orig. scribe marks were put on bark of tree and these were
destroyed when someone cut through blaze to solid wood in 1922.
Orig. 24" Fir, now dead snag without back, N.77°W., 13.0 ft. to nail.
Old blazed face on bark indicates scribe marks were put there.
6' Spruce N.65°E., 26.8 ft. 147.5 ft. -% =24.22 crayon mark RP BT W.C. S32.
8/4/43