

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 12 R.W.W.M.

ROSE CHAPMAN CO. EUBANK, ORE. 51981

60

Section corner for Sections 1 & 12; and Secs. 6 & 7 of T.21-11
Set - 2" Iron pipe with brass cap
from which:

- 10" Fir bears N.54°E., 15.8 ft.
- 12" Fir bears S.31°E., 9.7 ft.
- 10" Hemlock bears S.39°W., 38.8 ft.
- 12" Fir bears N.43°30'W., 9.8 ft.

All trees scribed. Corner falls in 'cat' road.

61

1/4 Corner for Sec. 12; and sec. 7 of T.21-11
Set - 2" Iron pipe with brass cap
from which:

- 14" Hemlock bears N.46°E., 17.9 ft.
- 18" Spruce bears S.48°30'W., 11.0 ft.

Both trees scribed.

10/13/79

Section corner for Secs. 2 and 1; and 35 & 36 of T.20-12

62

Found - broken 1 3/4" I.P. lying on the ground (unrecorded) from which:
a 48" fir stump bears N.78°E., 1.0 ft.

Set - Stamped 2" I.P. with brass cap

From which:

- 14" Fir bears N.21°30'E., 35.0 ft. scribed.
- 48" Fir stump bears N.78°00'E., 1.0 ft.
- 22" Fir bears S.51°15'E., 40.3 ft. scribed.
- 12" Hemlock bears S.13°00'W., 40.2 ft. scribed.
- 10" Spruce bears N.50°30'W., 53.8 ft. scribed.

Note: This corner was tied in by a Bonneville Power Administration crew on Dec. 2, 1948, at which time the I.P. was in place. The fir was a green tree, but was erroneously called a spruce by the crew. A copy of their field notes, Index No. A49-386A, may be obtained by contacting John Sink, Dept., of Energy, P. O. Box 3621, Portland Oregon 97208.

3/26/80

63

1/4 Corner for Sec. 1; and Sec. 36 of T.20-12

Found - 2" Alum. pipe and 45" Cedar BT stump, Ren. #17 C.S. 51/311.

Durham's new BT's are gone - probably destroyed during the subsequent logging.

In place - an Alum. tag on a 36" fir stump which bears S.47°W., 25.7 ft.

64

1/4 Corner for Sec. 1; and Sec. 6 of T.21-11

Set - Stamped 2" I.P. with brass cap from which:

- 12" Fir bears S.31°30'E., 45.2 ft. scribed
- 10" Fir bears N.25°00'W., 11.0 ft. scribed

1/4 Corner for Secs. 2 and 1.

Set - Stamped 2" I.P. with brass cap from which:

- 24" Alder bears N.23°30'E., 69.1 ft. scribed
- 18" Alder bears South, 20.2 ft. scribed.

65

1/4 Corner for Secs. 1 and 12.

66

Set - 2" I.P. stamped brass cap from which:

- 14" Fir bears S.89°15'E., 42.3 ft. scribed.
- 14" Fir bears N.8°30'W., 33.9 ft. scribed.

67

Section corner for Secs. 1, 2, 11 and 12.

Replaced 1 1/2" I.P. (unrecorded) with a 2" I.P. stamped brass cap
from which:

- 16" Spruce bears N.45°00'E., 26.2 ft. scribed.
- 72" Fir (snag) bears S.48°00'E., 27.7 ft. orig. BT.
- 14" Alder bears S.31°00'W., 43.8 ft. scribed.
- 10" Fir bears N.84°30'W., 32.4 ft. scribed.

Richard Hintz
October 1979
C.S. 58/176

Survey in progress:
in Secs. 1, 11, 12
and 13 of T.21
R. 12.

Will be filed
at a later date.

Filed as Survey #M79-30
and C.S. 58/140 3/80

Richard J. Hintz
For: Champion International and International Paper
March 1980
M 79 - 30 and C.S. 58/140

RE-FILED
INDEX NO. 104

RE-FILED
INDEX NO. #108