

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 12 R.W.W.M.

Richard J. Hintz
For: Champion Inter-
national and Inter-
national Paper
March 1980
M 79 - 30 C.S. 58/140

Section corner for Secs. 13, 14, 23 and 24.
Set - 2" I.P. with stamped brass cap from which:
36" Fir bears N.87°46'E., 162.9 ft. scribed.
52" Spruce bears S.58°00'E., 257.2 ft. to 50d nail in the face.
scribed. BT overhangs Franz Creek.

RE-RENEWED, SEE CORNER NO. 97

3/80

CONDITION REPORT ONLY - -

78

Section corner for Sections 22, 23, 27 and 26
Found - A 1 1/2" I.P. with a 2" pipe fitting cap protruding 18" from
ground marked "22 23" Monument is firmly set.
27 26

Search was made for original trees and trees in Ren. #1. None
were found.

A 56" D.B.H. I. Spruce bears N.51°E., 73.7 ft. scribed "S23 BT"
on a single blaze, unhealed and painted yellow.

A 38" D.B.H. I. Spruce bears S.56 1/2°E., 33.6 ft. scribed "S26
BT" on a single blaze, unhealed and painted yellow.

A 17" D.B.H. Alder bears S.41°W., 59.2 ft. scribed "S 27 BT"
T.21S R12W" as a bark scribe and painted yellow.

A 10" DBH Hemlock bears N.8 1/2°W., 12.3 ft. scribed "S22 BT"
on a single unhealed blaze painted yellow.

All trees are marked with International Paper Co. bearing tree tags and NOT
OF RECORD. NOTE: 11/80, Corner of record now. Map file # M 84 - 24 County
Surveyors records. 7/14/80

Stephen Flause
Dougl. Co. Surveyors
Office

Bill Stewart
July 14, 1980 Iron Pipe
C.S. 61/11 was FD 84
International
Paper Co. 7/1980
C.S. 63/161-28

1/4 Corner for Secs. 23 and 26.

Set - 1 1/4" I.P. with stamped brass cap
BT's - 12" Alder bears N.7°00'W., 7.9 ft. scribed.
12" Fir bears S.34°00'W., 5.9 ft. scribed.

Note - I made a thorough search for the iron pipe and brass cap as
shown being found in CS 51/333 and CS 54/30, but its position
was in the head of a draw which has now slid away to bed rock.
11/80

80

Witness Corner to Meander corner to Secs. 24 and 25.

Set - 2" Alum. pipe with stamped alum. cap on top of dike, left bank
of Smith River.
BT's - 60" Spruce bears N.78°30'E., 284.4 ft. to 50d nail in the face
48" double Spruce bears S.36°00'E., 197.9 ft. to 50d nail in
the face, scribed. BT is on top of river dike.

81

1/4 Corner for Secs. 24 and 25.

Set - 2" Alum. pipe with stamped alu. cap from which:
BT's - 18" Spruce bears N.46°00'W., 4.4 ft. scribed.
28" Maple bears S.39°15'E., 15.5 ft. scribed.

82

1/4 Corner for Secs. 26 and 25

Note - Corner falls on West shoulder of Smith River County Road #48,
NOT SET.

Reference monuments:

2" Alum. pipe with stamped alum. cap bears N.0°13'10"E., 30.00 ft.
2" Alum. pipe with stamped alum. cap bears N.89°46'50"W., 30.00 ft.

83

1/4 Corner for Secs. 25 and 36.

Set - 2" Alum. pipe with stamped alum. cap from which:
BT's - 10" Fir bears N.10°30'E., 5.8 ft. scribed.
6" Fir bears S.43°45'E., 5.7 ft. scribed.

84

Witness corner to M.C. Secs. 25 and 36.

Set - 2" Alum. pipe with stamped alum. cap from which:
BT's - 16" Fir bears N.87°30'E., 31.3 ft. scribed.
16" White Fir bears N.14°00'W., 18.2 ft. scribed

Richard J. Hintz LS 497
For: International Paper Co.
Menasha Corporation
U.S. Forest Service
Nov. 1980
M 84 - 24 A & B