

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 T. S. R. 12 R. W. W. M.

ROSE CHAPMAN CO., EUGENE, ORE. 97501

Richard Hintz  
For: International Paper  
Dec. 1991  
M 114 - 22

Section Corner for sections 13, 14 23 & 24.

97

Reset - Hintz's previous corner (map M 79-30; renewal # 77) was incorrectly set in 1980. the brass cap set in 1980 was pulled up and moved to its present position.

B.T.'s recalculated -

36" fir bears N.87 3/4°E., 175.3 ft. scribed

52" spruce bears S.59 1/2°E., 267.9 ft. to a 50d nail in face, scribed

No other references within limits in sec's 14 and 23.

Note - The position for this corner per M 79-30 was east, 12.52ft.

1/92

1/4 Corner for Sections 13 and 14.

98

Reset - Hintz's previous corner (map M 79-30; renewal # 75) was incorrectly set in 1980. The brass cap set in 1980 was pulled up and moved to its present position.

B.T.'s recalculated -

16" hemlock bears N.69 1/2°E., 25.9 ft. scribed.

14" alder bears N.3 3/4°W., 17.8 ft. scribed.

Note - The position for this corner per M 79-30 was East, 6.26 ft.

1/92

1/4 Corner for Sections 13 and 24.

99

Reset - Hintz's previous corner (map M 79-30; renewal # 76) was incorrectly set in 1980. The brass cap set in 1980 was pulled up and moved to its present position.

B.T.'s recalculated -

24" fir bears N.45 1/2°E., 17.5 ft. scribed.

18" fir bears S.63°W., 36.8 ft. scribed.

Note - The position for this corner per M 79-30 was East 6.25 ft.

1/92

Richard J. Hintz  
for Robert Cowan  
April 1975  
C.S. 58/47-2

1/4 corner for sec. 24 & 19

100

Fd. - Original BT, 30" Spruce, bears S.46°W., 26.4'

-1" I.P., bears S.67°55'W., 12.07'

Set - 1" I.P./B.C.?

1/4 corner for sec. 24 & 19

101

Fd. - 1" I.P. at 1/4 corner

BTs Fd.- 40", GLO Spruce stump, bears S.46°W, 26.4'(slope dist)

36", 1891 Glo Hemlock uproot remains, (1857 GLO 36" spruce),

bears S.9°E., 13.2' (slope dist)

38", Spruce stump, bears S.5°E, appox 15', Do. Co. Tag

Unrecorded Stuntzner BTs:

16", Alder, bears N.14°W., 35.8', bankscribed "1/4 S24 BT"

38", Cedar, bears S.17°W., 26.0', "X" chopped into it (tag

reads 34' at 64%)

35", Spruce, bears S.49°E., 10.9', "X" chopped into it (tag

reads N.57 1/2°W., 11')

19", Alder, bears N.28°E., 31.7', scribed "1/4 S19 BT".

Sec. corner to 13,24,18 & 19

102

Fd. - 3 1/4" Alum cap with 3/4" x 30" Alum rod

BTs Fd.- 19", Hemlock with a healed face, bears N.68°W., 27'

20", DF stump with a healed face, bears N.72 1/2°E., 26.8'

27", DF with a healed face, bears S.6 1/2°W., 8.4'

New BTs- 07", WF I scribe "S13 T21S R12W BT", bears N.1°W., 35'

1/4 corner for sec. 13 & 18

103

Fd. - 2 1/2" County Brass cap

BTs Fd.- 39", DF Stump with healed face, bears N.80 1/2°W., 61.7'

22", Spruce with healed face, bears S.82°E., 29.3' (record

S.83 3/4°E., 29.5')

New BTs- 21", Alder I scribe "1/4 S18 BT", bears N.41°E., 8.4'

18", Spruce I scribe "1/4 S18 BT", bears S.47°E., 35.8'

CLYDE MULKINS  
For I.P. Timberlands  
Jan 18 1994  
M118-62