

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 4 R. W. W. M.

✓ N. E. COR. JOHN SCOTT D.L.C. NO. 37
(F.B. No. 30 Page 40) 9
A Walnut 27" S. 6° 50' E. 394.0 ft.

✓ 1/4 COR. BMT. 27-28
F.B. 40 P. 20 10
RE-NEWED, SEE CORNER NO. 28
Fina 18" in diam. bears on line S. 18° W. remark same
Fir 40" in diam. S. 19° W. 1 link.

✓ CORNER SECS. 7, 8, 17, 18
Original bearing trees destroyed. By a former survey I
found marks on the S.W. bearing tree loc lying on the ground
from which I set a post & marked a fir 8" in. diam. which
bears N. 23° E. 9 links distance & marked T. 223. R. 47. S. 7 B.T.
A Fir 30" in diam. on line bears N. 55° W. 40 links &
marked T. 223. R. 47. S. 7 B.T.

RE-NEWED, SEE CORNER NO. 30
At this point I set a cedar post 3 inches square & 30 inches
long, properly marked. I remarked the above trees & adding
C. S. to both. trees also marked a fir 12" in diam., which
bears N. 43° W. 65 links dist. & marked T. 223. R. 47. S. 7 B.T.
C.S.
A Fir 14" in diam., which bears S. 5° W. 19 links dist.
& marked T. 223. R. 47. S. 7 B.T. C.S.

✓ RE-SET FOLLOWING CORNER Cor. Sec. 19-20-29-30 T. 23 S. R. 4 W.
Re-set from all 3 old pit's. All in end of E. except one in
Sec. 20. Drove 1" x 36" Iron Pipe & rock from which
marked a 8" Fir W. 69° E. (Note Boyer left out distance) I
re-marked all of the 3 old Fir trees. (See Area Three Book 8 pg 23)

SEC. 6 - 7 - 12 - 1 (west side of rd)
Found original bearing tree described as a Fir 20 in. S 18° E 68 lks. dist.
This tree is now a windfall, and the remaining trees are defaced and
burned by fire.
Found the original post in place. I replaced the post with a new post
5 in. x 5 in. R.F.W. long and an iron 1 1/8 in. x 16 in. from which I
scribed four new bearing trees.
14 in. Chinquapin S 30° E 14.5 ft., marked T 22 S, R 4 W, S 7 B T.
42 in. Fir S 7° 15' W 40.1 ft., marked T 22 S, R 5 W, S 12 B T.
38 in. Fir N 79° W 57.9 ft., marked T 22 S, R 5 W, S 1 B T.
18 in. Incense Cedar N 15° 30' E 46.0 ft., marked T 22 S, R 4 W, S 6 B T.

East 1/4 corner to section 6.
Two bearing trees:
16" D. Fir Bears S. 80° W. 31.0 ft.
20" Incense Cedar S. 67° W. 23.0 ft.
RE-NEWED, SEE CORNER NO. #163 14

Center 1/4 corner to section 36.
Set stake 4 inches by 4 inches by 36 inches for center of section 36 15

Center 1/4 corner Sec. 33.
Found by crossing true 1/4 lines.
Set corner and mark.
A N. C. 8 in. N. 10° E. 778 lks.
A Maple 2 1/2 in. S. 65° E. 249 lks.
An Ash 1 1/2 in. N. 15° W. 923 lks.
A W.O. 7 in. S. 23° 35' W. 469 lks. 16
RE-NEWED, SEE CORNER NO. 51

Jan. 1913
O. S. Foyer
F.B. 30, P. 40

O. S. Thell, Surveyor
Pyron DeVore
Arthur Woolley
V. 16 E. 55
1940
J. W. Wolford
A. Boyer
Apr. 8, 41

Blaine H. McCallitcuddy
Forest Engineer
March, 1952
C.S. 40/501

Gilbert A Gardner
for W. A. Woodard
Lumber co.
October 24, 1953.
File 41/221
Gardner
for W. A.
Woodard Lmbr.
carpentry.
Oct. 1953

Floyd Cole, Deputy
Harris Chalmers
Letson
March 2, 1915
Vol. 2, page 203.

F.B. 40

File, 41/223