

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 T. S. R 4 R. W. W. M.

FORM CHAPMAN CO., EUREKA, CALIF. 51881

Wilford N. Haines
For: Winslow & Baldwin
Maple Creek Ranch
Sept. 1976
M 61 - 79

1/4 Corner for Secs. 19 and 20,
Found - 1963 BLM brass cap-
BT's scribed in 1963 now stumps,
Found old BT scribed 50-100 years, now dead stub, bears
N. 87° 23' W., 35.0 ft.
Set - 5/8" Steel rod "rebar"

*FIND OK
5/17/11 M115-17*

RE-RENEWED CORNER NO. # 153 131

9/76

Charles Guile
For: Steve Reid
May 1977
M 64 - 45

1/4 Corner for Secs. 17 and 18
Found - Brass cap and pipe bent & twisted. Ren. #99
Also found 3/4" I.P. in hole.
Set - A 5/8" Iron rod in hole 6" deep.

132

5/77

Robert G. Dean
For: Don Jackson
May 12, 1980
M 83 - 37
C.S. 58/204 (N)

1/4 Corner for Sec. 33; and Sec. 4 of T.23-4
Found - 1" iron rod
31" Fir snag "1/4S" visible N.18°08'W., 39.3 ft. (orig. BT.
N.18°W., 39.6 ft.) See Ren. #50
44" Fir windfall, S.3°W., 50.4 ft. approx.
Haines T iron South 0.1 ft.
New BT's - 8" W. Fir scribed "BT" at base N.30°W., 15.3 ft.
8" W. Fir, S.34°37'E., 18.7 ft. scribed "BT" at base.

133

5/12/80

Center 1/4 Corner for Section 33.
Found - A 3/4" Iron rod bears S.1°26'E., 27.14 ft. See Ren. #51
A 3/4" iron rod bears N.1°23'E., 32.67 ft.
A 23" Double W. Oak, hollow scar, bears S.23°30'W., 311.3 ft.
(Rec. S.23°35'W., 303.6 ft.)
A 27" Ash, good scars bears N.15°06'W., 609.3 ft. (Rec. N.15°W.,
609.2 ft.)
Set - A square 1/2" iron spike in pagement from which a 1/2" iron rodd
bears S.0°05'10"W., 27.13 ft.

134

5/12/80

Burton Holt
For: Sun Studs
February 1981
M 86 - 56
C.S. 58/252 (n)

Witness Corner for
1/4 Corner for Secs. 4 and 5
Set - 1 1/2" x 36" I.P. with brass cap for Witness corner
1/4 Corner bears 3.18 ft. South.
BT's - 14" D. Fir bears N.72°30'E., 9.0 ft. scribed WC 1/4 S4 BT.
7" D. Fir bears S.62°W., 24.1 ft. scribed WC 1/4 S5 BT.

135

Center 1/4 Corner for Sec. 4
Set - 5/8" x 30" I. Rod
BT's - 17" Oak bears N.65°W., 36.0 ft. scribed C 1/4 S4 BT
16" D. Fir bears S.60°W., 38.4 ft. scribed C 1/4 S4 BT.

136

2/81

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Terrie Plouff, wit.
Dec. 21, 1981
C.S. 61/30

Sec. Corner common to Secs. 34, & 35, and Secs. 2, & 3 of T.23-4. **137**
Found - 1" x 1" x 36" "T" iron w/w. Haines Brass Button, Ren. # 123
firmly set, flush with the ground, from which:
BTs - 5", now 11" W. Oak bears S.73°W., 33.7-ft. Ren. # 123
(Rec. 33.3-ft.), with good scar visible.
12" now 20" Fir w/scribed "T" visible in prev- Ren. # 123
iously opened blaze bears S.40°E., 70.0-ft.
14" now 23" Fir w/large partially healed blaze Ren. # 123
with rotted face bears S.66°E., 69.2-ft.
Note - In my research for this cor., I could not find any information
as to the origin of the two Fir BTs. The only filed survey
prior to Ren.#123, is M 2-60 which does not mention either tree.
Set - I ref. the location of the found "T" iron & set a 1" x 30" I.P.
w/B.C. attached in its place. B.C. is stamped: "Douglas
Co Surveyor 1981 T22S R4W T23S S34 S35 S3 S2." I place
fd. "T" iron along East edge of B.C.
New Accessories - Power Pole #4-191 bears N.34°W., 154.0-ft. w/DCSO
BT tag attached.
4" Pole fence Corner bears S70°E., 6.3-ft. with DCSO BT tag attache
Note - See sketch in Ren. # 123 (C.S. 61/30) 12/21/81

*FD. B.C.
D. Pool
M115-78*