

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 22                      T. S.                      R 4                      R. W. W. M.

COLE-CHAPMAN CO., EUGENE, ORE. 91871

154

Daniel Baker  
C.S. 63/154  
5 - 13 - 94

1/4 COR SEC. 4 & 9  
Monument Pd. - Douglas County Brass Cap Dated 1958 - good cond.  
Accessories Pd. - 38" Cedar, N.14°E. 15 lks., - 1855 BT (uprooted)  
18" W.Fir, S.30°W. 25.3' - 1958 Do. Co. - rec.  
S.29 1/2°W., 25.'  
38" Cedar, S.25°W. 32.2' - 1959 Weyerhaeuser -  
updated & log removed.  
New Accessories - 10" D.Fir, N.17°E. 20.2' to "W" Nail.  
15" W.Fir, N.62°W. 9.7' to "W" Nail.  
21" W.Fir, N.84°E. 19.5' to "W" Nail.

155

Center 1/4 for Section 3  
Found - U.S.B.L.M Brass cap dated 1994.  
5" Yew, N.8°W., 2.6 ft. to spike - scribe visible.  
record: BLM tag reads S.18°E.  
15" Hemlock, S.39°W., 8.1 ft. to spike - scribe visible.  
record: BLM tag reads N.36°E.  
Set - 6 ft. fence post 1 ft. east.  
Note - Spikes were set this survey at side center.

166

1/4 Corner for Sec. 3, and Sec. 34 of T.21-4.  
Found - U.S.B.L.M. Brass cap dated 1980. Cond. report only  
17" White fir, N.2 1/2°E., 47.5 ft. to spike - visible scribe  
record: North, 47.5 lks. (1980 BLM)  
20" White fir, S.14 1/2°E., 44.8 ft. to spike - closed face  
record: S.18 1/2°W., 70 lks. (1980 BLM)  
Note - Spikes were set this survey at side center.

167

Section Corner for Sections 3, 4 & 33, 34 of T.21-4  
Found - U.S.B.L.M Brass cap dated 1980.  
13" Cedar, N.56°E., 19.7 ft. - closed face  
record: N.56°E., 30 lks. (1980 BLM)  
9" Cedar, S.53 1/2°E., 18.0 ft. - closed face  
record: S.53 3/4°E., 27 lks. (1980 BLM)  
15" Fir, S.56°W., 29.5 ft. - closed face  
record: S.55 1/2°W., 45 lks. (1980 BLM)  
8" Fir, N.33 3/4°W., 38.7 ft. - down and out.  
record: N.33 1/2°W., 59 lks. (1980 BLM)  
New BT- 7" Fir, N.52°W., 8.5 ft. to "W" nail  
scribed "T21S R4W S33 BT"

Section Corner for Sections 10, 11, 14 & 15  
Found - Douglas Co. Surveyor's Office Brass cap dated 1965, with 1957 monel pipe alongside. See renewal #108.  
40" Fir stump, S.48°E., 44.6 ft. to "W" nail - scribing  
visible. (rec. S.48°E., 44.6 ft. - 1963 Weyerhaeuser)  
20" Fir, N.24°E., 24.4 ft. - closed face.  
(rec. N.23°E., 23.5 ft. to "W" nail - 1963 Weyerhaeuser)  
New Accessories -  
13" Fir, S.78°E., 6.2 ft. to "W" nail - scribed "T22S R4W  
S14 BT"  
11" Alder, S.44°W., 8.4 ft. to "W" nail - scribed T22S R4W  
S15 BT"  
9" Fir, N.3°E., 13.1 ft. to "W" nail - scribed T22S R4W S11  
BT"

169

Daniel Baker  
C.S. 65/1-2  
9/11/95

Section Corner for Sections 29, 30, 31, 32  
Set - 2" x 38" iron pipe with brass cap marked "T22S R4W S29 S30  
S31 S32 PLS 1978 1995"  
New Accessories -  
9" Oak, S.30°E., 326.2 ft. to "W" nail, scribed "T22S R4W S32 BT"  
11" Ash, S.56°E., 462.2 ft. to "W" nail, scribed "T22S R4W S32 BT"  
8" Ash, S.22°W., 272.1 ft. to "W" nail, scribed "T22S R4W S31 BT"  
11" Ash, N.82°W., 512.8 ft. to "W" nail, scribed "T22S R4W S30 BT"

Daniel Baker  
For: Weyerhaeuser  
Sept. 1995  
M119 - 73

Daniel Baker, for Weyerhaeuser Co.  
Jan. 1995 M119 - 54