

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 4 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

65

Section Corner common to Sections 16 - 17 - 20 - 21.

GLO Survey Record 1856

Post	Gone
18" Fir N.37°E. 106 lks.	No Trace
20" Fir S.62°E. 36 lks.	Found rotted stump only
30" Fir S.60°W. 84 lks.	54" Fir Stump
60" Fir N.43°W. 143 lks.	Rotten widdfall, no scribing found.

County Survey Record 1928

Set 4" x 6" x 1/2" scribed cedar post, Post in place; scribing visible and "T" Iron Stke.
 8" Fir N.61 1/2°E. 41 lks. 20" Fir, healed faces
 30" Fir S.71 1/2°E. 11 lks. 36" Fir, scribing visible
 60" Fir S.58 1/2°W. 84 lks. 54" Fir Stump
 36" Fir N.29°W. 300 lks. 42" Snag; bark scribing plainly vis.

Referenced by Wm. L. Wilt (Plates & "W" nails only) Decl. 20°

20" Fir N.60°E. 27.4 ft.
 36" Fir S.85°E. 6.8 ft.
 14" Fir S.21°W. 29.2 ft.
 14" Fir N.62°W. 54.8 ft.

66

Section Corner common to Sections 17 - 18 - 19 - 20

GLO Survey Record 1856

Post	Gone
6" W.Oak N.10°E. 48 lks.	No trace; land cleared
60" W.Oak S.45°E. 122 lks.	50" Stump; bottom of upper face shows in stump cut; cut below scrbing.
18" W.Oak S.75°W. 149 lks.	No trace; land cleared.
20" W.Oak N.63°W. 74 lks.	Found remains Oak Stump only.

County Record 1928

Set 1" x 6" G.I. Pipe 5 1/2" in gr. Pd. 3/4" I. Rod; extends 6" above ground.
 12" Fir N.87 1/2°E. 47 lks. 22" Stump; lower healed scar visible.
 60" W.Oak S.45°E. 122 lks. 50" Stump
 14" B.Oak S.63 1/2°W. 29 lks. 26" B.Oak; healed scars visible.
 30" W.Oak N.68°W. 74 lks. Remains of old stump.

Referenced by Wm. L. Wilt (Plates & "W" nails only) Decl. 20°

10" W.Oak N.85°E. 50.2 ft.
 12" W.Oak S.63°E. 20.1 ft.
 26" B.Oak S.64°W. 14.9 ft.
 36" Fir Stp. N.31°W. 19.0 ft.

67

1/2 Corner common to Sections 17 and 20.

GLO Survey Record 1856

Post	Gone
20" Fir S24°E. 15 lks.	No Trace
24" Fir N.20°W. 65 lks.	No Trace

Set 1" aluminum pipe for cor. by single prop. method.

Referenced by Wm. L. Wilt (Weyerhaeuser Method with disc.#2149) Decl.20°

6" Fir S.51°E. 15.6 ft.
 6" Fir S.67°W. 36.1 ft.

68

Corner common to Sections 15, 16, 21 and 22.

GLO Survey Record 1855

Post	Gone, replaced by Haines "T" Iron.
10" Laurel N.23°E. 114 lks.	All evidence gone
10" Fir S.28°E. 118 lks.	44" Fir; chopped out, scrbing.vis.
8" Oak S.40°W. 127 lks.	All evidence gone
40" Fir N.72°W. 202 lks.	54" Fir

Referenced by Wm. L. Wilt (Plates & "W" nails only) Decl. 20°

28" Fir N.31°E. 37.7 ft.
 44" Fir S.28°E. 76.3 ft. Orig. BT.
 12" Fir S.12°W. 14.7 ft.
 54" Fir N.72°W. 133.4 ft. Orig. BT.

Weyerhaeuser Company
 Lester E. Calder by William L. Wilt.
 7/61 & 5/62
 Filed October 1962
 C. S. File No. 51/87

(SEE H. ENG)
 Weyerhaeuser Company
 Lester E. Calder by Robert Barta
 September 1962
 C. S. File No. 51/87

97