Douglas County Surveyor's Record of Government Corners Renewed

22 T. S. 5 R. W. W. M.

FORE-CHAPMAN CO. EUGENE, ORE. 81082

Vol. 3 Pg. 109
G.G. Stewart
D.C.S.
John Thomas
Chas.E.Remington
Witness
Jan. 23, 1922

✓N. E. COR. GOODELL D.L.C. #40 RE-RENEWED, SEE CORNER NO. #31
Find stone monument with cross on it. As corners sets in mass of brush etc. it is difficult to find. I remark Fir. 8
N.30°W., 14.0 ft.,
A 4" Fir S.76°E., 19.8 ft.

✓¼ COR. BET. SECS. 4-5 FB 52 PG20
I found a sandstone marked ¼S. C. S. from which as 111
Fir 10" S. 21°W. 14.4 ft.
Fir 12" N.24°30'E. 13.5 ft. 9
Stump of 24" Fir no scribe marks visible bears
N.72°E. 62.9 ft. no trace of other Govt. B.T.
I believe this corner was renewed by M.B.Germond but not recorded. (SEE FIELD BOOK 15 PG 29 for possible record)

Vol. 3, Pg. 176
J. W. Cole., C.S. Jan. 4-10, 1924
W. A. Sagaberd
J. Sagaberd
J. Grimm
Witnesses
Vol. 1 Pg. 18 FB 15-29

✓¼ COR. N. BOUNDARY SEC. 4 FB 52 PG 21
I renewed this corner from stump of large W. Oak N.51°W. 229 lks. and Fir stump S.55°W. 405 lks. both stumps badly decayed. Fence corner 15 ft. South and 10 ft. West. 98 10
I set an iron pipe 1" x 36" from which I mark
A. W. Oak 10" dia. S.50°50'W. 147.9 ft.
A. Fir 30" N.47°W. 66.8 ft.

✓¼ CORNER BET. SECS. 3-4 - FB 52 PG 24
I renewed this corner at a point where I found a fir stake marked ¼S. C. S. presumable set by Germond. from which RE-RENEWED, SEE CORNER NO. 54A
A Fir 30" dia. (chopped open by Germond but scribe 11
marks visible at this time) bears N.45°W. 93.0 ft.
no trace of other B. T.
I marked a Fir 12" S.5° 00E. 12.0 ft. ¼S. C.S., B.T.

✓¼ CORNER 28-29
Set stake from old Witness trees one down with marks, other standing marks gone. Marked new trees RE-RENEWED, SEE CORNER NO. 51
24" Fir S.77°W. 27 feet. 12
24" Fir S.59°E. 64.0 feet.

✓¼ SEC. COR. BETWEEN SEC. 31. T.22S. R.4W. SEC. 36 T.22S. R.5W.
Location identified from one original B.T. Set a stone
8" x 8" x 12" above ground marked X¼S. on top from which 13
Fir 50" diam., bears S.24°W. 36 ft., marked ¼S. 36 C.S. B.T.
Fir 44" diam., bears N.45°E. 96 ft., marked ¼S. 31. C. S., B.T. 102

SEC. CORNER ON SOUTH BOUNDARY OF SEC. 35
Location identified from original B.T. N.7°W., 70 lks. dist. down & badly rotted but part of scribe marks visible.
Oak stump N.51°E. 79 lks. dist. other B.T. all marks obliveated.
Drove a 1½" x 42" iron pipe 40" in ground for corner, from 14
which
Oak 6" diam., bears N.64°E. 31.0 ft. marked ¼S.35. C.S., B.T.
Fir. 8" diam., bears N.87°W. 27.0 ft. marked ¼S. 35. C.S., B.T. — SEE 1983 BLM RENEWAL Vol. 44 PG. 1766 —

✓¼ COR. BETWEEN 34 and 35
Both old bearing trees fallen but dim marks found on the SE. bearing tree (tree fallen and badly decayed). Set
a 7" x 10" x 14" stone and iron bar for ¼ Cor. Marked 44
¼ S. C. S. on Stone. Marked two bearing trees. RE-RENEWED, SEE CORNER NO. 15
8" W. Oak, S.30°W., 26 lks., marked ¼ S. B.T.C.S.
12 " B. Oak, N.10°E., 27 lks., marked ¼S. B.T.C.S.

Vol. 1 Pg. 18
Ben B. Irving Apr. 2, 1927
D.C.S.
N.E.Richardson
Loren Weber
Witness
Aug. 1940
C.S. V.16 E.55
L.W. Smith
H. L. Eppstein
C. S.

Vol. 1 Pg. 18
Ben B. Irving,
D.C.S.
N. E. Richardson
Loren Weber
Witness
Sept. 20, 1940
C.S. V.16 E.55

Oscar Thiele
No date
(prob. 1942)
Art Thomas Wit.
Chancey Smith Wit. Witness