

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 5 R. W. W. M.

FO. OK 4-91
D. BENTZ
M 113-70
FDOK
G. Riley
4/19/94
M 121-34

SEC. CORNER BETWEEN 8-9-16 & 17 *SEE FB. 49 Pg. 3*
Found a stake in place, scribed S 8, S 9, S 16, S 17.
Set an I. P. with a Brass Cap marked "County Surveyor's Office," **16**
T 22 S, R 5 W, Secs. 8, 9, 16, and 17", from which
36" B. Oak bears N 63° E 71.2 ft. dist.
22" Fir bears S 75° E 111.7 ft. dist.
24" B. Oak bears South 8.5 ft. dist. (scribed once when about 5" tree)
K. Coe. Found O.K. FEB. 1965 B.B.P.A

N. E. Richardson
Milo Godfrey
Les Kershner
March 24, 1948

S. E. CORNER DLC #40
Two O. B. T. standing, have been remarked
Set a 2" I. P. in a mound of rock, from which
8" W. Oak bears N 65° W 10.7 ft. dist., marked C. 40. **17**

FD. Pipe 2" BT. Bix
7/19/84 J. S. H. D
C.S. 23/9

N. E. Richard
March 24, 194

NW CORNER DLC #38
Found Rock Corner - identified from old Oak Witness tree,
N 5° W 72 lks., standing, scribed marks plain.
Reset corner rock, marked B. T. *SEE C.S. 39/167* **18**
16" D. Fir N 44 1/2° W 35.5 ft.
24" D. Fir S 64 1/2° W 39.7 ft.

April 6, 1948
A. R. Evans
Milo Godfrey
C.S. 39/167

1/4 COR. BETWEEN 8-9
Set 1" galv. iron pipe with a brass cap mkd. C. S.,
T 22 S, R 5 W, 1/4 S 8-9 from which
15" Chinquapin bears N 30 1/2° E 195.4 ft.
White Oak, O. B. T. bears S 30° E 28.7 ft. **19**

(SEE ALSO
THEIR'S BOOK 1
PAGE 9)

Feb. 11, 1948
N. E. Richardson
Dep. Onty. Surv
Godfrey
Kershner
Witnesses

1/4 Corner on the West line of Section 8.
Found:
Fir, 50 inches in diam., S. 85° E., 13.9 feet. *REN. #2*
Fir stump, N. 9° W., 54.8 feet. **118**
Set 5/8 inch rod. **20**
Marked two bearing trees:
Fir, 14 inches in diam., S. 60° W., 24.9 feet.
Fir, 18 inches in diam., N. 30° W., 27.0 feet.

Also, see
Vol. 2 Pg. 81

Mr. C. Thomson
February, 1955.
C. S. File No. 41/344.

Southwest corner section 8.
Found:
Cross on rock outcrop.
Laurel 18, S. 50° W., 14.5 feet.
Fir stump, N. 12° E., 17.1 feet. **21**
Marked:
Fir, 14 inches in diam., S. 34° E., 57.3 feet.
Fir, 8 inches in diam., S. 11° W., 30.4 feet.

1/4 section corner to secs. 11 and 14.
As recorded.
Replaced post with iron pipe. **22**
RE-RENEWED, SEE CORNER NO. 35

H. McCalliuddy
March, 1955.
C. S. File No. 42/33.

1/4 section corner to secs. 13 and 14.
Established corner half way between section corners.
Set 1/2" x 30" iron pipe, from which
28" Apple tree, N. 41° 41' E., 113.43 feet (nail in tree).
24" Oak, S. 23° 35' W., 189.45 feet (nail in tree). **23**
Light Pole, N. 9° 18' W., 347.19 feet.
Light Pole, S. 31° 03' E.,

RE-RENEWED, SEE CORNER NO. #174

QUESTIONABLE
Work?
SEE FILE

1/4 section corner between secs. 14 and 23.
Set 1" x 30" iron pipe half way between section corners in open
prairie - No bearing trees. **24**