

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 5 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

45

Section Corner to Sections 26, 27, 34, & 35.

Found - Two trees that I believe to be original BT's.

24" Redwood, now 36" Cedar N. 3°W. 19.8 ft. opened years ago, old face now rotted. I open lower scar which also shows rotted face. No scribing found, but I do find old axe marks. This BT. checks for size & ring count.

Also find base of Lare Fir Stump that would check bearing & distance for orig. S.W. BT. Bark now gone from stump, no scribing found.

Corner Checks calls to North & East.

Set Brass Cap at Corner marked S27|S26 T22S R5W, County Surveyor's Office, 1958

New BT's: 36" Cedar N. 3°W. 19.8 ft. rescribe S27 T22S R5W CS BT.  
14" W. Fir S.81°W. 38.4 ft. scribed S34 T22S R5W CS BT.  
18" R. Fir S.31°E. 62.0 ft. scribed S35 T22S R5W CS BT.  
4" Ewood N.50°E. 9.8 ft. scribed S26 T22S R5W CS BT.

RE-RENEWED, SEE CORNER NO. #154

FOUND O.K. FEB. 1965 B.B.P. J.H.

James W. Byron, Deputy County Surveyor  
M. Godfrey  
S. Bilow  
Feb. 24, 1958  
C. S. File No. 49/59

46

Section Corner to Sections 22, 23, 26, & 27.

Found - Orig. 60" now 65" Fir N.58°W. 16.1 ft. on old face, good scribing visible "22".

60" Fir down N.13°E. 99.0 ft., checks bearing & distance for orig. N.E. BT. Bark is covered, no scribing found. No trace of S.E. BT. found.

Set Brass Cap marked S22|S23 T22S R5W County Surveyor's Office, 1958.

New BT's: 8" R. Fir N.89°W. 38.2 ft. scribed S22 T22S R5W CS BT.  
11" R. Fir N.78°E. 13.7 ft. Scribed S23 T22S R5W CS BT.  
17" R. Fir S.76°E. 21.3 ft. scribed S26 T22S R5W CS BT.

FO. O.K. FEB. 1965 B.B.P. J.H. BY G. Bloom 12/80 M73-64

James W. Byron, Deputy County Surveyor  
M. Godfrey  
S. Bilow  
March 4, 1958  
C. S. File No. 49/59

47

Section Corner to Sections 27, 28, 33, & 34.

Found - Orig. 20" now 54" B. Oak S. 15°W. 97.7 ft., now down. I open & find good scribing "B /".

Possible Orig. S. E. BT., checks bearing & distance, now 40" Maple alive, but rotted inside. No scribing found.

No trace of Orig. N. E. & N. W. BT's.

Corner in E.W. Fence line.

Set Brass Cap at corner marked S28|S27 T22S R5W County Surveyor's Office, 1958.

New BT's: 10" W.O. S.56°W. 109.0 ft. scribed S33 T22S R5W CS BT.  
24" Maple N.32°W. 59.2 ft. scribed S28 T22S R5W CS BT.

Center Line old Pacific Hwy. bears East 89.0 ft.

RE-RENEWED, SEE CORNER NO. #185

FO. B.C. OK 12/80 G. Bloom M 79-64

48

South  $\frac{1}{2}$  Corner to Section 31.

Found:- Orig. 18" now 40" B. O. N.80°E. 608.5 ft. I open & find good scribing "S /".

No trace of Orig. N. W. BT.

Tie to N.  $\frac{1}{2}$  Corner Section 6, T23S R5W, for sketch see file 49/59.

Set Brass Cap at Corner marked: County Surveyor's Office, 1958

S.  $\frac{1}{2}$  S31 T22S R5W.

New BT's: 26" W. O. N.87 $\frac{1}{2}$ °W. 797.0 ft. scribed S $\frac{1}{2}$  S31 CS BT  
10" W. O. N.55°E. 436.5 ft. scribed S $\frac{1}{2}$  S31 CS BT.

FO. O.K. 2/1965 C.S. 5/101 B.C.

49

Section Corner to Sections 31 & 32 T22S R5W & Sec. 6, T23 S R5W.

Found - 8" now 19" R. Fir N.75°20'E. 228.4 ft. I open upper scar & find good scribing "W S." This recorded as renewed, 1901, by ring count. It was scribed about 1928, also the tree was 12" when scribed (Record 8").

Rotted Base of Fir that checks bearing & distance for N. W. BT. Find upper section of old rotted & scribed stake on ground.

Set Brass Cap at corner marked: S31|S32 T22S R5W County Surveyor's Office, 1958.

New BT's: 10" R. Fir bears N.11°W. 8.5 ft. scribed S31 T22S R5W CS BT.  
20" R. Fir bears N.74°E. 47.5 ft. scribed S32 T22S R5W CS BT.  
10" R. Fir bears S.44°E. 36.0 ft. scribed S6 T23S R5W CS BT.

Note - Sketch in file showing location of Brass Cap. No trace of Original BT's Found.

FO. O.K. Feb. 1965 C.S. 5/101 B.C.R.

E BY: Eugene Bloom 9/81 M 88-75