

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

98

1/4 Corner to Section 4, T22-5W. & Section 33, T21-5W.
Found - 2" Iron Pipe. (See Ren. #10)
Fir Stump N.47°W. 66.8 ft., bark scribing visible "33 21/5".
16" W.Oak S.51°W. 147.9 ft., shows very plain scar.
No trace of Original Bearing Trees.
20" Fir S.66°W. 30.0 ft., recently scribed. No Record.
New BT's: 38" D. Fir N.28°W. 20.0 ft. Mkd: 1/4 S33 CS BT. (This tree
in fence line, N. & S.)
DID NOT SET BRASS CAP.

Dec. 1, 1964

Milo E. Gaffrey, Deputy
Wm. Stoffel & M. Stone
Dec. 1, 1964
C.S. File 49/68

99

1/4 Corner to Sections 20 and 21.
Found - 30" Oak S.42°E. 120 lks.
Set - 1" x 1" x 36" T. Iron
Scribed - 13" Fir N.58 1/2°E. 56.7 feet
36" Inc. Cedar N.16°W. 84.7 feet.

COR. DESTROYED
BURNED & BULL DOZED
PER E. Bloom 12/9/60
Z.H.

1/4 Corner to Sections 29 and 30. *Fd. OK 4/94 BY PIESKE M-120-4*
Found - 12" Oak N.54°E. 186 lks. (now 24" Stump)
Scribed Stake in mound of Stone
Set - 1" x 1" x 36" "T" Iron by Stake
Scribed - 8" Fir N.85°W. 53.6 feet.
9" Fir N. 9°E. 4.0 feet.
There is a 28" B.Oak S.38°E. 9.6 feet and W. Oak (20")
N.51°W. 74.2 feet. Looks like they may have been
faced for BT's. Did not open either tree.

100

Wilford N. Haines
October 1964
C. S. File No. 51/305

101

Section Corner to Sections 17 - 18 - 19 - 20.
Found - Mound of Stone (One with an "X") from which
the 1/4 corner for sections 19 and 20 bears
S0°04'W. 2641.0 feet.
Set - 1" x 1" x 36" "T" Iron in Mound of Stone.
Scribed - 14" Fir S.69 1/2°W. 338.0 feet.

#186
Fd. OK 2/14/68
R. DEAN
C.S. 63/69

102

1/4 Section Corner to Sec. 36, T22-5W. & Sec. 31, T22-4W.
Found - 8" x 8" x 12" Stone at Corner Mkd: "X" 1/4 S" on top. *Ren. #13*
50" Fir, now 60", S.24°W. 36 ft., bark scribing visible.
44" Fir, now stump, N.45°E. 96 ft., bark scribing.
Set - Brass Cap along North Side Stone Mkd: T22S
1/4 R5W S36/S31 R4W
County Surveyor's Office, 1965
New BT's: 11" W.Oak N.38°E. 33.1 ft. Mkd: 1/4 S31 CS BT.
12" Fir N.80°W. 22.0 ft. Mkd: 1/4 S36 CS BT.
In Fence Corner.

Bruce R.
Rogers & Crew
Jan. 8, 1965
C. S. File
No. 53/101

103

Section Corner to Sections 3 - 4 - 9 - 10.
Found - "T" Iron in E - W. Fence Line Set By Haines (Ren. #68)
Corner is 45 ft. West of Road.
New BT's: 11" Fir N.22°W. 23.8 ft. Mkd: T22S R5W S4 CS BT.
13" Fir N.66°E. 4.5 ft. Mkd: T22S R5W S3 CS BT.
11" Madrone S.22°W. 25.5 ft. Mkd: T22S R5W S9 CS BT.
13" Fir S.53°E. 42.5 ft. Mkd: T22S R5W S10 CS BT.

Bruce R. Rogers, Deputy
Wm. Stoffel & Mike Stone
January 1965
C. S. File No. 53/101

104

1/4 Corner to Sections 33 and 34.
Found = Old Wood Stake & 1" plugged I. Pipe at Corner in E-W Fence.
24" B.Oak, now 33", Orig. BT. S.43°W. 10.6 ft., shows good scar.
12" W.Oak, now 15", chopped out, good scribing, "BT".
N. 45° E. 49.9 ft. (Ren. #6)
New BT: 15" D.Fir S.22°W. 27.4 ft. Mkd: 1/4 S33 CS BT.

REN. #6

Fd. OK 10/92
K. HOFFMAN M 116-2

Fd. 12/83
M 95-74
L. Smith

Fd. Oct. 1983
by R. Dean
M 95-64 AEB
FNO. OK 9-93 BY
BAKER M 118-10

RE-RENEWED SEE CORNER NO. #195

RE-RENEWED SEE CORNER NO. #186