

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 5 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

113

1/4 Corner to Sections 11 and 14.

Found - Brass Cap at Corner, See Ren. #35.

7" Fir, now 11", N.16°E. 51.2 ft., shows good scar.

34" Cedar, now snag, S.39°E. 73.0 ft., shows good scribing.

New BT: 10" Alder bears N. 51° E., 29.7 ft. Mkd: 1/4 S11 CS BT.

April 13, 1965

Bruce R. Rogers
& W. S. & M. S.
April 1965
C. S. File
No. 53/101

Sec. Cor. to Secs. 2 & 3, T22-5W. and
Secs. 34 & 35, T21-5W.

114

Found - Squared Stake at Corner.

Orig. 30" Fir, now stump S.33, E. 17.2 ft., scribe vis.

Orig. 14" Fir, down, N.54, W., chopped out & fd. scribe.

(14" W. Fir, now 19", N.21, E. 31.3 ft., scribnd. vis.)

(28" Fir N.21, W. 9.0 ft. scribing visible.) Ren. #18

(46" Fir S.22, W. 44.2 ft., scribe visible.) #18

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
T21S 1965

S 34	S 35	R5W
S 3	S 2	
T22S		

FO. OK 10/88
D. WELLMAN
M 107-26

B R
R O
U G
C E
E R
S, Deputy

1/4 Corner to Sections 12 and 13.

Found - Orig. 40" Fir N.7, E. 71.9 ft. prev. opened,
scribing visible.

Orig. 8" Fir, now rotten stump, scribing visible.

3/4" Alum. Pipe has been set at the intersection

of the record distances, making the bearing to the

40" Fir N.5, E.

New BT's: 30" Fir N.82, E. 26.7 ft. Mkd: 1/4 S12 CS BT.

10" W. Fir S.43, W. 39.4 ft. Mkd: 1/4 S13 CS BT.

115

May 1965
C. S.
File
No. 53/101

RE-RENEWED, CORNER NO. #176

FO. OK 12/87
D. PEEL
M 105-27

Section Corner to Sections 13 - 14 - 23 - 24.

Found - Corner as described by McGillicuddy. (Ren. #26)

Burnt stumps fit good for bearing & dist. & appear
to have been about the right size.

3/4" Iron Pipe in 4 way Fence.

McGillicuddy didn't scribe any trees.

New BT's: 12" D. Fir S.43°E. 18.0 ft. Mkd: T22S R5W S24 CS BT.

10" D. Fir N.32°W. 18.0 ft. Mkd: T22S R5W S14 CS BT.

13" D. Fir S.25°W. 33.1 ft. Mkd: T22S R5W S23 CS BT.

116

Bruce R.
Rogers, Deputy
Wm. S. & M. S.
July 1, 1965
C. S. File
No. 53/101

117

1/4 Corner to Sections 9 and 10.

Found - 1/2" Iron Rod with Eye on top as recorded in Ren. #88.

Orig. 6", now 30" Fir N.56°W. 16.5 ft., find "S" scribe
& reverse face & scribe where BT. would be about 6".

Other Bearing Tree new gone.

New BT: 5" Laurel S. 49° E. 10.0 ft. mkd: 1/4 S10 CS BT.

No other trees available, corner lies on steep west slope
of hill in dense brush.

RE-RENEWED, CORNER NO. #187

FO. OK W. HAINES
5/82
M 92-31

1/4 Corner to Sections 7 and 8.

Found - 5/8" Iron Rod as recorded in Ren. #20.

18", now 25" Fir N. 30° W., 27.0 ft., good scar, alive
and "S" scribe in wood. "W" Nail in base of tree.

Orig. S. E. BT. still alive but burned out.

New BT: 7" D. Fir N.24°E. 31.5 ft. Mkd: 1/4 S 8 CS BT.

Note - This corner lies on brushy, steep East slope approximately
250.0 feet East of top of ridge.

118

Vernon "Ray" Tracy
Mike Darby - Mike Stone
Terry Connell
Aug. 3, 1965
C. S. File No. 53/101