

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Corner to Sections 5 and 6 only, N. Boundray T. 23 - 5W
Set 1" x 1" x 36" T. Iron

Scribed: 8" Fir S. 01° E. 26.2 ft.
6" Fir S. 06° W. 27.5 ft.

RE-RENEWED, SEE CORNER NO. #190

127

Standard 1/4 Corner to Section 5, N. Boundrey T. 23 - 5W
Set 1" x 1" x 36" T. Iron scribed:

16" Fir S. 32° W. 34.9 ft.

Found - Orig. 10" Fir S. 28° W. 201 lks., now 36"

128

Corner to Sections 5 & 4 only, N. Boundary T. 23 - 5W

Found - Orig. 18", now 38" Fir Stump, previously opened,
shows good scribing "5".

S.W. BT. gone

Angle Iron Set by Haines. See M16-3 Ren#31 (of T. 23-5)

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959

T22S R5W

S 5/8 4

T23S

New BT's: 12" R. Fir bears S. 45° E. 89.4 ft. scribed S4 T23S R5W CS BT.

8" R. Fir bears S. 19° W. 14.0 ft. scribed S5T23S R5W CS BT.

Note - Corner is at West edge of old Log Road.

129

#153

North 1/4 Corner to Section 1 only, T. 23 - 5W

Found - Orig. 28", now 40" B.Oak S. 36° W. 36.3 ft. Shows good scars.

Orig. 18" S. 46 1/2° E. 66.0 ft. B. Oak. Previously opened.
shows good scribing "S1".

Also find 12" B.Oak bears S. 39° W. 6.9 ft., shows scribing,
(See BBI renewal, 1940) (Ren. #2 of T23-5)

Find 1/4" x 1 1/2" Strap Iron at corner which is under N.S. Fence.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960,
North 1/4 S1 T23S R5W.

New BT,s: 6" R.Fir bears S. 15° W. 14.4 ft. scribed N 1/4 S1 CS BT.

5" R. Fir bears S. 60° E. 36.7 ft. scribed N 1/4 S1 CS BT.

130

Township Corner

R	T 21 S	R
5	S 36 S 31	4
W	S 1 S 6	W
T 22 S		

131

Found - 3/4" Iron Pipe & 4"x4" Post with scribing visible laying beside
the I.P., See Ren. #11, T21-5W. Ren. #96

30" D.Fir BT., face visible, bears S. 25 1/2° E. 6.0 ft. (Rec. 5.0 ft.)

34" D.Fir BT., face visible, bears N. 42 1/2° E. 27.8 ft. (Rec. 26.4 ft.)

34" D.Fir BT., face visible, bears N. 9 1/2° W. 52.5 ft. (Rec. 51.7 ft.)

28" D.Fir BT., scribes visible bears S. 21 1/4° W. 60.7 ft.

40" Orig. D.Fir BT., burned stub, bears S. 11 1/2° W. 132.0 ft.

Set Brass Cap Mkd: T21S, T22S, R5W, R4W, S36, S31, S1, S6, 1972.

8/30/72

1/4 Corner to Sec. 1, R5W. and Sec. 6, R4W.

Set - Brass Cap Mkd: T22S, R5W, R4W, WM

S 1, S 6, 1/4 S 1972

Found - 30" Orig. Doug. Fir BT., scribing partially visible, bears
N. 80° W. 24.4 ft.

I scribed: 22" D.Fir "1/4S S6 BT" bears N. 82° E. 9.9 ft.

12" D.Fir "1/4S S1 BT" bears S. 78 1/2° W. 42.0 ft.

8/30/72

132

Willford N. Haines
For Yoncalia Lumber Co.
June 1960
Map file M 19 - 6

C. S. File 49/42

James W. Byron, Deputy Co.
Surveyor
Kilo Godfrey, Clete Putnam
January, 1960
G. S. File No. 49/42

MARCH 71

Bruce A. Shaner
For: U.S. B. L. M.
Map File M 42 - 68